

CATERPILLAR MACHINE PRICE LIST

AP1055F

AP1055F TRACK ASPHALT PAVER
 MINNEAPOLIS, MN, USA (SAP)

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

- CAT C7.1 inline 6-cylinder, turbocharged diesel engine
- Air cleaner, dry-type dual element with integral precleaner
- Air-to-air after cooler (ATAAC)
- Belt, automatic tensioner
- Demand fans (2)
- Diesel particulate filter
- Fuel filter / water separator
- Fuel priming pump, electric
- Propel system - direct hydrostatic, dual path drive, electronic control
- Dual braking systems(service & parking)
- Dual propel pump and motor system
- 2-speed planetary, 1-speed motor
- Propel modes, pave/travel/maneuver
- Speed control system
- Track undercarriage, mobil-trac system
- Automatic track tensioning, hydraulic
- Belts, rubber, 457 mm (18 in) wide
- Fully bogied undercarriage with rubber coated steel mid-wheels

ELECTRICAL

- Alarm, back-up
- Alternator, 100-amp
- Batteries, two maintenance free, 1400 CCA each
- CAT ET diagnostic connector
- Integrated high performance generator
- Horn, forward warning
- Machine security system wire-ready
- Product link ready
- Remote jump start receptacle
- Starting and charging system, 24-volt
- Plug and play aftermarket grade and slope ready machine wiring

OPERATOR ENVIRONMENT

- Electronic monitoring and warning system with advanced element diagnostics
- Automatic engine speed control
- Dual, swing-out operator stations
- Control and propel consoles, tilting
- Cup holder
- Ground speed indicator
- Propel lever with speed control dial
- Steering wheel, spring return
- 12 V aux power port
- Hopper wing control, independent
- Hour meter
- Instrumentation, dual LCD touchscreens
- Lockable vandalism guards

- Platform handrails / guardrails
- Power assist steering
- Throttle control, high/low idle,
- Eco-mode and variable, electronic

APPLICATION SPECIFIC COMPONENTS

- Adjustable height augers, hydraulic cast ni-hard steel, split segment, 406 mm (16 in) diameter
- Electronic auger/feeder control system
- Gateless feeder system
- Manual override
- Reversible
- Variable speed
- Heavy-duty feeder flight bars, forged steel, bushed roller chain
- High-hardness, abrasion resistant drag pans, replaceable
- Outboard feeder drives
- Remote mounted bearing lube points

FLUIDS

- Extended life coolant with protection to -37C (-35F)

OTHER STANDARD EQUIPMENT

- Doors, service access, hinged, locking
- Filters, hydraulic, grouped
- Fuel tank with sediment drain 348 L (92 gal)
- Grouped lube points
- Pressure test ports, hydraulic, quick-connect
- Screed counter balance
- Screed lock pins
- Sight gauges
- engine coolant
- pump drive
- material feed planetaries
- Slow moving vehicle sign (for AM-N)
- S.O.S. sampling ports
- Sound-suppression insulation kit
- Steering guide (1)
- Tow point indicator scales, lower
- Vandalism protection caplocks

CATERPILLAR MACHINE PRICE LIST

AP1055F

AP1055F TRACK ASPHALT PAVER MINNEAPOLIS, MN, USA (SAP)	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the
 Base Order Management program.**

377-9354	AP1055F MTS ASPHALT PAVER 31,782 LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	\$412,090
-----------------	---	------------------

OP-3523	AP1055F MISC MATL 0 AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	NC
----------------	---	-----------

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0		NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.			
OP-9003	LANE 3 ORDER	0		NC

FEATURE PACKAGES

HOPPER

L	505-9954	HOPPER, STD ENTRY, LOW SIDE	0	NC
		Hopper provides a minimum front entry height on the hopper wing of 605 mm (23.8"). The inner width of the hopper is 3224 mm (10' 6.9"). The hopper has a capacity of 7.5 cu m (264.8 cu ft). Hopper has a lower side profile for improved visibility into the hopper.		
L	504-6957	HOPPER, LOW ENTRY, LOW SIDE	0	NC
		Hopper provides a minimum front entry height on the hopper wing of 571 mm (22.5"). The inner width of the hopper is 3492 mm (11' 5.5"). The hopper has a capacity of 7.85 cu m (277.2 cu ft). Hopper has a lower side profile for improved visibility into the hopper.		

HOPPER APRON CONTROL

L	463-6580	APRON, MAN FOLD STD ENTRY	172	NC
		Manual raise hopper apron for easy material clean-out. Apron provides a minimum front entry height of 572 mm (22.5"). ONLY FOR USE WITH: 505-9954 HOPPER, STD ENTRY, LOW SIDE		
L	397-1175	APRON, MANUAL FOLD	175	NC
		Manual raise hopper apron for easy material clean-up. Apron provides a minimum front entry height of 529 mm (20.8"). ONLY FOR USE WITH: 504-6957 HOPPER, LOW ENTRY, LOW SIDE		
L	547-8093	APRON, STR HYD FOLD, STD ENTRY	0	\$5,130
		Hydraulically actuated hopper apron folds straight across the front and contains material after truck dump and while raising hoppers. Provides a minimum center entry height of 577 mm (22.7") and a side entry height of 616 mm (24.3"). ONLY FOR USE WITH: 505-9954 HOPPER, STD ENTRY, LOW SIDE		
L	559-5892	APRON, STR HYD FOLD, LOW ENTRY	0	\$5,130
		Hydraulically actuated hopper apron folds straight across the front and contain material after truck dump and while raising hoppers. Provides a minimum center entry height of 527 mm (20.75") and a side entry height of 587 mm (23.1"). ONLY FOR USE WITH: 504-6957 HOPPER, LOW ENTRY, LOW SIDE		

HOPPER FLASHING

L	459-6760	FLASHING, MAN FOLD STD ENTRY	78	NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of bumper. ONLY FOR USE WITH: 463-6580 APRON, MAN FOLD STD ENTRY		
L	415-7317	FLASHING, MANUAL FOLD	115	NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of hopper. ONLY FOR USE WITH: 397-1175 APRON, MANUAL FOLD		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

HOPPER FLASHING (Cont.)

L	505-9953	FLASHING, STR HYD FOLD SE 0		NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of hopper.		
		ONLY FOR USE WITH: 547-8093 APRON, STR HYD FOLD, STD ENTRY		
L	505-5879	FLASHING, STR HYD FOLD LE 0		NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of hopper.		
		ONLY FOR USE WITH: 559-5892 APRON, STR HYD FOLD, LOW ENTRY		

TRUCK INTERFACE

L	416-4116	PUSH ROLLER, OSCILLATING 1,200		\$4,235
			1,200	\$4,235 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER		
		Oscillating, solid push roller on a fore-aft adjustable pivot for centering truck and to assist steering during unloading.		
		Includes scrapers to prevent material build-up.		
		CANNOT BE USED WITH: 396-8984 HITCH, HYDRAULIC TRUCK		
L	396-7137	HITCH, HYD PREP, TRACTOR 10		\$1,430
			10	\$1,430 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER		
		Includes hydraulic lines required to accept truck hitch.		
		Recommended if a future field installed truck hitch is likely.		
		ONLY FOR USE WITH: 416-4116 PUSH ROLLER, OSCILLATING or 396-8984 HITCH, HYDRAULIC TRUCK		
L	396-8984	HITCH, HYDRAULIC TRUCK 1,050		\$17,230
			1,050	\$17,230 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER		
		Truck hitch (clamp arms with rollers) to hold truck to paver when unloading. Actuated from operator's console.		
		Includes scrapers to minimize material accumulation.		
		Also includes truck hitch valve and hydraulic hoses.		
		REQUIRES: 396-7137 HITCH, HYD PREP, TRACTOR		

MAINFRAME EXTENSIONS

L	416-4111	EXTENSION, MAINFRAME, POWER 275		\$6,410
			275	\$6,410 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER		
		Pair of hydraulically powered mainframe extensions to direct material delivery to endgate and facilitate frequent screed width changes. Extends 0.46 m (18 in) past mainframe.		
		CANNOT BE USED WITH: CONTROL, FEEDER, PADDLE		
		CANNOT BE USED WITH: NON-COMMERICAL WIDE WIDTH PAVING PACKAGES		
		CANNOT BE USED WITH: EXTENSIONS 2'6" MAINFRAME		
L	423-7851	MAINFRAME, NO POWER EXTENSION 15		NC
		Cover plates required when no power extensions are selected.		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

AUGER EXTENSIONS

P	416-4109	EXTENSION, 6" AUGER, PAIR 55 ALSO AVAILABLE ON MISCELLANEOUS ORDER For paving base tractor width to base tractor width plus 1.2 m (4 ft). Includes a LH and RH 152 mm (6") auger extension. FOR USE WITH: ALL SCREEDS AND ALSO FOR TRACTORS ORDERED WITHOUT A SCREED TO MEET MINIMUM PAVING REQUIREMENT FOR MOST APPLICATIONS.		\$1,005 NI
P	438-6252	AUGER 18" EXTENSION PER SIDE 195 ALSO AVAILABLE ON MISCELLANEOUS ORDER Recommended if paving base tractor width plus 1.2 m (4 ft) to base tractor width plus 1.8 m (6 ft). Includes a pair of (left and right) of 152 mm (6") and a pair (left and right) of 305 mm (1') auger extensions. RECOMMENDED FOR USE WITH: REAR MOUNT SCREEDS w/o Wide Width Paving packages.		\$2,425 NI
P	416-4110	KIT, AUGER AND MAINFRAME EXT 270 ALSO AVAILABLE ON MISCELLANEOUS ORDER Recommended if paving base tractor width plus 1.8 m (6 ft) to base tractor width plus 2.4 m (8 ft) wide. Includes a pair (left and right) of 152 mm (6") auger extensions, two pairs (left and right) of 305 mm (1') auger extensions and a pair of foldable, hinged 610 mm (2') mainframe extensions to facilitate frequent screed width changes. RECOMMENDED FOR USE WITH: ALL SCREEDS w/o Wide Width Paving packages.		\$5,290 NI

SCREED INTERFACE PACKAGES

L	416-4120	ADAPTER, VIBE SCREED 0 Provides hydraulics for vibe-only screeds. No provision for tamper systems. CANNOT BE USED WITH: 522-1492 SCREED, SE60 VT XW		NC
L	396-7127	ADAPTER, TAMP/VIBE SCREED 108 Provides hydraulics for vibe system plus pump, valve and hoses for tamper system. Works with tamper and vibe screeds.		\$2,060

WASH DOWN SYSTEMS

L	399-8387	TANK, WASHDOWN 70 ALSO AVAILABLE ON MISCELLANEOUS ORDER 30 L (8 gal) tank with integral pump mounted below deck on RH side. Intended for use with ecological cleaning fluids. Includes pump.	70	\$3,095 \$3,095 NI
L	399-8386	PUMP, DIESEL 10 FOR USE WITH LANE 3 ONLY Provides diesel fuel supply for pressurized washdown system, taken directly from paver fuel tank.		\$1,520
L	327-9167	COVER, NO WASHDOWN 0		NC

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
POWERTRAIN				
ENGINE				
L	391-0832	ENGINE, TIER 4F EPA/STG IV EU 0 168KW T4F Certified Engine, after treatment and DEF system.		NC
UNDERCARRIAGE				
MTS UNDERCARRIAGE				
L	267-5625	TRACK, MTS, TREADBAR 0 FOR USE WITH LANE 3 ONLY Mobil-trac rubber belts with lugs. 62 mm (2.4 in) thick.		\$22,420
L	289-8492	TRACK, MTS, SMOOTH 0 Mobil-trac rubber smooth belts. 58 mm (2.3 in) thick.		\$22,820
ELECTRICAL				
LIGHTING				
P	424-0927	LIGHTS, WORKING 10 Four 24V halogen floodlamps. Two front and two rear facing.		\$760
P	399-3169	LIGHTS, ROADING 15 Includes 2 front headlamps with turn signals, 2 rear floodlamps, 2 rear turn signals with brake lamps.		\$1,215
FEEDER CONTROL SENSORS				
P	416-1465	CONTROL, FEEDER, PADDLE 40 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Two, proportional, contacting paddle sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed. Located at end of augers. CANNOT BE USED WITH: 416-4111 EXTENSION, MAINFRAME, POWER		\$2,365 NI
P	416-1467	SENSOR, FEEDER, SONIC 20 ALSO AVAILABLE ON MISCELLANEOUS ORDER Two, proportional, non-contacting sonic sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed. Located at end of augers.		\$3,890 NI
P	416-1468	SENSOR, AUG SONIC, CONV PADDLE 60 ALSO AVAILABLE ON MISCELLANEOUS ORDER Two, proportional, non-contacting auger sonic sensors and two proportional conveyor paddle sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed. Located at end of augers.		\$6,260 NI
P	465-1275	SENSOR, AUG SONIC, CONV SONIC 25 ALSO AVAILABLE ON MISCELLANEOUS ORDER Four, proportional, non-contacting auger and conveyor sonic sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed.		\$7,650 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

STEERING CONTROL

L	416-4118	STEERING, SPRING RETURN	5	NC
		Conventional type, spring return controlled steering wheels.		
L	416-4119	STEERING, FRICTION	10	\$4,515
		Operator adjustable steering wheel brake holds the steering wheel in the desired position to maintain the selected turning radius.		

DECEL PEDAL

P	416-1453	PEDALS, DECELERATOR	2	\$1,725
			2	\$1,725 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER Two decelerator pedals, one for each operator station, that provide dynamic machine speed control without having to decrease the propel speed setting.		
L	416-1454	COVER, NO DECEL PEDAL	5	NC
		No provision for decel pedals.		

SEAT

L	416-1446	SEAT, VINYL SUSPENSION	140	NC
		Seats, vinyl, suspension, flip up armrests. Retractable 51 mm (2 in) seat belt.		
L	416-1447	SEAT, VINYL, DELUXE	150	\$1,475
		Pneumatic suspension vinyl seats with extendable flip-up armrests. Heated lumbar support and retractable 51 mm (2 in) seat belt.		

VENTILATION SYSTEM

Required for U.S. market only

L	396-7158	VENTILATION SYSTEM, NO CANOPY	290	\$8,350
		Asphalt fumes extraction with hydraulically driven fan.		
L	396-7159	VENTILATION SYSTEM, CANOPY	290	\$8,350
		FOR USE WITH LANE 3 ONLY Asphalt fumes extraction with hydraulically driven fan. REQUIRES: HARD TOP CANOPY		

TECHNOLOGY PRODUCTS

PRODUCT LINK (Must Select One)

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

P	461-2627	PRODUCT LINK, SATELLITE PL631	10	\$432
		Product Link Pro series PL631 uses satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

PRODUCT LINK (Must Select One) (Cont.)

P	461-2626	PRODUCT LINK, CELLULAR PL641 10 Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
P	497-3499	PRODUCT LINK, SATELLITE PLE631 0 FOR USE WITH LANE 3 ONLY Product Link Elite series PL631 uses satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$575 NET
P	497-3500	PRODUCT LINK, CELLULAR PLE641 0 FOR USE WITH LANE 3 ONLY Product Link Elite series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link users applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		\$264 NET

CONTROL CYLINDERS

L	417-6766	CYLINDER KIT, STANDARD 0 16" Auger segments, tow arm group, standard auger, tow point and screed lift cylinders.		NC
---	----------	--	--	----

OTHER ATTACHMENTS

COMMISSIONING SUPPORT

NOTE: It is recommended that startup and commissioning of machines be included as part of the machine sale. The net charge covers a three day commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the online request form.
URL:<https://dealer.cat.com/PavingOnDemand>

OP-2586	COMMISSIONING, NEEDED 0		\$6,330 NET
			\$6,330 NI
			NET
	ALSO AVAILABLE ON MISCELLANEOUS ORDER Commissioning Needed, trained personnel are required to properly commission the machine.		
OP-2587	COMMISSIONING, NOT NEEDED 0		NC
	Commissioning, Not Needed, dealer personnel are available to properly commission the machine.		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

INSTRUCTIONS

PICTOGRAPH FILMS

L	416-4121	INSTRUCTIONS, NORTH AMERICAN 0 ANSI picto warning decals using symbols plus the word "WARNING", as required for the USA.		NC
---	----------	--	--	-----------

PAINT

L	567-0751	PAINT, STANDARD, ANSI/ISO 0 Provides standard Caterpillar Yellow and Black paint scheme. Select this option for when custom paint is not desired. Films are provided in the pictograph film selection above.		NC
L	566-2438	PAINT, CUSTOM, ANSI 0 Machine is provided with required safety and regulatory ANSI films installed, and provides necessary loose films for application by the dealership after custom paint is applied. ONLY FOR USE WITH: 416-4121 INSTRUCTIONS, NORTH AMERICAN		\$204

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

ELECTRICAL

POWER DISTRIBUTION

Maximum of one power supply per order.

P	416-2013	PANEL, POWER SUPPLY	90	\$6,620
			90	\$6,620 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER Electrical distribution panel with a total output of 6.6 kVA continuous with 8 kVA start-up capability, protected by a circuit breaker at the panel, provides power for ex-factory installed lighting and customer work tools. Includes eight 120 V outlets. Mounted on RH side of safety railing behind operator station.		

LIGHTING

P	198-8284	LIGHT, HAZARD	15	\$740 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER LED amber beacon light mounted on a 3' mast with coil cord and connector. CANNOT BE USED WITH: 416-2202 HARD TOP CANOPY		
P	363-7444	LIGHT, HAZARD, CANOPY	0	\$339 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Two LED amber beacon lights mounted to the hard top canopy. ONLY FOR USE WITH: 523-4277 WIRING, LIGHTS/HAZARD READY		
P	418-0539	LIGHTS, HID/LED, CANOPY	15	\$1,660
			15	\$1,660 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Six LED lights, two forward facing and four rear facing, mounted to the hard top canopy. ONLY FOR USE WITH: 523-4277 WIRING, LIGHTS/HAZARD READY		
P	523-4277	WIRING, LIGHTS/HAZARD READY	0	\$354
			0	\$354 NI
		FOR USE WITH LANE 3 ONLY Wiring and mounting plates installed in hard top fiberglass canopy to accept LED lights for night paving and amber beacons. REQUIRES: 416-2202 HARD TOP CANOPY		

OPERATOR ENVIRONMENT

OPERATOR PROTECTION

L	416-2202	HARD TOP CANOPY	640	\$9,770
			640	\$9,770 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Hardtop canopy to provide paver operator sun and rain protection. Raises or lowers by folding manually. ONLY FOR USE WITH: 396-7159 VENTILATION SYSTEM, CANOPY or 396-7160 COVER, NO VENTILATION		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

OPERATOR PROTECTION (Cont.)

L	416-4103	WINDSHIELD, DUAL WINDOW	80 80	\$7,160 \$7,160 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER ONLY FOR USE WITH: 416-2202 HARD TOP CANOPY and 396-7159 VENTILATION SYSTEM CANOPY		
P	187-6649	UMBRELLA, CAT	20	\$179 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER One umbrella to provide paver operator sun and rain protection. Measures 54" x 54" and is collapsible. Includes support shaft and mounting hardware.		

TECHNOLOGY PRODUCTS

GRADE AND SLOPE CONTROLS

P	416-2003	CONTROL, BASE CAT G&S SYSTEM	0 0	\$8,280 \$8,280 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER Cat Grade and slope controller, power supply, harness, and mounting provisions for grade sensors. User interface integrated in existing screed displays. Only LANE 2 and 3 machine orders with a screed are calibrated from the factory. FOR GRADE/GRADE OPERATION MUST HAVE TWO GRADE SENSORS FOR GRADE/SLOPE OPERATION MUST HAVE ONE GRADE SENSOR AND SLOPE SENSOR. MUST BE ORDERED WITH A TRACTOR OR SCREED. NI IS FOR SCREED ORDERS ONLY		
P	362-8687	SENSOR, SLOPE	20	\$2,820 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes one slope sensor located on transverse beam at front of screed with mounting hardware. Connects to main CAT G&S wiring harness. FOR GRADE/SLOPE OPERATION MUST HAVE ONE SLOPE SENSOR AND ONE GRADE SENSOR ONLY ONE SLOPE SENSOR PER MACHINE ORDER ALLOWED ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		
P	416-2006	SENSOR, GRADE, SONIC	50	\$4,600 NI
		ALSO AVAILABLE ON MISCELLANEOUS ORDER Contact-free tracing of ground or stringline with self-averaging to minimize effect of short surface irregularities and objects. Includes one sonic tracer consisting of five maintenance-free ceramic sensors with automatic temperature compensation, coily cable, sensor pole, two support arms and mounting hardware. Unit is 28 cm (11 in) long. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

GRADE AND SLOPE CONTROLS (Cont.)

P	459-6770	SENSOR, GRADE, SONIC, EXTEND 50 ALSO AVAILABLE ON MISCELLANEOUS ORDER Contact-free tracing of ground or stringline with self-averaging to minimize effect of short surface irregularities and objects. Includes one sonic tracer consisting of five maintenance-free ceramic sensors with automatic temperature compensation, coily cable, sensor pole, and a telescoping sensor mount. The square tubing telescoping mount has a range of approximately 26" to 46" and mounts on the endgate. The sonic sensing unit is 28 cm (11") long. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		\$4,600 NI
P	416-2007	SENSOR, GRADE, MECHANICAL 70 ALSO AVAILABLE ON MISCELLANEOUS ORDER Mechanically traces the ground or stringline. Includes one proportional contacting mechanical sensor with one wand and one riding shoe attachment, coily cable, sensor pole, two support arms and mounting hardware. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		\$3,215 NI
P	513-0333	SENSOR, GRADE, MECH, EXTEND 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Mechanically traces the ground or stringline. Includes one proportional contacting mechanical sensor with one wand and one riding shoe attachment, coily cable, sensor pole, and a telescoping sensor mount. The square tubing telescoping mount has a range of approximately 26" to 46" and mounts on the endgate. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		\$3,215 NI
P	533-4151	SENSOR, GRADE, MECH DBL EXTEND 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Mechanically traces the ground or stringline. Includes one proportional contacting mechanical sensor with one wand and one riding shoe attachment, coily cable, sensor pole, and dual telescoping sensor mount. The square tubing, telescoping mount has a range of approximately 124 cm to 277 cm (49" to 109") and mounts on the screed hydraulic extension top frame. Required for paving at or below speeds of 4 mpm (13 ft/min) on lifts of 5 cm (2 in) or less. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM CANNOT BE USED WITH: 390-4740 SCREED, SE60V XW 453-6578 SCREED, SE60 V		\$2,815 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

GRADE AND SLOPE CONTROLS (Cont.)

P	533-4152	SENSOR, GRADE SONIC DBL EXTEND 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Contact-free tracing of ground or stringline with self-averaging to minimize effect of short surface irregularities and objects. Includes one sonic tracer consisting of five maintenance-free ceramic sensors with automatic temperature compensation, coily cable, sensor pole, and dual telescoping sensor mount. The square tubing, telescoping mount has a range of approximately 124 cm to 277 cm (49" to 109") and mounts on the screed hydraulic extension top frame. The sonic sensing unit is 28 cm (11") long. Required for paving at or below speeds of 4 mpm (13 ft/min) on lifts of 5 cm (2 in) or less. FOR GRADE/GRADE OPERATION ORDER QTY OF 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM CANNOT BE USED WITH: 390-4740 SCREED, SE60V XW 453-6578 SCREED, SE60 V	0	\$3,965 NI
---	----------	---	---	------------

LEVELING DEVICES

P	417-1907	BEAM, SONIC AVERAGING, CAT G&S 190 ALSO AVAILABLE ON MISCELLANEOUS ORDER Non-contacting beam utilizing three sonic tracers for enhanced averaging capability. System smooths out any unevenness of the reference surface by calculating an average value over the entire length of the beam. 9.1 m (30 ft) total beam length of four sections with both ends that fold for adjustability and ease of transport. Includes: two sonic tracers (assumes customer already has one or if not an additional sonic tracer must be selected), wiring harness, two support arms, two tow arm support brackets and mounting hardware. Requires: ONE SENSOR, GRADE, SONIC TO MAKE A COMPLETE AVERAGING BEAM ON ONE SIDE OF THE MACHINE ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM	190	\$17,100 NI
P	491-0721	CASE, SONIC SENSOR 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Case for storing grade sensors. Provides a storage location for up to four sonic sensors and two mechanical sensors. This case is only needed when running two BEAM, SONIC AVERAGING, CAT G&S on one machine. ONLY FOR USE WITH: 417-1907 BEAM, SONIC AVERAGING, CAT G&S	0	\$247 NI

OTHER ATTACHMENTS

OTHER TRACTOR ATTACHMENTS

L	481-8618	PLOW, TRACK 0 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Heavy duty ground scraper mounted in front of tracks that can be secured in raised position. Provides smoother operation and longer track life.	0	\$2,180 \$2,180 NI
---	----------	---	---	-----------------------

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

OTHER TRACTOR ATTACHMENTS (Cont.)

P	438-6149	EXTENSION, 1' AUGER LH 70 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 305 mm (1") auger extension and mounting hardware.		\$780 NI
P	438-6150	EXTENSION, 1' AUGER RH 70 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 305 mm (1") auger extension and mounting hardware.		\$780 NI
P	416-4130	EXTENSION, 2'6" AUGER LH 150 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One 755 mm (2' 6") auger extension and mounting hardware.		\$1,645 NI
P	416-4131	EXTENSION, 2'6" AUGER RH 150 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One 755 mm (2' 6") auger extension and mounting hardware.		\$1,645 NI
P	416-1189	KIT, 9'10" AUG, MAINFRAME EXT 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Recommended for wide width paving with Weiler screeds equipped with 3' of extensions on each side of the screed. Includes two 755 mm (2'6") left hand augers and two 755 mm (2'6") right hand augers, two augers support bearings and mainframe braces, four 788 mm (2'7") mainframe extensions, and two mainframe extension mounts.		\$13,750 NI
P	215-7553	EXTENSION, 0-2' MAINFRAME,PAIR 70 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Consists of a pair of hinged mainframe extensions foldable from 0 mm (0 ft) to 610 mm (2 ft) to facilitate frequent screed width changes. Bolts to mainframe. Does not raise and lower the augers. Unless the customer has auger extensions the preferred package is the KIT, AUGER AND MAINFRAME EXT Included in: KIT AUGER AND MAINFRAME EXT		\$1,265 NI
P	438-6255	EXTENSION, 1' MAINFRAME 25 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One 305 mm (1") fixed mainframe extension and mounting hardware. FOR DUAL MAINFRAME EXTENSIONS ORDER QTY 2		\$408 NI
P	416-4129	EXTENSION, 2'6" MAINFRAME 80 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One 788 mm (2'7") fixed mainframe extension and mounting hardware. FOR DUAL MAINFRAME EXTENSIONS ORDER QTY 2 CANNOT BE USED WITH: 416-4111 EXTENSION, MAINFRAME, POWER		\$650 NI
P	493-3538	KIT, ANGLED DEFLECTOR 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Single plate angled deflector kit for the front of the auger drive housing and a standard auger segment for the right side auger. This kit changes material flow from feeding from both sides to a left to right material flow.		\$292 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

OTHER TRACTOR ATTACHMENTS (Cont.)

P	273-9969	GUIDE, STEERING 15 ALSO AVAILABLE ON MISCELLANEOUS ORDER Second, adjustable position steering guide with indicator chain.		\$675 NI
P	416-4105	INDICATOR, TOW POINT 5 5 ALSO AVAILABLE ON MISCELLANEOUS ORDER Pair of tow point height gauges mounted on top of paver deck.		\$670 \$670 NI
P	458-4087	KIT, UPTIME 5 ALSO AVAILABLE ON MISCELLANEOUS ORDER Consists of critical spare parts to ensure maximum machine uptime. Items come packed in a lockable tool box and each part is clearly identified. Kit includes: O-rings, relays, sensors, position sensors, and fuses.		\$870 NI
P	416-4128	SPRAY WAND 15 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes 9 m (30 ft) hose, spray wand and quick-connect coupling. ONLY FOR USE WITH: 399-8387 TANK, WASHDOWN or 399-8386 PUMP, DIESEL CANNOT BE USED WITH: 463-6563		\$467 NI
P	463-6563	HOSE, REEL WITH WAND 60 60 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes 9 m (30 ft) hose on self-storing reel with spray wand mounted to left-hand handrail at rear of tractor. ONLY FOR USE WITH: 399-8387 TANK, WASHDOWN or 399-8386 PUMP, DIESEL CANNOT BE USED WITH: 416-4128 SPRAY WAND		\$1,880 \$1,880 NI
P	460-2964	PLATE, HOPPER, MAN APRON 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two hopper floor plate inserts to eliminate the drop in the front of the hopper. Raises the truck entry height by 1.5", but minimizes material build up in the hopper. Uses the flashing supplied with the machine. ONLY WORKS WITH MANUAL APRONS ONLY FOR USE WITH: 504-6957 HOPPER, LOW ENTRY, LOW SIDE		\$1,705 NI
P	480-7961	MIRRORS, EXTENSION, SCREED 0 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes 2 convex mirrors mounted outboard of the screed lift cylinders to provide the screed operator with a clear view of material in front of the screed extensions.		\$137 \$134 NI
P	490-4132	VISORS, DISPLAY, TRACTOR 0 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two folding visors that shade the tractor displays from sunlight. The visors fold back to allow the installation of the vandal covers.		\$805 \$805 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

OTHER TRACTOR ATTACHMENTS (Cont.)

P	485-2960	MOUNT, CANOPY, TEMP SCAN 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes the necessary hardware to mount a Moba Pave Scan infrared temperature scanner and display to a paver with canopy. ONLY FOR USE WITH: 416-2202 CANOPY, HARD TOP		\$2,660 NI
P	491-5820	MOUNT, TEMP SCAN 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes the necessary hardware to mount a Moba Pave Scan infrared temperature scanner and display to a paver with no canopy. CANNOT BE USED WITH: 416-2202 CANOPY, HARD TOP		\$3,020 NI
P	505-0167	DEFLECTOR, CONVEYOR 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Conveyor deflector that is positioned more directly under the head shaft. The plate minimizes material carry forward under the tractor in over feed conditions such as wide width or deep paving. Requires the removal of the production deflector.		\$555 NI
P	460-2967	FLASHING, SIDE 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Rubber flashing for use with rubber flashing options and manual fold tivar. Includes two folded rubber flashing pieces that mount on the sides of hopper above the standard flashing. Reduces material spillage between the sides of hopper and truck box. ONLY FOR USE WITH: 459-6760 FLASHING, MAN FOLD STD ENTRY or 415-7319 FLASHING, MANUAL FOLD RUBBER or 415-7317 FLASHING, MANUAL FOLD		\$755 NI

BALLAST PACKAGES

P	416-4107	BALLAST, 2 PLATE BUMPER 395 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Adds 179 kg (395 lb) of steel plate mounted to the front bumper for improved tractive effort and stability for wide width paving. Limits bumper oscillation in some bumper positions. CANNOT BE USED WITH: 431-0691 BALLAST, 4 PLATE BUMPER or 431-0692 BALLAST, 6 PLATE BUMPER	395 395	\$1,150 \$1,150 NI
P	431-0691	BALLAST, 4 PLATE BUMPER 787 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Adds 357 kg (787 lb) of steel plate mounted to the front bumper for improved tractive effort and stability for wide width paving. Limits bumper oscillation in some bumper positions. CANNOT BE USED WITH: 416-4107 BALLAST, 2 PLATE BUMPER or 431-0692 BALLAST, 6 PLATE BUMPER	787 787	\$2,295 \$2,295 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

BALLAST PACKAGES (Cont.)

P	431-0692	BALLAST, 6 PLATE BUMPER	910 910	\$2,650 \$2,650 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Adds 413 kg (910 lb) of steel plate mounted to the front bumper for improved tractive effort and stability for wide width paving. Limits bumper oscillation in some bumper positions. CANNOT BE USED WITH: 416-4107 BALLAST, 2 PLATE BUMPER or 431-0691 BALLAST, 4 PLATE BUMPER		
P	431-0693	BALLAST, 8 PLATE SIDE	743 743	\$2,160 \$2,160 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Adds 337 kg (743 lb) of steel plate mounted to the outside of the front of the machine frame behind the bumper.		

LEVELING DEVICES

P	109-5623	LEVELER, 30' OUTBOARD	2,190	\$8,030 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER 30' long multi-pad aluminum beam (measured from front to rear-most pivot pin) that runs along the outside of the tractor and the screed. Utilizes a combination of beams and shoes that pivot on pins to provide the optimum reference for grade controls. Two sub-beams with two shoes each attach to both the front and rear of the main beam. A string line runs along the top of the beam from front to rear. The whole unit is to be positioned mid way along the paver and the grade sensor (not provided) mounts on the tow arm and senses the midpoint of the string. The leveler gets pulled by the paver and increases the sensing length. It averages the high and low points in the reference surface to maximize the self-leveling characteristics of the paver. Includes mounting hardware. Best for smoothness and rideability. Good for joint matching. Primarily for highways and paving jobs with long pulls due to difficulty in maneuvering.		
P	109-5622	LEVELER, 40' OUTBOARD	2,280	\$8,250 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER SAME AS LEVELER, 30' OUTBOARD above except for 40' long multi-pad aluminum beam. Capable of producing an even flatter and more level surface than the 30' leveler but is not as transportable.		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

LEVELING DEVICES (Cont.)

P	109-5625	LEVELER, FORE'N AFT420 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER 12' long multi-pad aluminum beam (measured from front to rear-most pivot pin) that mounts ahead and inboard of the screed. Two sub-beams with two shoes each that pivot on pins attach to the main beam. This leveler gets pulled by the paver. An additional towed shoe attaches to the screed and rides on the mat. A string line gets stretched between the front inboard and aft leveler. A grade sensor (not provided) mounts on the tow arm and senses the string midpoint. During paving the front leveler will average out the high and low points of the reference surface while the aft leveler responds to height changes in the mat behind the screed. Includes mounting hardware. Best for highways and paving jobs with long pulls. Not as effective as an outboard leveler. Used when outboard referencing is not practical due to width restrictions.		\$7,870 NI
---	----------	---	--	-------------------

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS

SE60 V SCREED SELECTION

L	453-6578	SCREED, SE60 V	6,819 0	\$94,980 \$94,980 NI
---	----------	--------------------------	------------	-------------------------

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Double extending vibratory screed. Provides paving widths from 3.0 m to 6.0 m (9' 10" to 19' 6"). Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibrate speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Screed plate thickness is 13 mm (0.5"). Hydraulic extensions have hydraulic power for height and electric power for slope. Main screed has electric powered crown.

CONTROL CYLINDERS

Selection required with Screed, SE60 V

L	461-7477	CYLINDER KIT, STANDARD	181	NC
---	----------	----------------------------------	-----	----

Standard extend and retract cylinders.
REQUIRED BY: SCREED, SE60 V

PICTO LABELS

Selection required with Screed, SE60 V

L	449-8858	FILM GP US	0	NC
---	----------	----------------------	---	----

Picto warning decals using symbols plus the word "WARNING" as required for the USA.
Also includes extensions width scales reading inches.
REQUIRED BY: SCREED, SE60 V

EXTENSION CONTROLS

Selection required with Screed, SE60 V

L	460-8038	EXT, POWER FOR MANUAL ENDGATE	0	NC
---	----------	---	---	----

Provides hydraulic motor power for raising and lowering extension height relative to the main screed.
FOR USE WITH: ENDGATE MANUAL
REQUIRED BY: SCREED, SE60 V

L	473-3321	EXT, POWER FOR POWER ENDGATE	0	\$3,230
---	----------	--	---	---------

Provides hydraulic motor power for raising and lowering extension height relative to the main screed.
Also provides hydraulic power for powered endgates.
FOR USE WITH SE60V SCREEDS JJ300282 AND UP
REQUIRED BY: SCREED, SE60 V

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SCREED ENDGATES

Selection required with Screed, SE60 V

All standard and powered endgates have an upward travel of 50 mm (2") above grade and 150 mm (6") below grade.

L	538-9613	ENDGATE, ADJUSTABLE CRANK 0 Standard endgate with replaceable wear skis and two adjustable crank jacks. ONLY FOR USE WITH: 460-8038 EXT, POWER FOR MANUAL ENDGATE REQUIRED BY: 453-6578 SCREED, SE60 V		NC
L	523-4576	ENDGATE, POWER 0 Left and right powered endgate with replaceable wear skis and two hydraulic cylinders to position the height of the endgate. ONLY FOR USE WITH: 460-8038 EXT, POWER FOR MANUAL ENDGATE or 473-3321 EXT. POWER FOR POWER ENDGATE REQUIRED BY: 453-6578 SCREED, SE60 V		\$8,270

ENDGATE HEATER OPTION

L	490-1681	HEATER, ENDGATE 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two heater elements to heat the non-folding endgate shoes. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V	0	\$2,110 \$2,110 NI
---	----------	--	---	-----------------------

SE60 V OPTIONAL ATTACHMENTS

P	467-0083	VISORS, DISPLAY 6 Includes two folding visors that shade the screed display from sunlight. The visors fold back to allow the installation of the vandal covers.		\$323
P	473-3322	CONTROL, PENDANT 7 ALSO AVAILABLE ON MISCELLANEOUS ORDER Two removable pendant controls with coily cord. Allows adjustment of optional powered endgate, screed width, extension height and slope and manual override and pause of the feeders system. FOR USE WITH SE60 V SCREED ONLY	0	\$2,330 \$2,330 NI
P	480-7055	MOUNT, SWIVEL CONTROLS 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes a left and right mounting bracket to allow the left and right screed operator controls to swivel up and down and also left and right. FOR USE WITH SCREED, SE60 V		\$1,255 NI
P	467-4275	UMBRELLA, SCREED OPERATOR 35 ALSO AVAILABLE ON MISCELLANEOUS ORDER One CAT umbrella and mount to provide screed operator sun and rain protection. Measures 54" x 54" and is collapsible. Includes support shaft and mounting hardware. For a complete machine, providing protection to both screed operators, order qty 2. FOR USE WITH SE60 V SCREED ONLY		\$323 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60 V OPTIONAL ATTACHMENTS (Cont.)

P	472-0510	SHOE, WIDE 72 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Consist of two wide endgate shoes that can be used to replace the standard endgate shoe. The wide shoes are 88 mm (3.5") wide. These shoes are wider than the endgate structure. This shoe can be used with the endgate heater.		\$855 NI
P	472-0512	SHOE, EDGE 26 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Consists of two vertical endgate shoes that can be used to replace the standard endgate shoe. The vertical edge shoes also have the mounting tabs welded to the outside of the vertical structure. The vertical shoe is 5 mm thick and has 16 mm of clearance from the bottom wear surface up to the mounting tabs. At the mounting tabs total width is 50 mm. The vertical endgate shoes do not work with endgate heaters.		\$755 NI
P	467-4575	SHOE, SAFETY EDGE 125 ALSO AVAILABLE ON MISCELLANEOUS ORDER Reversible safety edge shoe for use on either side of the screed. Attaches to the rear of the endgate and modifies the edge of the mat as it leaves the screed. Mounts to the same location as the folding endgate, so it cannot be used while the folding endgate is installed.		\$855 NI
P	490-2550	PACKAGE, CUT OFF SHOE 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One plate for 1' cut off and one plate for 2' cut off reducing paving widths in 6" increments. For use with SCREED SE60 V		\$2,090 NI
P	486-4622	EXTENSION, 9.8" SCREED 180 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 250 mm (9.8") screed extension. Electrically heated. No vibration. 1/4 turn quick connect harnesses. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH SCREED, SE60 V JJ300282 AND UP		\$4,280 NI
P	486-4620	EXTENSION, 2' 5.5" SCREED 487 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 750 mm (2' 5.5") screed extension. Electrically heated. Includes quick connect shaft, mounting hardware, and 1/4 turn harnesses. ORDERS QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED. FOR USE WITH SCREED, SE60 V JJ300282 AND UP		\$5,670 NI
P	468-5854	EXTENSION, 9.8" SCREED 180 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 250 mm (9.8") screed extension. Electrically heated. No vibration. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH SCREED, SE60 V JJ300281 AND DOWN		\$4,470 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60 V OPTIONAL ATTACHMENTS (Cont.)

P	478-1898	EXTENSION, 2' 5.5" SCREED 487 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 750 mm (2' 5.5") screed extension. Electrically heated. Includes vibe drive shaft and mounting hardware. ORDERS QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED. FOR USE WITH SCREED, SE60 V JJ300281 AND DOWN		\$5,670 NI
---	----------	--	--	-------------------

SE60 V EXTENSION PACKAGES

P	473-8992	PACKAGE, COMMERCIAL + 1' 7.7" 380 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes mounting hardware and 1/4 turn harnesses. Includes: KIT, AUGER AND MAINFRAME EXT and two mechanical 250 mm (9.8") bolt on heated extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver, if equipped, prior to installing this package. FOR SCREED SERIAL NUMBER JJ300282 AND ABOVE.		\$12,690 NI
P	477-1128	PACKAGE, COMMERCIAL + 4' 11" 1,378 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes a pair (left and right) of 152 mm (6") auger extensions, two pairs (left and right) of 305 mm (1') auger extensions and a pair of foldable, hinged 610 mm (2') mainframe extensions to facilitate frequent screed width changes. Also includes two 1.25 m (4'1") prestrikeoffs and two 750 mm (2' 5.5") heated-vibratory screed extensions. Includes quick connect drive shaft, mounting hardware and 1/4 turn harnesses. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph) FOR SCREED SERIAL NUMBER JJ300282 AND ABOVE.		\$16,920 NI
P	475-2632	PACKAGE, BASE WIDTH + 4' 11" 2,855 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two 755 mm (2'6") left hand augers and two 755 mm (2'6") right hand augers, two auger support bearings and mainframe braces, four 788 mm (2'7") mainframe extensions, two mainframe extension mounts, two 750 mm (2' 5.5") heated-vibratory screed extensions, prestrikeoffs and one tube for front mounting support of reference ski. Includes quick connect drive shaft, mounting hardware and 1/4 turn harnesses. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2mph) FOR SCREED SERIAL NUMBER JJ300282 AND ABOVE.		\$25,390 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60V XW AND SE60VT XW SCREED SELECTIONS

L	390-4740	SCREED, SE60V XW	8,800 0	\$102,410 \$102,410 NI
---	----------	----------------------------	------------	---------------------------

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Double extending vibratory screed. Provides paving widths from 3.00 m to 5.95 m (9'10" to 19'6"). Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibrate speeds, counterbalance pressure and optional CAT Grade and Slope control in both metric and SI units. Screed plate thickness is 13 mm (0.5"). Hydraulic extensions have hydraulic power for height and slope. Main screed has hydraulic powered crown.

L	522-1492	SCREED, SE60 VT XW	0 0	\$115,720 \$115,720 NI
---	----------	------------------------------	--------	---------------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
Double extending screed with tamper bar and vibrate. Provides paving widths from 3.0 m to 6.0 m (9'10" to 19' 6"). Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, tamper and vibrate speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Screed plate thickness is 13 mm (0.5"). Hydraulic extensions have hydraulic power for height and slope. Main screed has a split plate design with hydraulic powered crown.
Includes: SCREED COVER, EXTENDED
ONLY FOR USE WITH: 396-7127 ADAPTER, TAMP/VIBRE SCREED

CONTROL CYLINDERS

Selection required with Screed, SE60V XW and Screed, SE60 VT XW

L	390-4825	CYLINDER KIT, STANDARD	181	NC
---	----------	----------------------------------	-----	----

Standard extend and retract cylinders.
REQUIRED BY: 390-4740 SCREED, SE60V XW or
522-1492 SCREED, SE60 VT XW

COVER GROUPS

Selection required with Screed, SE60V XW

L	390-4829	SCREED COVER, EXTENDED	317	\$2,110
---	----------	----------------------------------	-----	---------

Full screed covers includes metal top cover, plastic front and rear covers, and rubber flaps on the main screed. Also includes rubber flaps on the extensions.
REQUIRED BY: SCREED, SE60V XW

P	433-1486	SCREED COVER, STANDARD	178	NC
---	----------	----------------------------------	-----	----

Partial screed cover includes a half plate metal top cover and plastic rear cover.
REQUIRED BY: SCREED, SE60V XW

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

THICKNESS CONTROLS

Selection required with Screed, SE60V XW and Screed, SE60 VT XW

L	390-4948	THICKNESS CONTROL, HANDLE 11 Provides a handle for making quick paving depth changes while doing commercial and manual paving jobs. Typically used with vibratory screeds in North America. REQUIRED BY: 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		NC
L	390-4949	THICKNESS CONTROL, KNOB 4 Provides a 41.3 mm (1 5/8") hex head for making paving depth changes. Changes angle of attack of the screed. REQUIRED BY: 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		NC

PICTO LABELS

Selection required with Screed, SE60V XW and Screed, SE60 VT XW

L	390-4952	FILM GP, US 0 Picto warning decals using symbols plus the word "WARNING" as required for the USA. Also includes extension width scales reading inches. REQUIRED BY: 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		NC
---	----------	---	--	----

WIDE PACKAGE SUPPORT

Selection required with Screed, SE60V XW and Screed, SE60 VT XW

P	448-8262	HARNESS, WIDE PACKAGE 5 Includes an additional left and right power harness connecting from the screed power module to the power distribution boxes on the hydraulic screed extensions. This is required for heating +3.0m and 4.0m (9'10" and 13'2") paving packages on both the SE60 V XW and SE60 VT XW. REQUIRED BY: 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		NC
---	----------	---	--	----

SCREED ENDGATES

Selection required with Screed, SE60V XW and Screed, SE60 VT XW

All standard and powered endgates have a upward travel of 50 mm (2") above grade and 150 mm (6") below grade.

L	528-8321	ENDGATE, ADJUSTABLE CRANK 0 Standard endgate with replaceable wear skis and two adjustable crank jacks. REQUIRED BY: 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SCREED ENDGATES (Cont.)

L	523-4577	ENDGATE, POWER	0	\$11,510
		Left and right powered endgate with replaceable wear skis and two hydraulic cylinders to position the height of the endgate. REQUIRED BY: 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		

ENDGATE HEATER OPTIONS

L	490-1690	HEATER, ENDGATE	0	\$2,110
			0	\$2,110 NI

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Includes two heater elements to heat the non-folding endgate shoes.
4465919
ONLY FOR USE WITH: 390-4740 SCREED, SE60V XW or
522-1492 SCREED, SE60 VT XW

L	446-5919	HEATER, ENDGATE, FOLDING	0	\$2,350
			0	\$2,350 NI

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Includes two heater elements to heat the folding endgate shoes.
ONLY FOR USE WITH: 390-4740 SCREED, SE60V XW
522-1492 SCREED, SE60 VT XW

FOLDING HEATER OPTION

L	390-4947	SCREED ENDGATES, FOLDING	0	\$5,160
			0	\$5,160 NI

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Includes a foldable system to provide the narrowest possible transport width.
ONLY FOR USE WITH: 446-5919 HEATER, ENDGATE, FOLDING

SE60V XW AND SE60VT XW OPTIONAL ATTACHMENTS

P	467-0083	VISORS, DISPLAY	6	\$323
		Includes two folding visors that shade the screed display from sunlight. The visors fold back to allow the installation of the vandal covers.		

P	473-3330	CONTROL, PENDANT	7	\$2,330
			0	\$2,330 NI

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Two removable pendant controls with coily cords. Allows adjustment of optional powered endgate, screed width, extension height and slope, and manual override and pause of the feeders system.
FOR USE WITH SE60VT XW SCREED ONLY

P	473-3322	CONTROL, PENDANT	7	\$2,330
			0	\$2,330 NI

ALSO AVAILABLE ON MISCELLANEOUS ORDER
Two removable pendant controls with coily cord. Allows adjustment of optional powered endgate, screed width, extension height and slope, and manual override and pause of the feeders system.
FOR USE WITH SE60V XW SCREED ONLY

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60V XW AND SE60VT XW OPTIONAL ATTACHMENTS (Cont.)

P	480-7055	MOUNT, SWIVEL CONTROLS 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes a left and right mounting bracket to allow the left and right screed operator controls to swivel up and down and also left and right. FOR USE WITH SCREED, SE60V XW		\$1,255 NI
P	467-4275	UMBRELLA, SCREED OPERATOR 35 ALSO AVAILABLE ON MISCELLANEOUS ORDER One CAT umbrella and mount to provide screed operator sun and rain protection. Measures 54" x 54" and is collapsible. Includes support shaft and mounting hardware. For a complete machine, providing protection to both operators, order qty 2. FOR USE WITH: SCREED, SE60V XW		\$323 NI
P	472-0510	SHOE, WIDE 72 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Consist of two wide endgate shoes that can be used to replace the standard endgate shoe. The wide shoes are 88 mm (3.5") wide. These shoes are wider than the endgate structure. This shoe can be used with the endgate heater.		\$855 NI
P	472-0512	SHOE, EDGE 26 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Consists of two vertical endgate shoes that can be used to replace the standard endgate shoe. The vertical edge shoes also have the mounting tabs welded to the outside of the vertical structure. The vertical shoe is 5 mm thick and has 16 mm of clearance from the bottom wear surface up to the mounting tabs. At the mounting tabs total width is 50 mm. The vertical endgate shoes do not work with endgate heaters.		\$755 NI
P	467-4575	SHOE, SAFETY EDGE 125 ALSO AVAILABLE ON MISCELLANEOUS ORDER Reversible safety edge shoe for use on either side of the screed. Attaches to the rear of the endgate and modifies the edge of the mat as it leaves the screed. Mounts to the same location as the folding endgate, so it cannot be used while the folding endgate is installed.		\$855 NI
P	490-2560	PACKAGE, CUT OFF SHOE 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One plate for 1' cut off and one plate for 2' cut off reducing paving width in 6" increments. For use with SE60 V XW screeds		\$2,330 NI
P	490-2570	PACKAGE, CUT OFF SHOE 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER One plate for 1' cut off and one plate for 2' cut off reducing paving width in 6" increments. For use with SE60 VT XW screeds		\$2,105 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60V XW AND SE60VT XW OPTIONAL ATTACHMENTS (Cont.)

P	481-5715	EXTENSION, 9.8" SCREED V XW 196 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 250 mm (9.8") screed extension. Electrically heated. No vibration. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH: SCREED, SE60V XW ONLY FOR USE WITH SCREED SERIAL NUMBER JS900149 AND BELOW CONSULT YOUR ORDER COORDINATOR IF ORDERING WITH A SCREED		\$4,470 NI
P	478-1899	EXTENSION, 2' 5.5" SCREED V XW 525 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 750 mm (2' 5.5") screed extension. Electrically heated. Includes vibe drive shaft and mounting hardware. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH: SCREEDS, SE60V XW ONLY FOR USE WITH SCREED SERIAL NUMBER JS900149 AND BELOW CONSULT YOUR ORDER COORDINATOR IF ORDERING WITH A SCREED		\$5,670 NI
P	487-5617	EXTENSION, 9.8" SCREED V XW 196 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 250 mm (9.8") screed extension. Electrically heated. No vibration. 1/4 turn quick connect harnesses. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDE OF SCREED FOR USE WITH SCREED, SE60V XW ONLY FOR USE WITH SCREED SERIAL NUMBER JS900150 AND ABOVE CONSULT YOUR ORDER COORDINATOR IF ORDERING WITH A SCREED		\$4,470 NI
P	487-5615	EXTENSION, 2' 5.5" SCREED V XW 525 ALSO AVAILABLE ON MISCELLANEOUS ORDER One 750 mm (2' 5.5") screed extension. Electrically heated. Includes quick connect shaft, mounting hardware and 1/4 turn harnesses. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH SCREED, SE60V XW ONLY FOR USE WITH SCREED SERIAL NUMBER JS900150 AND ABOVE CONSULT YOUR ORDER COORDINATOR IF ORDERING WITH A SCREED.		\$5,670 NI
P	453-2460	ENDGATE, DEEP LIFT, MANUAL 685 ALSO AVAILABLE ON MISCELLANEOUS ORDER FOR USE WITH LANE 3 ONLY Includes a complete left and right manual endgate with 380 mm (15") travel for deep lift paving. Travel is 75 mm (3") above grade and 12" (305 mm) below grade. Replaces the endgates that ship with the machine. Can be used with folding endgates, but cannot be used with the heated or powered endgate options. ONLY FOR USE WITH: 522-1492 SCREED, SE60 VT XW		\$7,520 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60V XW EXTENSION PACKAGES

P	477-1150	PACKAGE, COMMERCIAL + 1' 7.7" 380 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes: KIT, AUGER AND MAINFRAME EXTENSION and mechanical 250 mm (9.8") bolt on heated extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver, if equipped, prior to installing this package. FOR SCREED SERIAL NUMBER JS900150 AND ABOVE.		\$13,360 NI
P	477-1353	PACKAGE, BASE WIDTH + 4' 11" 2,855 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two 755 mm (2'6") left hand augers and two 755 mm (2'6") right hand augers, two auger support bearings and mainframe braces, four 788 mm (2'7") mainframe extensions, two mainframe extension mounts, two 750 mm (2' 5.5") heated-vibratory screed extension, 1.25 m (4' 1") prestrikeoffs and one tube for front mounting support of reference ski. Includes 1/4 turn electrical connectors and quick connect shafts. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. FOR SCREED SERIAL NUMBER JS900150 AND ABOVE.		\$26,710 NI
P	477-1354	PACKAGE, BASE WIDTH + 8' 2.4" 3,918 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes three 755 mm (2'6") left hand augers and three 755 mm (2'6") right hand augers, two auger support bearings and mainframe braces, six 788 mm (2'7") mainframe extensions, two mainframe extension mounts, two 1250 mm (4' 1.2") heated-vibratory screed extensions, two 1.25 m (4'1") and two 0.75 m (2'6") prestrikeoffs, and one tube for front mounting support of reference ski. Includes 1/4 turn electrical connectors, and quick connect shafts. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph). FOR SCREED SERIAL NUMBER JS900150 AND ABOVE.		\$44,550 NI
P	477-1355	PACKAGE, BASE WIDTH + 9' 10.1" 4,361 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes three 755 mm (2'6") left hand augers and three 755 mm (2'6") right hand augers, two augers support bearings and mainframe braces, six 788 mm (2'7") mainframe extensions, two mainframe extension mounts, four 750 mm (2' 5.5") heated-vibratory screed extensions, two 1.25 m (4'1") and two 0.75 m (2'6") prestrikeoffs, and one tube for front mounting support or reference ski. Includes 1/4 turn electrical connectors, and quick connect shafts. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph). FOR SCREED SERIAL NUMBER JS900150 AND ABOVE. ONLY FOR USE WITH: 431-0693 BALLAST, 8 PLATE SIDE		\$53,450 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60V XW EXTENSION PACKAGES (Cont.)

P	477-1356	PACKAGE, BASE WIDTH + 13' 1.5" 5,833 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes four 755 mm (2'6") left hand augers and four 755 mm (2'6") right hand augers, four auger support bearings and mainframe braces, eight 788 mm (2'7") mainframe extension, two mainframe extension mounts, two 750 mm (2' 5.5") heated-vibratory screed extensions, two 1250 mm (4' 1.2") heated-vibratory screed extensions, four 1.25 m (4'1") prestrikeoffs, and one tube for front mounting support of reference ski. Includes 1/4 turn electrical connectors, and quick connect shafts. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph). FOR SCREED SERIAL NUMBER JS900150 AND ABOVE. REQUIRES: BALLAST, 8 PLATE SIDE and BALLAST, 2 PLATE BUMPER		\$71,260 NI
P	533-5354	REDUCER PKG, 4'11", SCREED VXW 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two of the following: .75 m (2'5") prestrikeoffs, vertical support struts, and vibratory shafts. Allows for use of the 1.25 m (4'1") extenders to convert from 10.0 m (32'10") paving width to 8.5 m (27'10") paving width. ONLY FOR USE WITH: 477-1356 PACKAGE, BASE WIDTH + 13' 1.5"		\$4,835 NI

SE60VT XW EXTENSION PACKAGES

P	477-1357	PACKAGE, COMMERCIAL + 1' 7.7" 400 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes KIT, AUGER AND MAINFRAME EXT and mechanical 250 mm (9.8") bolt on heated extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver, if equipped, prior to installing this package.		\$11,870 NI
P	477-1364	PACKAGE, BASE WIDTH + 4'11" 3,157 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes two 0.75m (2'6") left hand augers and two 0.75m (2'6") right hand augers, two auger support bearings and mainframe braces, four 0.79m (2'7") mainframe extensions, two mainframe extension mounts, two 0.75m (2' 5.5") heated-vibratory/tamper screed extensions, prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped.		\$36,010 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60VT XW EXTENSION PACKAGES (Cont.)

P	477-1365	PACKAGE, BASE WIDTH + 8'2.4" 4,308 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes three 0.75m (2'6") left hand augers and three 0.75m (2'6") right hand augers, two auger support bearings and mainframe braces. six 0.79m (2'7") mainframe extensions, two mainframe extension mounts, two 1.25m (4'1.2") heated-vibratory/tamper screed extensions, prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph). ONLY FOR USE WITH: 431-0693 BALLAST, 8 PLATE, SIDE		\$60,010 NI
P	477-1366	PACKAGE, BASE WIDTH + 9'10.1" 5,097 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes three 0.75m (2'6") left hand augers and three 0.75m (2'6") right hand augers, two auger support bearings and mainframe braces. six 0.79m (2'7") mainframe extensions, two mainframe extension mounts, four 0.75m (2'5.5") heated-vibratory/tamper screed extensions, prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph). ONLY FOR USE WITH: 431-0693 BALLAST, 8 PLATE, SIDE		\$72,020 NI
P	477-1367	PACKAGE, BASE WIDTH + 13'1.5" 6,496 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes four 0.75m (2'6") left hand augers and four 0.75m (2'6") right hand augers, four auger support bearings and mainframe braces. eight 0.79m (2'7") mainframe extensions, two mainframe extension mounts, two 0.75m (2'5.5") heated-vibratory/tamper screed extensions, two 1.25m (4'1.2") heated-vibratory/tamper screed extensions, prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 10 kph (6.2 mph). ONLY FOR USE WITH: 416-4107 BALLAST, 2 PLATE BUMPER and 431-0693 BALLAST, 8 PLATE SIDE or 431-0691 BALLAST, 2 PLATE BUMPER or 431-0692 BALLAST, 6 PLATE BUMPER		\$96,020 NI
P	533-5355	REDUCER PKG, 4'11" SCREED VTXW 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two of the following: 0.75 m (2'5") prestrikeoffs, vertical support struts, tamper shafts and vibratory shafts. Allows for use of the 1.25 m (4'1") extenders to convert from 10.0 m (32'10") paving width to 8.5 m (27'10") paving width. ONLY FOR USE WITH: 477-1367 PACKAGE, BASE WIDTH + 4.0 M		\$4,935 NI

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

FRONT MOUNT SREED SUPPORT

The following Weiler screed selections are the only available configurations from the factory. For all other configurations please contact Weiler directly through their website: www.weilerproducts.com. Parts and warranty for all Weiler products, including the below sections, are administered through Weiler. All other optional attachments such as extensions, should be ordered through Weiler. Screeds ordered from Weiler must be installed at Weiler or the Caterpillar dealership.

L	495-8981	SCREED, WEILER SE10F, BASIC	0 0	\$134,790 \$134,790 NI
		Double extending front mounted extension vibratory screed. Provides paving widths from 10' to 19'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibe speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extension have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. REQUIRES: 495-9001 THICKNESS SCREWS, CCW or 495-9002 THICKNESS SCREWS, CW CANNOT BE USED WITH: 453-6578 SCREED, SE60 V or 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		
L	495-8980	SCREED, WEILER SE10F, 18" BERM	0 0	\$142,750 \$142,750 NI
		Double extending front mounted extension vibratory screed. Provides paving widths from 10' to 19'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibe speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extensions have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. Includes left and right berm attachments in the extensions. REQUIRES: 495-9001 THICKNESS SCREWS, CCW or 495-9002 THICKNESS SCREWS, CW CANNOT BE USED WITH: 453-6578 SCREED, SE60 V or 390-4740 SCREED, SE60V XW or 522-1492 SCREED, SE60 VT XW		

THICKNESS SCREWS

MUST SELECT ONE WITH A WEILER SCREED

P	495-9001	THICKNESS SCREWS, CCW	0	NC
		Two ACME RH threaded screws (8tpi). Counter-clockwise turn increases paving depth. ONLY FOR USE WITH: 495-8981 SCREED, WEILER SE10F, BASIC or 495-8980 SCREED, WEILER SE10F, 18" BERM		
P	495-9002	THICKNESS SCREWS, CW	0	NC
		Two ACME LH threaded screws (8tpi). Clockwise turn increases paving depth. ONLY FOR USE WITH: 495-8981 SCREED, WEILER SE10F, BASIC or 495-8980 SCREED, WEILER SE10F, 18" BERM		

CATERPILLAR MACHINE PRICE LIST

AP1055F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FACTORY SOURCED KITS

P	496-9628	LIGHTS, LED, CANOPY 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed four forward facing and four rear facing, LED lights, mounted to the hard top canopy. Dealer installation of front, outermost light bracket is required. ONLY FOR USE WITH: 523-4277 WIRING, LIGHTS/HAZARD READY and 434-0040 HARD TOP CANOPY		\$1,875 NI
P	496-9649	LIGHTS, LED, SCREED 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed includes wiring and eight LED lights, four mounted to the rear of the tractor and four mounted to the screed, to illuminate the screed in low light conditions. Dealer installation required.		\$2,275 NI

PACKING

0P-0210	PACK, DOMESTIC TRUCK 0		NC
---------	----------------------	---------	--	----

MISCELLANEOUS PACKING

0P-3651	PACKING, MISC MATERIAL 0 No charge for packing. Applicable freight charges may apply.			NC
---------	---	--	--	----