

CATERPILLAR MACHINE PRICE LIST

CB8

CB8 VIBRATORY ASPHALT COMPACTOR
 MINNEAPOLIS, MN, USA (SAP)

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

CAT C3.4 inline 4 cylinder, turbo-charged diesel engine (75kW / 101 HP)
 Cyclonic air cleaner
 Water separator
 Ultra clean fuel filter with integrated electric priming pump
 ECO mode throttle system
 Dual braking systems (service & parking)
 Two-speed hydrostatic transmission

ELECTRICAL

12-volt electric starting
 120 ampere alternator
 Maintenance free battery - 1000 CCA
 Halogen working lights - bumper mounted (2 front-facing and 2 rear-facing)
 Backup alarm and forward warning horn
 Cat engine and vehicle ECM's - ET compatible
 Product link ready

OPERATOR ENVIRONMENT

Isolated ROPS/FOPS structure
 Platform handrails / guardrails
 Four heavy-duty isolation mounts
 Power steering
 Adjustable, suspension seat
 50 mm (2") wide retractable seat belt
 Adjustable, steering console and control/display console
 Indicator light package with audible warning alarm for:
 -hydraulic oil pressure
 -hydraulic oil temperature
 -engine oil pressure
 -engine coolant temperature
 -glow plugs
 -service fault indicator
 Fuel level gauge
 Water level gauge
 Service hour meter
 Lockable, vandalism guard for instrument panel
 Sliding, rotating seat
 Automatic speed control
 Auto-vibe with adjustable on/off control
 Vibe tachometer
 Speedometer

DRUMS

Smooth drum
 1700 mm (67") wide x 1100 mm (43") diameter
 Two amplitudes with two vibe frequencies

Front and rear self adjusting scraper blades
 Pod-style eccentric weight housing

FLUIDS

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

OTHER STANDARD EQUIPMENT

Locking engine enclosure
 Sealed for life hitch bearings
 Sight gauges:
 -hydraulic tank level
 -air restriction indicator
 Cap lock for hydraulic tank
 Articulated frame with safety lock
 Transport tie-down and lift points
 208 L (55 gal) fuel tank capacity
 745 L (197 gal) water tank capacity
 Quick connect hydraulic pressure test ports
 SOS ports
 -engine oil
 Dual spray bar pumps
 Single water spray bar per drum

CATERPILLAR MACHINE PRICE LIST

CB8

CB8 VIBRATORY ASPHALT COMPACTOR MINNEAPOLIS, MN, USA (SAP)	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the
 Base Order Management program.**

505-8466	CB8 VIBRATORY COMPACTOR 0 LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	\$147,060
----------	--	------------------

OP-4156	CB8 MISC MATL 0 AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	NC
---------	---	-----------

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

POWERTRAIN

ENGINE

L	565-6386	ENGINE, AB&T	0	NC
		EPA Tier 4 Final AB&T certified engine. (Tier 4 Interim credit-using engine)		

DRUM TYPE

L	505-8534	DRUM, SOLID	0	NC
		1700 mm (67") solid drums.		

HITCH

L	341-8800	HITCH, STANDARD	712	NC
		Standard hitch without offset.		
L	341-8801	HITCH, OFFSET	831	\$3,380
		Switch control on propel gives + / - 152 mm (6") of drum offset. REQUIRES: 454-3055 CONTROL, PREMIUM		

HYDRAULICS

VIBRATORY HYDRAULICS

L	341-8752	SYSTEM, 5 AMPLITUDE	1,578	\$870
		Frequency of 53.3 Hz (3200 vpm). Drum mounted handwheel with 5 manual settings for vibratory amplitude control. Includes auto reversing weights. ONLY FOR USE WITH: 505-8534 DRUM, SOLID		
L	341-8765	SYSTEM, 2 AMP, 2 FREQ	1,484	NC
		Frequency of 53.3 Hz (3200 vpm) and 63.3 Hz (3800 vpm). Console switch control for amplitude / frequency setting. ONLY FOR USE WITH: 505-8534 DRUM, SOLID		

ELECTRICAL

LIGHTING

L	501-6572	LIGHTS, WORKING	0	NC
		Includes 2 front and 2 rear facing clear lights located in the bumpers.		
L	501-6573	LIGHTS, ROADING AND WORKING	0	\$835
		Includes 2 front high beam headlights, 2 rear facing flood lights, front and rear turn signals, and front and rear indicator/parking lights. All lights are attached to the bumpers. REQUIRES: 519-3979 LIGHTING PREP		

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

OPERATOR STATION

L	513-5924	PLATFORM, ROPS/FOPS	0	NC
		Includes grab handrails and foundation for the sliding and rotating operator station.		
L	512-8539	CAB, ROPS/FOPS	0	\$10,970
		Includes grab handrails and foundation for the sliding and rotating operator station.		

OPERATOR STATION MOVEMENT

L	343-6115	ROTATION, HALF	40	NC
		Includes operator station controls, LCD display and station slide and 180 deg rotate levers.		
L	356-0924	ROTATION, FULL	75	\$2,040
		Includes operator station controls, LCD display and station slide and 359 deg rotate levers.		

CONTROL PANEL

L	510-6132	PANEL, STD	0	NC
		8 button control panel for operator control of machine functions. Includes the following: frequency selection; vibratory drum selection, travel speed mode, selectable speed control, speed sensing water spray control, and water pump selection.		

PROPEL LEVER

L	454-3054	CONTROL, STD	2	NC
		Includes vehicle wiring and basic 2 button propel lever for propel control, vibratory on/off selection, and water spray functions.		
L	454-3055	CONTROL, PREMIUM	2	\$595
		Includes premier wiring and premium 6 button propel lever needed for most options. In addition to the standard control function, the additional 4 buttons will control the offset hitch and edge cutter functionality (only if machine is equipped with these options).		

STEERING WHEEL

L	489-6273	STEERING WHEEL, FIXED	0	NC
		LH located steering wheel with a fixed location.		
L	489-6274	STEERING WHEEL, PIVOTING	0	\$675
		LH located steering wheel with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers. CANNOT BE USED WITH: 514-1273 MAPPING, GNSS 514-1274 MAPPING, GNSS, CAB		

OPERATOR LANGUAGES

L	527-8200	LANGUAGES, OPTION 1	0	NC
		Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

SEAT SELECTION

L	343-6129	SEAT, STD VINYL 157 Vinyl suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back.		NC
L	355-3084	SEAT, HEATED VINYL 163 Heated vinyl suspension seat with fold-up arms rests, retractable seat belt, weight adj., and tilt back.		\$314
L	344-0124	SEAT, STD CLOTH 157 Cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS		\$209
L	355-3085	SEAT, HEATED CLOTH 163 Heated cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS		\$366

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact you Caterpillar marketing representative with questions.

L	451-3243	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS		\$432
L	451-3240	PRODUCT LINK, CELLULAR PL641 0 Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS		NC
L	451-3245	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS		\$432

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

PRODUCT LINK (Cont.)

L	451-3242	PRODUCT LINK, CELLULAR PL641 0		NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		
		ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS		

FLUIDS

HYDRAULIC OIL

L	343-6157	OIL, HYD, FACTORY FILLED 311		NC
L	343-6158	OIL, HYD, BIO, FACTORY FILLED 324		\$620
		FOR USE WITH LANE 3 ONLY		
		Bio degradable oil recommended for hydraulic system when environmental compliance is required or desired.		
L	355-3086	OIL, HYD, HIGH AMBIENT 324		\$366
		Hydraulic Oil recommended for machines operating in high temperature regions.		

INSTRUCTIONS

DECAL PACKAGES

L	505-8561	INSTRUCTIONS, NORTH AMERICAN 0		NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).		

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
L	519-3979	LIGHTING, PREP 0 Includes harnesses required for lighting options.		\$1,025
P	351-3443	LIGHT, ROTATING BEACON 4 Includes 2 LED amber strobe lights mounted on top of the machine.		\$625
P	356-1198	LIGHTS, HALOGEN, ROPS 35 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS and 519-3979 LIGHTING PREP CANNOT BE USED WITH: 351-3440 LIGHTS, HIGH INTENSITY, ROPS or 515-1429 LIGHTS, LED, ROPS		\$1,155 \$1,155 NI
P	351-3439	LIGHTS, HALOGEN, CAB 31 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS and 519-3979 LIGHTING PREP CANNOT BE USED WITH: 351-3441 LIGHTS, HIGH INTENSITY, CAB or 515-1430 LIGHTS, LED, CAB		\$1,155 \$1,155 NI
P	515-1429	LIGHTS, LED, ROPS 0 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS and 519-3979 LIGHTING PREP CANNOT BE USED WITH: 356-1198 LIGHTS, HALOGEN, ROPS or 351-3440 LIGHTS, HIGH INTENSITY, ROPS		\$2,105 \$2,105 NI
P	515-1430	LIGHTS, LED, CAB 0 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS and 519-3979 LIGHTING PREP CANNOT BE USED WITH: 351-3439 LIGHTS, HALOGEN, CAB or 351-3441 LIGHTS, HIGH INTENSITY, CAB		\$2,105 \$2,105 NI

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

ELECTRICAL (CONT.)

P	351-3440	LIGHTS, HIGH INTENSITY, ROPS	44 0	\$3,650 \$3,650 NI
---	----------	--	---------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Includes 4 high intensity halogen flood lamps mounted to the ROPS canopy, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamps: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.
 ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS and 519-3979 LIGHTING PREP
 CANNOT BE USED WITH: 356-1198 LIGHTS, HALOGEN, ROPS or 515-1429 LIGHTS, LED, ROPS

P	351-3441	LIGHTS, HIGH INTENSITY, CAB	35 0	\$3,650 \$3,650 NI
---	----------	---------------------------------------	---------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Includes 4 high intensity halogen flood lamps mounted to the cab roof, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamps: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.
 ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS and 519-3979 LIGHTING PREP
 CANNOT BE USED WITH: 351-3439 LIGHTS, HALOGEN, CAB or 515-1430 LIGHTS, LED, CAB

TECHNOLOGY PRODUCTS

CAT COMPACTION CONTROL

This is a factory designed and integrated SBAS accuracy level pass count and temperature mapping system which requires no off-board infrastructure. For higher level accuracy consult your Dealer Technology Representative to order the necessary base station, data radio and options keys for RTK corrected position signal. Additionally, the machine connectivity modem identified below, requires cellular data plan sold separately. To view IC Mapping data in the office, a VisionLink subscription with the 3D Project Monitoring module (an add-on to VisionLink) is required.

L	513-6264	SENSORS, MAT TEMPERATURE	0 0	\$3,460 \$3,460 NI
---	----------	------------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Includes front and rear bumper mounted infrared air purged temperature sensors, displayed on the standard LCD display.

L	510-4015	SENSOR, ACCELEROMETER.	0 0	\$5,370 \$5,500 NI
---	----------	--------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Hardware and an accelerometer mounted within the front drum. Output is a unit-less CMV stiffness indication displayed at the operator station.
 ONLY FOR USE WITH: 505-8534 DRUM, SOLID

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT COMPACTION CONTROL (Cont.)

L	514-1273	MAPPING, GNSS 0 Factory install of all components needed for mapping of temperature and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver. Includes: Sensors, Mat Temperature ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS		\$13,930
L	514-1274	MAPPING, GNSS, CAB 0 Factory install of all components needed for mapping of temperature and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver. Includes: Sensors, Mat Temperature ONLY FOR USE WITH: 512-8539 CAB,ROPS/FOPS		\$13,930

MACHINE TO MACHINE COMMUNICATION

Machine to Machine Communication is integrated hardware consisting of an electronic control module, radio and antennas with connecting wiring that enables machines to communicate key compaction data via local wireless and/or cellular data networks.
 Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	567-4607	MACHINE CONNECTIVITY, SNM941 0 FOR USE WITH LANE 3 ONLY SIM card enabled CDMA or GSM network with built in WIFI. ONLY FOR USE WITH: 514-1273 MAPPING, GNSS or 514-1274 MAPPING, GNSS, CAB		\$3,525
---	----------	--	--	---------

OTHER ATTACHMENTS

OPERATOR ENVIRONMENT

P	513-6265	SEAT BELT, 3" 0		\$80
L	360-6861	AIR CONDITIONER 64 ONLY FOR USE WITH: 512-8539 CAB,ROPS/FOPS		\$5,730
P	351-3438	SUN SCREEN 4 Sun screen/visor inside cab. ONLY FOR USE WITH: 512-8539 CAB,ROPS/FOPS		\$408
P	351-3433	MIRRORS, EXTERNAL 20 0		\$570 \$570 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 external adjustable mirrors on the front frame. Secondary set may be purchased and is to be mounted on the rear frame. Mounting provisions are provided standard on the front and rear frame.				
P	462-0499	MIRRORS, EXTERNAL, FRONT 20 20		\$575 \$575 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 external, adjustable mirrors on the front of the cab. ONLY FOR USE WITH: 512-8539 CAB,ROPS/FOPS				

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

OPERATOR ENVIRONMENT (Cont.)

P	462-0500	MIRRORS, EXTERNAL, REAR	20	\$575
			20	\$575 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 external, adjustable mirrors on the rear of the cab. ONLY FOR USE WITH: 512-8539 CAB,ROPS/FOPS				

EDGE MANAGEMENT

P	513-4764	EDGE CUTTER/COMPACTOR	0	\$7,720
			0	\$7,720 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes a straight cutting wheel, capable of cutting up to a 85 mm (3.3 in) lift, and a bevel compaction wheel, capable of edge compacting lifts greater than 96 mm (3.7 in) at a 41 degree bevel. For bevel compacting thinner lifts, between 45-96 mm (1.7-3.7 in), please purchase bevel compaction wheel, 461-5682, from the Caterpillar Parts Network. ONLY FOR USE WITH: 505-8534 DRUM, SOLID and 454-3055 CONTROL, PREMIUM				

WATER SYSTEM - UPGRADES

P	512-8538	MATS, COCOA	0	\$1,295
			0	\$1,295 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER CANNOT BE USED WITH: 512-8537 MATS, WATER DISTRIBUTION				
P	512-8537	MATS, WATER DISTRIBUTION	0	\$1,645
			0	\$1,645 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER CANNOT BE USED WITH: 512-8538 MATS, COCOA				
P	351-3429	FREEZE PROTECTION, ROPS/FOPS	1,279	\$590
Includes a reservoir that holds windshield washer or RV antifreeze that protects water lines, pumps, filters, and nozzles from freezing. ONLY FOR USE WITH: 513-5924 PLATFORM, ROPS/FOPS				
P	351-3427	FREEZE PROTECTION, CAB	4	\$590
Includes a reservoir that holds windshield washer or RV antifreeze that protects water lines, pumps, filters, and nozzles from freezing. ONLY FOR USE WITH: 512-8539 CAB, ROPS/FOPS				

MISC ATTACHMENTS

P	351-3424	COVERS, DRUM	45	\$880
Helps keep debris out of drums. ONLY FOR USE WITH: 505-8534 DRUM, SOLID or				
P	513-4771	STEPS, REFILL ASSIST	0	NC
			0	\$640 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Fold down steps mounted to the left-hand side of the machine. Steps mount to the front and rear drum supports and have a grab handles mounted to the frame side plates for assisting with water and fuel refilling.				

CATERPILLAR MACHINE PRICE LIST

CB8

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

FACTORY SOURCED KITS

P	487-5694	PIVOTING STEER WHEEL 5 FOR USE WITH LANE 3 ONLY ONLY AVAILABLE ON A MISCELLANEOUS ORDER Field installed kit to adapt the standard fixed steering wheel location to one with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers.		\$675 NI
P	483-0536	ACCELEROMETER READY 70 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER. Hardware mounted within the front drum to mount the aftermarket SITECH supplied CM310 accelerometer for CMV measurement. Output is a unit-less CMV stiffness indication displayed on SITECH-supplied mapping system. ONLY FOR USE WITH: 505-8534 DRUM, SOLID		\$3,245 NI

DOCUMENTATION

CERTIFICATES

P	354-8706	YEAR OF MANUFACTURE PLATE 0 Plate attached to PIN plate showing year of Final Plant Shipping date. Available for all regions, but required in Brazil. CANNOT BE USED WITH: 394-6543 CE CERTIFICATION		NC
P	0P-1870	CERTIFICATE OF ORIGIN 0		NC

PACKING

DOMESTIC PACKING

	0P-0210	PACK, DOMESTIC TRUCK 0		NC
--	---------	---	--	-----------

MISCELLANEOUS PACKING

	0P-3651	PACKING, MISC MATERIAL 0 No charge for packing. Applicable freight charges may apply.		NC
--	---------	---	--	-----------