

CATERPILLAR MACHINE PRICE LIST

CD10

CD10 VIBRATORY ASPHALT COMPACTOR
 XUZHOU, CHINA

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

CAT C3.4 inline 4 cylinder, turbo-charged diesel engine (75 kW / 101 HP)
 Cyclonic air cleaner
 Water separator
 Ultra clean fuel filter with integrated electric priming pump
 ECO mode throttle system
 Dual braking systems (service & parking)
 Two-speed hydrostatic transmission

ELECTRICAL

12-volt electric starting
 120 ampere alternator
 Maintenance free battery - 1000 CCA
 Halogen working lights - bumper mounted (2 front-facing and 2 rear-facing)
 Backup alarm and forward warning horn
 Cat engine and vehicle ECMs - ET compatible
 Product link ready

OPERATOR ENVIRONMENT

Isolated ROPS/FOPS structure
 Platform handrails / guardrails
 Four heavy-duty isolation mounts
 Power steering
 Adjustable, suspension, seat
 50 mm (2") wide retractable seat belt
 Adjustable, steering console and control/display console
 Indicator light package with audible warning alarm for:
 -hydraulic oil pressure
 -hydraulic oil temperature
 -engine oil pressure
 -engine coolant temperature
 -glow plugs
 -service fault indicator
 Fuel level gauge
 Water level gauge
 Service hour meter
 Lockable, vandalism guard for instrument panel
 Sliding, rotating seat
 Automatic speed control
 Auto-vibe with adjustable on/off control
 Vibe tachometer
 Speedometer

DRUMS

Smooth drum
 1700 mm (67") wide x 1200 mm (47") diameter
 Two amplitudes with two vibe frequencies

Front and rear self adjusting scraper blades
 Pod-style eccentric weight housing

FLUIDS

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

OTHER STANDARD EQUIPMENT

Locking engine enclosure
 Sealed for life hitch bearings
 Sight gauges:
 -hydraulic tank level
 -air restriction indicator
 Cap lock for hydraulic tank
 Drum steer with safety locks
 Transport tie-down and lift points
 191 L (50 gal) fuel tank capacity
 750 L (198 gal) water tank capacity
 Quick connect hydraulic pressure test ports
 SOS ports
 -engine oil
 Dual spray bar pumps
 Single water spray bar per drum

CATERPILLAR MACHINE PRICE LIST

CD10

CD10 VIBRATORY ASPHALT COMPACTOR XUZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the Base
 Order Management program.**

505-8464	CD10 01A VIBRATORY COMPACTOR 0 LANE 2 - AVAILABLE FROM XUZHOU FACTORY LANE 3 - AVAILABLE FROM XUZHOU FACTORY	\$147,550
0P-4183	CD10 MISC MATL 0 AVAILABLE FROM XUZHOU FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	NC

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

POWERTRAIN

ENGINE

L	565-6385	ENGINE, AB&T EPA Tier 4 Final AB&T certified engine. (Tier 4 Interim credit-using engine)	0	NC
---	----------	---	---	----

DRUM TYPE

L	507-4700	DRUM, SOLID 1700 mm (67") solid drums. REQUIRES: 357-9644 DRUM PREP, SOLID	0	NC
L	507-4703	DRUM, SPLIT 1700 mm (67") split drums to minimize mat tearing while operating at maximum turning. REQUIRES: 509-6731 CONTROL, OPTION	0	\$16,040
L	504-6813	DRUM, SOLID W/OSCILLATION STD 1700 mm (67") solid drums, front drum with conventional vibration and rear drum with oscillatory vibration. Both drums shells are comprised of standard material. REQUIRES: 357-9644 DRUM PREP, SOLID	0	NC
L	507-4704	DRUM, SPLIT, AUTOMATIC 1700 mm (67") split drums to minimize mat tearing while operating at maximum turning. REQUIRES: 509-6731 CONTROL, OPTION 355-3156 SYSTEM, AUTOMATIC	0	\$16,040

HYDRAULICS

VIBRATORY HYDRAULICS

L	358-2744	SYSTEM, 2 AMP, 2 FREQ, VT2 Frequency of 43 Hz (2580 vpm) and 53.3 Hz (3200 vpm). Console switch control for amplitude/frequency setting. ONLY FOR USE WITH: 507-4700 DRUM, SOLID	1,761	\$1,570
L	341-8777	SYSTEM, 2 AMP, 2 FREQ, EC Frequency of 42 Hz (2520 vpm) and 53.3 Hz (3200 vpm). Console switch control for amplitude/frequency setting. ONLY FOR USE WITH: 507-4703 DRUM, SPLIT	1,951	\$12,530
L	504-6810	SYSTEM, 2A/2F, CE W/OSC Frequency of 43 Hz (2580 vpm) and 53.3 Hz (3200 vpm) conventional vibration on the front drum with oscillatory vibration at 40 Hz (2400 vpm) on the rear drum. Console switch control for amplitude / frequency setting for front drum only. 2A/2F front drum with oscillatory rear drum. ONLY FOR USE WITH: 504-6813 DRUM, SOLID W/OSCILLATION STD	0	\$6,140

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

HYDRAULICS (CONT.)

VIBRATORY HYDRAULICS (Cont.)

L	355-3156	SYSTEM, AUTOMATIC	1,378	\$42,610
		Frequency of 42 Hz (2520 vpm) and 53.3 Hz (3200 vpm). Automatic system maximizes amplitude for quicker stiffness gains. Variable amplitude range between .18mm and .84mm. Console switch control for automatic or manual control. Manual controls for both amplitude and frequency are located at the operator's station. ONLY FOR USE WITH: 504-4704 DRUM, SPLIT, AUTOMATIC		

AUXILIARY HYDRAULICS

L	344-0430	STD MACHINE	60	\$2,610
		No chip spreader controls. ONLY FOR USE WITH: 507-4703 DRUM, SPLIT or 507-4704 DRUM, SPLIT, AUTOMATIC CANNOT BE USED WITH: 513-6286 CHIPSPREADER READY		
L	357-9644	DRUM PREP, SOLID	4	NC
		No chipspreader controls. ONLY FOR USE WITH: 507-4700 DRUM, SOLID or 504-6813 DRUM, SOLID W/OSCILLATION STD		
L	356-1782	CHIPSPREADER PREP.	79	\$2,610
		Valves and controls for chip spreader operation. REQUIRES: 513-6286 CHIPSPREADER READY ONLY FOR USE WITH: 507-4703 DRUM, SPLIT or 507-4704 DRUM, SPLIT, AUTOMATIC		

AUXILIARY HYDRAULICS - AUTOMATIC (AAC)

ONLY REQUIRED FOR USE WITH SYSTEM, AUTOMATIC

L	356-0929	MACHINE, AUTO SYS, NO CUTTER	0	NC
		Hydraulic lines for Auto Systems without edge cutter. ONLY FOR USE WITH: 507-4704 DRUM, SPLIT, AUTOMATIC and 344-0430 STD MACHINE or 356-1782 CHIPSPREADER PREP		
L	438-0019	MACHINE, AUTO SYS, W/CUTTER	0	NC
		Hydraulic lines for Auto Systems with edge cutter. REQUIRES: 514-4767 EDGE CUTTER/COMPACTOR ONLY FOR USE WITH: 507-4704 DRUM, SPLIT, AUTOMATIC and 344-0430 STD MACHINE or 356-1782 CHIPSPREADER PREP		

ELECTRICAL

LIGHTING

L	501-6572	LIGHTS, WORKING	0	NC
		Includes 2 front and 2 rear facing clear lights located in the bumpers.		
L	501-6573	LIGHTS, ROADING AND WORKING	0	\$835
		Includes 2 front high beam headlights, 2 rear facing flood lights, front and rear turn signals, and front and rear indicator/parking lights. All lights are attached to the bumpers.		

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

OPERATOR STATION

L	513-5927	PLATFORM, ROPS/FOPS 0 Includes grab handrails and foundation for the sliding and rotating operator station.		NC
L	513-5929	CAB, ROPS/FOPS 0 Includes grab handrails and foundation for the sliding and rotating operator station.		\$12,310

OPERATOR STATION MOVEMENT

L	343-6115	ROTATION, HALF 40 Includes operator station controls, LCD display and station slide and 180 deg rotate levers.		NC
L	356-0924	ROTATION, FULL 75 Includes operator station controls, LCD display and station slide and 359 deg rotate levers.		\$2,040

CONTROL PANEL

L	515-2444	PANEL, PREMIUM 0 16 button control panel for operator control of machine functions. Includes the following: frequency selection; vibratory drum selection, travel speed mode, selectable speed control, speed sensing water spray control, water pump selection, chip spreader controls, amplitude selection, automatic amplitude selection, and drum steering selection.		\$95
---	----------	---	--	------

PROPEL LEVER

L	454-3055	CONTROL, PREMIUM 2 Includes premier wiring and premier 6 button propel lever for propel control, vibratory on/off selection, water spray functions, offset hitch and edge cutter functionality (only if machine is equipped with these options).		\$595
---	----------	--	--	-------

STEERING WHEEL

L	489-6273	STEERING WHEEL, FIXED 0 LH located steering wheel with a fixed location.		NC
L	489-6274	STEERING WHEEL, PIVOTING 0 LH located steering wheel with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers. CANNOT BE USED WITH: 514-1275 MAPPING, GNSS 514-1276 MAPPING, GNSS, CAB		\$675

OPERATOR LANGUAGES

L	527-8200	LANGUAGES, OPTION 1 0 Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

SEAT SELECTION

L	343-6129	SEAT, STD VINYL 157 Vinyl suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back.		NC
L	355-3084	SEAT, HEATED VINYL 163 Heated vinyl suspension seat with fold-up arms rests, retractable seat belt, weight adj., and tilt back.		\$314
L	344-0124	SEAT, STD CLOTH 157 Cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$209
L	355-3085	SEAT, HEATED CLOTH 163 Heated cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$366

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions

L	451-3243	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applicatins. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS		\$432
L	451-3240	PRODUCT LINK, CELLULAR PL641 0 Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS		NC
L	451-3245	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$432

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

PRODUCT LINK (Cont.)

L	451-3242	PRODUCT LINK, CELLULAR PL641	0	NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		

FLUIDS

HYDRAULIC OIL

L	344-0505	OIL, HYD, FACTORY FILLED	289	NC
L	355-3153	OIL, HYD, BIO, FACTORY FILLED FOR USE WITH LANE 3 ONLY Bio degradable oil recommended for hydraulic system when environmental compliance is required or desired.	302	\$620
L	355-3152	OIL, HYD, HIGH AMBIENT Hydraulic Oil recommended for machines operating in high temperature regions.	302	\$366

INSTRUCTIONS

DECAL PACKAGES

P	510-6130	INSTRUCTIONS, NORTH AMERICAN ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).	0	NC
---	----------	--	---	----

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

ELECTRICAL

P	351-3443	LIGHT, ROTATING BEACON 4 Includes 2 LED amber strobe lights mounted on top of the machine.		\$625
P	361-2243	LIGHTS, HALOGEN, ROPS 2.9 0		\$1,155 \$1,155 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machines folded drum supports.
ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS
CANNOT BE USED WITH: 517-1280 LIGHTS, HIGH INTENSITY, ROPS or 515-1439 LIGHTS, LED, ROPS

P	365-1324	LIGHTS, HALOGEN, CAB 2.4 0		\$1,155 \$1,155 NI
---	----------	--	--	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.
ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS
CANNOT BE USED WITH: 515-1440 LIGHTS, LED, CAB or 517-1281 LIGHTS, HIGH INTENSITY, CAB

P	515-1439	LIGHTS, LED, ROPS 0 0		\$2,155 \$2,155 NI
---	----------	---	--	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machines folded drum supports.
ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS
CANNOT BE USED WITH: 361-2243 LIGHTS, HALOGEN, ROPS or 517-1280 LIGHTS, HIGH INTENSITY, ROPS

P	515-1440	LIGHTS, LED, CAB 0 0		\$2,155 \$2,155 NI
---	----------	--	--	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.
ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS
CANNOT BE USED WITH: 365-1324 LIGHTS, HALOGEN, CAB or 517-1281 LIGHTS, HIGH INTENSITY, CAB

P	517-1280	LIGHTS, HIGH INTENSITY, ROPS 0 0		\$3,745 \$3,745 NI
---	----------	--	--	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes 4 high intensity halogen flood lamps mounted to the ROPS canopy, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamps: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.
ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS
CANNOT BE USED WITH: 361-2243 LIGHTS, HALOGEN, ROPS or 515-1439 LIGHTS, LED, ROPS

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

ELECTRICAL (CONT.)

P	517-1281	LIGHTS, HIGH INTENSITY, CAB	0	\$3,745
			0	\$3,745 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes 4 high intensity halogen flood lamps mounted to the cab roof, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamps: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.
ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS
CANNOT BE USED WITH: 365-1324 LIGHTS, HALOGEN, CAB or 515-1440 LIGHTS, LED, CAB

TECHNOLOGY PRODUCTS

CAT COMPACTION CONTROL

This is a factory designed and integrated SBAS accuracy level pass count and temperature mapping system which requires no off-board infrastructure. For higher level accuracy consult your Dealer Technology Representative to order the necessary base station, data radio and options keys for RTK corrected position signal. Additionally, the machine connectivity modem identified below, requires cellular data plan sold separately. To view IC Mapping data in the office, a VisionLink subscription with the 3D Project Monitoring module (an add-on to VisionLink) is required.

L	499-4640	SENSORS, MAT TEMPERATURE	0	\$3,545
			0	\$3,545 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes front and rear bumper mounted infrared air purged temperature sensors, displayed on the standard LCD display.

L	510-4015	SENSOR, ACCELEROMETER.	0	\$5,370
			0	\$5,500 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Hardware and an accelerometer mounted within the front drum. Output is a unit-less CMV stiffness indication displayed at the operator station.
ONLY FOR USE WITH: 507-4700 DRUM, SOLID or 504-6813 DRUM, SOLID W/OSCILLATION STD

L	513-6290	SENSOR, ACCELEROMETER.	0	\$5,370
			0	\$5,370 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Hardware and an accelerometer mounted within the front drum. Output is a unit-less CMV stiffness indication displayed at the operator station.
ONLY FOR USE WITH: 507-4703 DRUM, SPLIT

L	514-1275	MAPPING, GNSS	0	\$14,290
---	----------	-------------------------	---	----------

Factory install of all components needed for mapping of temperature, and machine pass count.
Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver.
Includes: Sensor, Mat Temperature
ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT COMPACTION CONTROL (Cont.)

L	514-1276	MAPPING, GNSS, CAB 0 Factory install of all components needed for mapping of temperature, and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver. Includes: Sensor, Mat Temperature ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$14,290
---	----------	---	--	-----------------

MACHINE TO MACHINE COMMUNICATION

Machine to Machine Communication is integrated hardware consisting of an electronic control module, radio and antennas with connecting wiring that enables machines to communicate key compaction data via local wireless and/or cellular data networks.
Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	567-4607	MACHINE CONNECTIVITY, SNM941 0 FOR USE WITH LANE 3 ONLY SIM card enabled CDMA or GSM network with built in WIFI. ONLY FOR USE WITH: 514-1275 MAPPING, GNSS or 514-1276 MAPPING, GNSS, CAB		\$3,525
---	----------	--	--	----------------

OTHER ATTACHMENTS

OPERATOR ENVIRONMENT

P	513-6265	SEAT BELT, 3" 0		\$80
P	344-0509	AIR CONDITIONER 66 ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$5,730
P	351-3438	SUN SCREEN 4 Sun screen/visor inside cab. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$408
P	462-0499	MIRRORS, EXTERNAL, FRONT 20 20 ALSO AVAILABLE ON A MISCELLANEOUS ORDER. Includes 2 external, adjustable mirrors on the front of the cab. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$575 \$575 NI
P	462-0500	MIRRORS, EXTERNAL, REAR 20 20 ALSO AVAILABLE ON A MISCELLANEOUS ORDER. Includes 2 external, adjustable mirrors on the rear of the cab. ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS		\$575 \$575 NI

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

EDGE MANAGEMENT

P	513-4762	EDGE CUTTER/COMPACTOR	0 0	\$8,290 \$8,290 NI
---	----------	---------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes a straight cutting wheel, capable of cutting up to a 85 mm (3.3 in) lift, and a bevel compaction wheel, capable of edge compacting lifts to greater than 96 mm (3.7 in) at a 41 degree bevel.
For a bevel compacting thinner lifts, between 45-96 mm (1.7-3.7 in), please purchase bevel compaction wheel, 461-2682, from the Caterpillar Parts Network.

ONLY FOR USE WITH: 507-4700 DRUM, SOLID or
504-6813 DRUM, SOLID W/OSCILLATION STD

P	513-4767	EDGE CUTTER/COMPACTOR	0 0	\$8,290 \$8,290 NI
---	----------	---------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
Includes a straight cutting wheel, capable of cutting up to a 85 mm (3.3 in) lift, and a bevel compaction wheel, capable of edge compacting lifts to greater than 96 mm (3.7 in) at a 41 degree bevel.
For a bevel compacting thinner lifts, between 45-96 mm (1.7-3.7 in), please purchase bevel compaction wheel, 461-2682, from the Caterpillar Parts Network.

ONLY FOR USE WITH: 507-4703 DRUM, SPLIT or
507-4704 DRUM, SPLIT, AUTOMATIC

WATER SYSTEM - UPGRADES

P	511-7007	MATS, COCOA	0 0	\$1,295 \$1,295 NI
---	----------	-----------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
CANNOT BE USED WITH: 511-7006 MATS, WATER DISTRIBUTION

P	511-7006	MATS, WATER DISTRIBUTION	0 0	\$1,645 \$1,645 NI
---	----------	------------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER.
CANNOT BE USED WITH: 511-7007 MATS, COCOA

P	351-3428	FREEZE PROTECTION, ROPS/FOPS	9	\$590
---	----------	--	---	-------

Includes a reservoir that holds windshield washer or RV antifreeze that protects lines, pumps, filters, and nozzles from freezing.
ONLY FOR USE WITH: 513-5927 PLATFORM, ROPS/FOPS

P	355-3140	FREEZE PROTECTION, CAB	7	\$590
---	----------	----------------------------------	---	-------

Includes a reservoir that holds windshield washer or RV antifreeze that protects lines, pumps, filters, and nozzles from freezing.
ONLY FOR USE WITH: 513-5929 CAB, ROPS/FOPS

MISC ATTACHMENTS

L	509-6731	CONTROL, OPTION	0	\$422
---	----------	---------------------------	---	-------

Includes electronic control for full functions of option.
Maximum of 1 per machine.
ONLY FOR USE WITH: 507-4702 DRUM, SPLIT or
507-4704 DRUM, SPLIT, AUTOMATIC and/or
513-6260 ROAD HOMOLOGATION ITALY

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
OTHER ATTACHMENTS (CONT.)				
<i>MISC ATTACHMENTS (Cont.)</i>				
L	513-6286	CHIPSPREADER READY 0 Mounting brackets, includes all electrical, hydraulic, and mechanical interfaces and control system for Strassmeyer model BS-WA-CAT chip spreader. Cannot be used with machines shipping to Italy. REQUIRES: 356-1782 CHIPSPREADER PREP and 507-4703 DRUM, SPLIT or 507-4704 DRUM, SPLIT, AUTOMATIC		\$5,510
P	351-3425	COVERS, DRUM 97 Helps keep debris out of drums. ONLY FOR USE WITH: 507-4700 DRUM, SOLID or 504-6813 DRUM, SOLID W/OSCILLATION STD		\$880
P	460-5246	BALLAST, 500 KG 500 FOR USE WITH LANE 3 ONLY Adds 500 kg (1102 lbs) additional weight to the machine mass to meet French VT2 specification. ONLY FOR USE WITH: 358-2744 SYSTEM, 2 AMP, 2 FREQ, VT2		\$3,880
P	513-4771	STEPS, REFILL ASSIST 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Fold down steps mounted to the left-hand side of the machine. Steps mount to the front and rear drum supports and have a grab handles mounted to the frame side plates for assisting with water and fuel refilling.	0	NC \$640 NI
FACTORY SOURCED KITS				
P	487-5694	PIVOTING STEER WHEEL 5 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed kit to adapt the standard fixed steering wheel location to one with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers.		\$675 NI
P	513-6288	CHIPSPREADER READY FLD 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes valves, controls, mounted brackets, includes all electrical, hydraulics, and mechanical interfaces and control system for Straussmeyer model BW-WA-CAT chip spreader. Requires machine equipped with split drums. CANNOT BE USED with machines shipping to Italy		\$8,180 NI
P	504-6807	DRUM KIT, REAR, OSC, FLD 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 1700 mm (67") rear oscillatory drum consisting of standard shell material for field installation into CB10, CB54B, CD10 or CD54B.		\$20,850 NI

CATERPILLAR MACHINE PRICE LIST

CD10

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

FACTORY SOURCED KITS (CONT.)

P	483-0536	ACCELEROMETER READY 70 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hardware mounted within the front drum to mount the aftermarket SITECH supplied CM310 accelerometer for CMV measurement. Output is a unit-less CMV stiffness indication displayed on SITECH-supplied mapping system. ONLY FOR USE WITH: 507-4700 DRUM, SOLID or 504-6813 DRUM, SOLID W/OSCILLATION STD		\$3,245 NI
---	----------	--	--	-------------------

DOCUMENTATION

CERTIFICATES

P	354-8706	YEAR OF MANUFACTURE PLATE 0 Plate attached to PIN plate showing year of Final Plant Shipping Date. Required for all machines shipping to Brazil. CANNOT BE USED WITH: 394-6546 CE CERTIFICATION		NC
	OP-4990	CERTIFICATE OF ORIGIN 0		\$168

PACKING

	OP-4507	ROLL ON-ROLL OFF 0		\$595 NET
	OP-6706	BUNDLE EXPORT PACKING 0 This OP should be ordered for miscellaneous orders		NC