



SP900

Machine Specific

General:

Weight:	220 Pounds
Length:	77 Inches
Height:	44 Inches
Width:	24 Inches
Tires:	13 X 500 X 6
Tire Pressure:	40 PSI
Controls:	Handlebar Mounted
Fuel Capacity:	1.72 Gallons

Engine:

Manufacturer:	Honda GX390K1
Number of Cylinders:	One Cylinder with Overhead Valves
Bore:	64 mm
Stroke:	88 mm
Displacement:	389 cubic cm
Maximum RPM:	3600
Horsepower:	13
Cooling Medium:	Air
Air Cleaner:	Dry Type with Precleaner
Oil Capacity:	1.1 quarts
Fuel Capacity:	1.72 US Gallons
Electrical:	12 Volt

Drive System:

Engine Sheave:	4/3V3.0
Cutter Head Sheave:	2B3.4
Drive Belt:	Two Band RPB-56-Z
Cutter Head Shaft:	1 ¼ Inch
Engine Engagement:	Cebtrifical Clutch
Belt and Chain Shields:	Metal Bolt On

Bearings:

Cutter Head Bearings: 1 ¼ Inch Tap

Cutter Wheel:

Wheel Diameter:	12 ½ Inches v
Wheel Thickness:	½ Inch
Wheel Speed:	1350 RPM N
Number of Teeth:	12 Carbide T
Chip Guards:	Rubber and N

Cutting Dimensions:

Below Ground:	
Above Ground:	9 Inches
	21 Inches

[Return to SP900 Price Sheet](#)

[Return to Index](#)

ations

ered Roller Bearings

with Teeth

ominal
ipped
metal