

**AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS**

**25A Flail Mower with Heavy Duty Roller and 9 In. Offset  
Equipment for Base Machine**

Cutting Height 1/2 to 5 Inch  
Cutting Width 78 Inches  
Three Bank Rotor 17-1/4 Inch Diameter  
36 Heat Treated Knives  
Built-In Tractor Hookup  
PTO Shields  
PTO-540 RPM  
65 Continuous, 90 Intermittent  
HP Rated Gearbox

Heavy Duty Gauge Roller with Anti-Friction  
Self-Aligning Bearings

*For Tractors Equipped with Category 1 3-Point Hitch*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas or Moline, Illinois*

0488P		25A Flail Mower with Heavy Duty Roller and 9 In. Offset	5,490.00
-------	--	---	----------

**OPERATOR'S MANUAL AND DECALS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9020		French Operator's Manuals and Labels	No Charge
------	--	--------------------------------------	-----------

**RUBBER DEFLECTORS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9010		Rubber Deflector Shield for Rear Mounting	203.00
------	--	---	--------

**HITCH ADAPTERS**

9002		Hitch adapter for category 2 hitches	69.00
------	--	--------------------------------------	-------

**ATTACHMENTS FOR FIELD CONVERSION**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

	<b>Miscellaneous</b>		
BE10236		Hitch Adapter for Category 2 Hitch	72.60
BP16369		Rubber Deflector Shield for Rear Mounting	223.30

AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS

---

**25A Flail Mower with Heavy Duty Roller and 9 In. Offset**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE FLAIL MOWERS**

**360 Heavy Duty Flail Mower**  
Equipment for Base Machine

Cutting Height: 1/2 to 5 In.  
Cutting Width: 58.5 In.  
Heat Treated Side-Slicer Knives: 54  
Built-In Tractor Hook-Up: Cat. I/II  
PTO Shields  
PTO - 540 RPM  
Rotor Bearings 1-3/8 In. in Cast Mountings  
Skid Shoes  
Replaceable Skid Plates  
3-Bank Rotor 17 1/4 In. Diameter at  
Knife Tips

Bearing Shield Rings Inside  
Anti-Wrap System  
65 Continuous, 90 Intermittent HP  
Rated Gearbox  
Bearing Protection Guards Outside

*For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas or Moline, Illinois*

0484P		360 Heavy Duty Flail Mower	5,594.00
-------	--	----------------------------	----------

**KNIVES CONFIGURATION**

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-138.00

**OPERATOR'S MANUAL AND DECALS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9020		French Operator's Manuals and Labels	No Charge
------	--	--------------------------------------	-----------

**RUBBER DEFLECTORS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9010		Rubber Deflector Shield for Rear Mounting	121.00
------	--	---	--------

**ATTACHMENTS FOR FIELD CONVERSION**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

	<b>Miscellaneous</b>		
BP16371	Rubber Deflector Shield for Rear Mounting		133.10
E31900	Smooth-Cut Knives		2.40

AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS

---

**360 Heavy Duty Flail Mower**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE FLAIL MOWERS**

**370 Heavy Duty Flail Mower**  
Equipment for Base Machine

Cutting Height: 1/2 to 5 In.  
Cutting Width: 71.5 In.  
Heat Treated Side-Slicer Knives: 66  
Built-In Tractor Hook-Up: Cat. I/II  
PTO Shields  
PTO - 540 RPM  
Rotor Bearings 1-3/8 In. in Cast Mountings  
Skid Shoes  
Replaceable Skid Plates  
3-Bank Rotor 17 1/4 In. Diameter at  
Knife Tips

Bearing Shield Rings Inside  
Anti-Wrap System  
65 Continuous, 90 Intermittent HP  
Rated Gearbox  
Bearing Protection Guards Outside

*For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas or Moline, Illinois*

0485P		370 Heavy Duty Flail Mower	6,141.00
-------	--	----------------------------	----------

**DESTINATION**

0202		United States	In Base Price
0184		Canada	No Added Cost
0195		Mexico	No Added Cost
0182		Barbados	No Added Cost
0188		Dominican Republic	No Added Cost
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost

AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS

**370 Heavy Duty Flail Mower**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>DESTINATION ...Continued...</b>	
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0220		Uruguay	No Added Cost
0221		Venezuela	No Added Cost

**KNIVES CONFIGURATION**

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-173.00

**OPERATOR'S MANUAL AND DECALS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9020		French Operator's Manuals and Labels	No Charge
------	--	--------------------------------------	-----------

**RUBBER DEFLECTORS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9010		Rubber Deflector Shield for Rear Mounting	134.00
------	--	---	--------

**ATTACHMENTS FOR FIELD CONVERSION**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

	<b>Miscellaneous</b>		
BP16370		Rubber Deflector Shield for Rear Mounting	147.40
E31900		Smooth-Cut Knives	2.40

**AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS**

**390 Heavy Duty Flail Mower - Center Pull  
Equipment for Base Machine**

Cutting Height: 1/2 to 5 In.  
Cutting Width: 90.5 In.  
Heat Treated Side-Slicer Knives: 84  
Built-In Tractor Hook-Up: Cat. I/II  
PTO Shields  
PTO - 540 RPM  
Rotor Bearings 1-3/8 In. in Cast Mountings  
Skid Shoes  
Replaceable Skid Plates  
3-Bank Rotor 17 1/4 In. Diameter at  
Knife Tips

Bearing Shield Rings Inside  
Anti-Wrap System  
65 Continuous, 90 Intermittent HP  
Rated Gearbox  
Bearing Protection Guards Outside

*For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas or Moline, Illinois*

0486P		390 Heavy Duty Flail Mower - Center Pull	6,939.00
-------	--	--	----------

**KNIVES CONFIGURATION**

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-225.00

**OPERATOR'S MANUAL AND DECALS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9020		French Operator's Manuals and Labels	No Charge
------	--	--------------------------------------	-----------

**RUBBER DEFLECTORS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9010		Rubber Deflector Shield for Rear Mounting	152.00
------	--	---	--------

**ATTACHMENTS FOR FIELD CONVERSION**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

	<b>Miscellaneous</b>		
BP16368	Rubber Deflector Shield for Rear Mounting		167.20
E31900	Smooth-Cut Knives		2.40

AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS

---

**390 Heavy Duty Flail Mower - Center Pull**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS**

**390 Heavy Duty Flail Mower - 12 In. Offset  
Equipment for Base Machine**

Cutting Height: 1/2 to 5 In.  
Cutting Width: 90.5 In.  
Heat Treated Side-Slicer Knives: 84  
Built-In Tractor Hook-Up: Cat. I/II  
PTO Shields  
PTO - 540 RPM  
Rotor Bearings 1-3/8 In. in Cast Mountings  
Skid Shoes  
Replaceable Skid Plates  
3-Bank Rotor 17 1/4 In. Diameter at  
Knife Tips

Bearing Shield Rings Inside  
Anti-Wrap System  
65 Continuous, 90 Intermittent HP  
Rated Gearbox  
Bearing Protection Guards Outside

*For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas or Moline, Illinois*

0487P		390 Heavy Duty Flail Mower - 12 In. Offset	6,939.00
-------	--	--	----------

**KNIVES CONFIGURATION**

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-225.00

**OPERATOR'S MANUAL AND DECALS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9020		French Operator's Manuals and Labels	No Charge
------	--	--------------------------------------	-----------

**RUBBER DEFLECTORS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9010		Rubber Deflector Shield for Rear Mounting	152.00
------	--	---	--------

**ATTACHMENTS FOR FIELD CONVERSION**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

	<b>Miscellaneous</b>		
BP16368		Rubber Deflector Shield for Rear Mounting	167.20
E31900		Smooth-Cut Knives	2.40

AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS

---

**390 Heavy Duty Flail Mower - 12 In. Offset**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS**

**390 Heavy Duty Flail Mower - 26 In. Offset  
Equipment for Base Machine**

Cutting Height: 1/2 to 5 In.  
Cutting Width: 90.5 In.  
Heat Treated Side-Slicer Knives: 84  
Built-In Tractor Hook-Up: Cat. I/II  
PTO Shields  
PTO - 540 RPM  
Rotor Bearings 1-3/8 In. in Cast Mountings  
Skid Shoes  
Replaceable Skid Plates  
3-Bank Rotor 17 1/4 In. Diameter at  
Knife Tips

Bearing Shield Rings Inside  
Anti-Wrap System  
65 Continuous, 90 Intermittent HP  
Rated Gearbox  
Bearing Protection Guards Outside

*For Tractors Equipped with Cat. I/II Hitch and 540 RPM PTO.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas or Moline, Illinois*

0494P		390 Heavy Duty Flail Mower - 26 In. Offset	6,939.00
-------	--	--	----------

**KNIVES CONFIGURATION**

1000		Heat Treated Side-Slicer Knives	In Base Price
1010		Smooth-Cut Knives	-225.00

**OPERATOR'S MANUAL AND DECALS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9020		French Operator's Manuals and Labels	No Charge
------	--	--------------------------------------	-----------

**RUBBER DEFLECTORS**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

9010		Rubber Deflector Shield for Rear Mounting	152.00
------	--	---	--------

**ATTACHMENTS FOR FIELD CONVERSION**

*Attachments ordered for field conversion will be shipped EX-WORKS Moline, Illinois.*

	<b>Miscellaneous</b>		
BP16368		Rubber Deflector Shield for Rear Mounting	167.20
E31900		Smooth-Cut Knives	2.40

AGRICULTURAL PRODUCTS  
JOHN DEERE FLAIL MOWERS

---

**390 Heavy Duty Flail Mower - 26 In. Offset**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---