

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### E12 Flex Wing Rotary Cutter Equipment for Base Machine

<p>Pull Type 12 Ft. (3.7 m) Cutting Width 2 In. Brush Cutting Capacity Four Gear cases Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 75 HP (55.1 kW) Peak Horsepower Rating: Splitter 300 HP (224 kW) Wing : 100 HP (75 kW) 1-3/4 In. Gear case Input Shafts Xxx in Gear case output shaft Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Tubular Telescoping Driveshaft Members Easy Clean Dome Shaped Welded Wear skid shoes Frames: Deck Thickness: 0.12 in (3 mm) 11 gauge Body Depth 10 In. (276 mm) 1/4 In. (6 mm) Side Skirt Thickness (3 gauge) 3-Section Flexible</p>	<p>90 Degrees Up for transportation Working angles: 22 Degrees Down, 45 Degrees Up Pivot Pins with Single Bushings Grease-able Hinges Blade Tip Speed: 17,047 fpm, (86.6 m/s) Double Leveling Rods for tip adjustment Easy Adjust Wing Leveling Turnbuckles Standard Self Level Hitch Clevis 30 mm Front and Rear Safety Shields - Chains Safety Tow Chain Hitch Integrated Jack Stand Implement Jack SMV Emblem and Support Transport light kit - comply with regulations Fully Assembled Heavy Duty Rating Intermittent, 4-Bolt Wheel Hubs - Four Wheels</p>
--	--

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2290P		E12 Flex Wing Rotary Cutter <i>Serial Number 1Y80E12CZJT412000 and above.</i>	14,276.00
-------	--	--	-----------

#### DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0186		Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

#### TIRES

		<b>Laminated Tires</b> 4 Laminated Tires - (Single tires on center and wings) - Puncture proof	-293.00
3010			
		<b>Severe Duty Tires</b> 4 Pneumatic Tires - (Single tires on center and wings) - Severe duty ag tires	In Base Price
3020			

#### OPERATOR'S MANUAL, DECALS, AND LANGUAGE

AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS

**E12 Flex Wing Rotary Cutter**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
<b>...Continued...</b>			
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge
9043		Text Free Operator's Manual and Decal Kit	No Charge
<b>BLADES</b>			
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
<b>INDEPENDENT CONTROL VALVE</b>			
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	851.00
<b>WING CYLINDER HOSE</b>			
9150		Extra Wing Cylinder Hose	101.00

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### E15 Flex wing Rotary Cutter Equipment for Base Machine

<p>Pull Type 15 Ft. (4.6 m) Cutting Width 2 In. Brush Cutting Capacity Four Gear cases Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 75 HP (55.1 kW) Peak Horsepower Rating: Splitter 300 HP (224 kW) Wing : 100 HP (75 kW) 1-3/4 In. Gear case Input Shafts Xxx in Gear case output shaft Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Tubular Telescoping Driveshaft Members Easy Clean Dome Shaped Welded Wear skid shoes Frames: Deck Thickness: 0.12 in (3 mm) 11 gauge Body Depth 10 In. (276 mm) 1/4 In. (6 mm) Side Skirt Thickness (3 gauge) 3-Section Flexible</p>	<p>90 Degrees Up for transportation Working angles: 22 Degrees Down, 45 Degrees Up Pivot Pins with Single Bushings Grease-able Hinges Blade Tip Speed: 17,281 fpm, (87.8 m/s) Double Leveling Rods for tip adjustment Easy Adjust Wing Leveling Turnbuckles Standard Self Level Hitch Clevis 30 mm Front and Rear Safety Shields - Chains Safety Tow Chain Hitch Integrated Jack Stand Implement Jack SMV Emblem and Support Transport light kit - comply with regulations Fully Assembled Heavy Duty Rating Intermittent, 4-Bolt Wheel Hubs - Four Wheels</p>
--	--

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

230AP		E15 Flex wing Rotary Cutter <i>Serial Number 1Y80E15CZJT414000 and above</i>	17,304.00
-------	--	---	-----------

#### DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0186		Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

#### TIRES

<b>Laminated Tires</b>			
3010		4 Laminated Tires - (Single tires on center and wings) - Puncture proof	-293.00
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof	440.00
<b>Severe Duty Tires</b>			
3020		4 Pneumatic Tires - (Single tires on center and wings) - Severe duty ag tires	In Base Price

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

**E15 Flex wing Rotary Cutter  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>TIRES ...Continued...</b>	
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires	875.00
<hr/>			
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge
9043		Text Free Operator's Manual and Decal Kit	No Charge
		<b>BLADES</b>	
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
		<b>INDEPENDENT CONTROL VALVE</b>	
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	851.00
		<b>WING CYLINDER HOSE</b>	
9150		Extra Wing Cylinder Hose	101.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

**M15 Flex Wing Rotary Cutter  
Equipment for Base Machine**

Pull Type  
15 Ft. (4.6 m) Cutting Width  
3 In. Brush Cutting Capacity  
Four Gear cases  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing : 100 HP (75 kW)  
Peak Horsepower Rating:  
Splitter 300 HP (224 kW)  
Wing 150 HP (111 kW)  
1-3/4 In. Gear case Input Shafts  
Xxx in Gear case output shaft  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches,  
Tubular Telescoping Driveshaft Members  
Easy Clean Dome Shaped  
Replaceable bolt on Wear skid shoes  
Frames:  
Deck Thickness: 0.14 in (3.5 mm) 10 gauge  
Body Depth 10 In. (276 mm)  
1/4 In. (6 mm) Side Skirt Thickness (3 gauge)  
3-Section Flexible  
90 Degrees Up for transportation

Working angles: 22 Degrees Down, 45 Degrees Up  
Pivot Pins with Single Bushings  
Grease-able Hinges  
Blade Tip Speed:  
540 rpm: 15,586 fpm, (79.2 m/s)  
1000 rpm: 15,837 fpm, (80.5 m/s)  
Double Leveling Rods for tip adjustment  
Easy Adjust Wing Leveling Turnbuckles  
Front and Rear Safety Shields single row chains  
Safety Tow Chain  
Hitch Integrated Jack Stand (on rigid casting hitch)  
Implement Jack  
SMV Emblem and Support Transport light kit - comply with regulations  
Fully Assembled Heavy Duty Rating Intermittent,  
4-Bolt Wheel Hubs - Six Wheels

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2310P	M15 Flex Wing Rotary Cutter <i>Serial Number 1Y80M15CZJE416000 and above.</i>	22,821.00
-------	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0186	Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

**BLADE ROTATION**

2540	Basic Outward Rotation <i>All machines will come standard with outward rotation. It helps with the material distribution.</i>	In Base Price
2541	Inward Rotation - For governmental business <i>Will only be available in 15 ft models M and R spec. This configuration will be build to order, will have different lead time and its purpose is for bids that require an inward rotation.</i>	No Added Cost

**GEARBOX**

---

**AGRICULTURAL PRODUCTS**  
**FLEX-WING ROTARY CUTTERS**

---

**M15 Flex Wing Rotary Cutter**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
3600		<b>GEARBOX ...Continued...</b> 540 RPM -100 hp Gearbox	In Base Price
3601		540 RPM - 100 hp Gearbox - Inward rotation	No Added Cost
3602		540 RPM - 125 hp Gearbox - Commercial duty	647.00
3603		540 RPM - 125 hp Gearbox - Commercial duty - Inward rotation	647.00
3639		1000 RPM - 100 hp Gearbox	No Added Cost
3640		1000 RPM - 100 hp Gearbox - Inward rotation	No Added Cost
3641		1000 RPM - 125 hp Gearbox - Commercial duty	647.00
3642		1000 rpm - 125 hp Gearbox - Commercial duty - Inward rotation	647.00
<hr/> <b>DRIVELINES</b> <hr/>			
3510		540 RPM Driveline	In Base Price
3511		540 RPM Driveline - Cat 6	In Configuration
3539		1000 RPM Driveline - 1 3/8" coupler	In Configuration
3541		1000 RPM Driveline - 1 3/8" coupler - Cat 6	In Configuration
3543		1000 RPM Driveline - 1 3/4" coupler	In Configuration
3545		1000 RPM Driveline - 1 3/4" coupler - Cat 6	In Configuration
<hr/> <b>BLADE HOLDER</b> <hr/>			
2500		Blade Pan	In Base Price
2501		Blade Pan - 125 hp	No Added Cost
2502		Blade Bar - Double blade	673.00
<hr/> <b>SUSPENSION</b> <hr/>			
1200		Spring Suspension	In Base Price
1210		Torsional Suspension	848.00
<hr/> <b>TONGUE</b> <hr/>			
5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	672.00
<hr/> <b>HITCH</b> <hr/>			
5110		Clevis Hitch	In Base Price
5120		Ball Type Hitch	259.00
5140		Swivel Hitch	430.00

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### M15 Flex Wing Rotary Cutter Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>TIRES</b>			
<b>Laminated Tires</b>			
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof	-436.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof	297.00
<b>Severe Duty Tires</b>			
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires	875.00
<b>Foam Filled Tires</b>			
3035		6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires	347.00
3335		8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires	1,328.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge
9043		Text Free Operator's Manual and Decal Kit	No Charge
<b>BLADES</b>			
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
<b>WALKING TANDEM</b>			
9300		Walking Tandem Kit <i>Kit just for center section. For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,917.00
<b>INDEPENDENT CONTROL VALVE</b>			
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	851.00
<b>WING CYLINDER HOSE</b>			
9150		Extra Wing Cylinder Hose	101.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

---

**M15 Flex Wing Rotary Cutter**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### M20 Flex wing Rotary Cutter Equipment for Base Machine

<p>Pull Type 20 Ft. (6.1 m) Cutting Width 3 In. Brush Cutting Capacity Four Gear cases Continuous Horsepower Rating:     Splitter 250 HP (186 kW)     Wing : 100 HP (75 kW) Peak Horsepower Rating:     Splitter 300 HP (224 kW)     Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts Xxx in Gear case output shaft Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Tubular Telescoping Driveshaft Members Easy Clean Dome Shaped Replaceable bolt on Wear skid shoes Frames:     Deck Thickness: 0.14 in (3.5 mm) 10 gauge     Body Depth 10 In. (276 mm)     1/4 In. (6 mm) Side Skirt Thickness (3 gauge) 3-Section Flexible 90 Degrees Up for transportation</p>	<p>Working angles: 22 Degrees Down, 45 Degrees Up Pivot Pins with Single Bushings Grease-able Hinges Blade Tip Speed:     540 rpm: 16,087 fpm, (81.7 m/s)     1000 rpm: 16,346 fpm, (83.5 m/s) Double Leveling Rods for tip adjustment Easy Adjust Wing Leveling Turnbuckles Front and Rear Safety Shields single row chains Safety Tow Chain Hitch Integrated Jack Stand (on rigid casting hitch) Implement Jack SMV Emblem and Support Transport light kit - comply with regulations Fully Assembled Heavy Duty Rating Intermittent, 4-Bolt Wheel Hubs - Six Wheels</p>
--	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2320P		M20 Flex wing Rotary Cutter <i>Serial Number 1Y80M20FZJE418000 and above</i>	29,397.00
-------	--	---	-----------

#### DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0186		Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

#### GEARBOX

3600		540 RPM -100 hp Gearbox	No Added Cost
3602		540 RPM - 125 hp Gearbox - Commercial duty	647.00
3639		1000 RPM - 100 hp Gearbox	In Base Price
3641		1000 RPM - 125 hp Gearbox - Commercial duty	647.00

#### DRIVELINES

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### M20 Flex wing Rotary Cutter Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DRIVELINES ...Continued...</b>			
3510		540 RPM Driveline	In Configuration
3511		540 RPM Driveline - Cat 6	In Configuration
3539		1000 RPM Driveline - 1 3/8" coupler	In Base Price
3541		1000 RPM Driveline - 1 3/8" coupler - Cat 6	In Configuration
3543		1000 RPM Driveline - 1 3/4" coupler	In Configuration
3545		1000 RPM Driveline - 1 3/4" coupler - Cat 6	In Configuration
<b>BLADE HOLDER</b>			
2500		Blade Pan	In Base Price
2501		Blade Pan - 125 hp	No Added Cost
2502		Blade Bar - Double blade	673.00
<b>SUSPENSION</b>			
1200		Spring Suspension	In Base Price
1210		Torsional Suspension	848.00
<b>TONGUE</b>			
5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	672.00
<b>HITCH</b>			
5110		Clevis Hitch	In Base Price
5120		Ball Type Hitch	259.00
<b>TIRES</b>			
<b>Laminated Tires</b>			
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof	-436.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof	297.00
<b>Severe Duty Tires</b>			
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires	875.00
<b>Foam Filled Tires</b>			
3035		6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires	347.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

**M20 Flex wing Rotary Cutter**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
3335		<b>TIRES ...Continued...</b> 8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires	1,328.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge
9043		Text Free Operator's Manual and Decal Kit	No Charge
<b>BLADES</b>			
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
<b>SHREDDING KIT</b>			
9200		Shredding Kit <i>It is a diamond base to attach on the blade bar and add 4 more blades to each blade bar configuration, resulting in 8 blades per spindle.</i>	1,638.00
<b>WALKING TANDEM</b>			
9300		Walking Tandem Kit <i>Kit just for center section. For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,917.00
<b>INDEPENDENT CONTROL VALVE</b>			
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	851.00
<b>WING CYLINDER HOSE</b>			
9150		Extra Wing Cylinder Hose	101.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

---

**M20 Flex wing Rotary Cutter**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

**R10 Flex wing Rotary Cutter  
Equipment for Base Machine**

Pull Type  
10 Ft. (3 m) Cutting Width  
4 In. Brush Cutting Capacity  
Three Gear cases  
Continuous Horsepower Rating:  
  Splitter 250 HP (186 kW)  
  Wing : 125 HP (93 kW)  
Peak Horsepower Rating:  
  Splitter 300 HP (224 kW)  
  Wing 194 HP (145 kW)  
1-3/4 In. Gear case Input Shafts  
Xxx in Gear case output shaft  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline Cat 6  
Two Slip Clutches,  
Tubular Telescoping Driveshaft Members  
Easy Clean Dome Shaped  
Replaceable bolt on Wear skid shoes  
Frames:  
  Deck Thickness: 0.17 in (4.5 mm) 7ga  
  Body Depth 10 In. (276 mm)  
  1/4 In. (6 mm) Side Skirt Thickness  
2-Section Flexible + counterweight  
90 Degrees Up for transportation

Working angles: 22 Degrees Down, 45 Degrees Up  
Pivot Pins with Single Bushings  
Maintenance free bushings on hinges  
Blade Tip Speed:  
  540 rpm: 15,586 fpm, (79.2 m/s)  
Double Leveling Rods for tip adjustment  
Easy Adjust Wing Leveling Turnbuckles  
Front and Rear Safety Shields single row chains  
Safety Tow Chain  
Hitch Integrated Jack Stand (on rigid casting hitch)  
Implement Jack  
SMV Emblem and Support Transport light kit - comply with regulations  
Fully Assembled Heavy Duty Rating Intermittent, 5-Bolt Wheel Hubs with sealed bearings - five Wheels

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2330P		R10 Flex wing Rotary Cutter <i>Serial Number 1Y80R10EZJB424000 and above.</i>	21,460.00
-------	--	--	-----------

**DESTINATION**

0202		United States	In Base Price
0184		Canada	No Added Cost
0186		Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

**DRIVELINES**

3511		540 RPM Driveline - Cat 6	In Base Price
------	--	---------------------------	---------------

**TONGUE**

5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	672.00

**HITCH**

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### R10 Flex wing Rotary Cutter Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
5110		<b>HITCH ...Continued...</b> Clevis Hitch	-259.00
5120		Ball Type Hitch	In Base Price
<b>TIRES</b>			
3015		<b>Laminated Tires</b> 6 Laminated Tires - (Double center, single on wings) - Puncture proof <i>For R10 - 5 Tires ( Double center, single on wing)</i>	-673.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof <i>For R10 - 6 Tires (Double tires on center and wing)</i>	59.00
3025		<b>Severe Duty Tires</b> 6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires <i>For R10 - 5 Tires (Double tire on center, single on wing)</i>	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires <i>For R10 - 6 Tires (Double tires on center and on wing)</i>	948.00
3035		<b>Foam Filled Tires</b> 6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires <i>For R10 - 5 Tires ( Double center , single on wing)</i>	352.00
3335		8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires <i>For R10 - 6 Tires ( Double tire on center and wing)</i>	1,406.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge
9043		Text Free Operator's Manual and Decal Kit	No Charge
<b>BLADES</b>			
9100		Hi-Impact Hammer Blades <i>Includes blades, bolts and nuts to replace the current. Kit with 6 pairs of blades, bolts and nuts.</i>	392.00
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
<b>DOUBLE FRONT SAFETY CHAIN SHIELDS</b>			
9400		Front Safety Shield - Second row chain	149.00
<b>DOUBLE REAR SAFETY CHAIN SHIELDS</b>			
9410		Rear Safety Shield - Second row chain	149.00

### WALKING TANDEM

AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS

**R10 Flex wing Rotary Cutter**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
9300		<b>WALKING TANDEM ...Continued...</b> Walking Tandem Kit <i>Kit just for center section.</i> <i>For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings.</i> <i>Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,917.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

---

**R10 Flex wing Rotary Cutter**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

**R15 Flex wing Rotary Cutter  
Equipment for Base Machine**

Pull Type  
15 Ft. (4.6 m) Cutting Width  
4 In. Brush Cutting Capacity  
Four Gear cases  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing : 125 HP (93 kW)  
Peak Horsepower Rating:  
Splitter 300 HP (224 kW)  
Wing 194 HP (145 kW)  
1-3/4 In. Gear case Input Shafts  
Xxx in Gear case output shaft  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline Cat 6  
Three Slip Clutches,  
Tubular Telescoping Driveshaft Members  
Easy Clean Dome Shaped  
Replaceable bolt on Wear skid shoes  
Frames:  
Deck Thickness: 0.17 in (4.5 mm) 7ga  
Body Depth 10 In. (276 mm)  
1/4 In. (6 mm) Side Skirt Thickness  
3-Section Flexible  
90 Degrees Up for transportation

Working angles: 22 Degrees Down, 45 Degrees Up  
Pivot Pins with Single Bushings  
Maintenance free bushings on hinges  
Blade Tip Speed:  
540 rpm: 15,586 fpm, (79.2 m/s)  
1000 rpm: 15,837 fpm, (80.5 m/s)  
Double Leveling Rods for tip adjustment  
Easy Adjust Wing Leveling Turnbuckles  
Front and Rear Safety Shields single row chains  
Safety Tow Chain  
Hitch Integrated Jack Stand (on rigid casting hitch)  
Implement Jack  
SMV Emblem and Support Transport light kit - comply with regulations  
Fully Assembled Heavy Duty Rating Intermittent,  
5-Bolt Wheel Hubs with sealed bearings - six Wheels

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2340P		R15 Flex wing Rotary Cutter <i>Serial Number 1Y80R15EZJB420000 and above.</i>	26,285.00
-------	--	--	-----------

**DESTINATION**

0202		United States	In Base Price
0184		Canada	No Added Cost
0186		Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

**BLADE ROTATION**

2540		Basic Outward Rotation <i>All machines will come standard with outward rotation. It helps with the material distribution.</i>	In Base Price
2541		Inward Rotation - For governmental business <i>Will only be available in 15 ft models M and R spec. This configuration will be build to order, will have different lead time and its purpose is for bids that require an inward rotation.</i>	No Added Cost

**GEARBOX**

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### R15 Flex wing Rotary Cutter Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>GEARBOX ...Continued...</b>			
3602		540 RPM - 125 hp Gearbox - Commercial duty	In Base Price
3603		540 RPM - 125 hp Gearbox - Commercial duty - Inward rotation	No Added Cost
3641		1000 RPM - 125 hp Gearbox - Commercial duty	No Added Cost
3642		1000 rpm - 125 hp Gearbox - Commercial duty - Inward rotation	No Added Cost
<b>DRIVELINES</b>			
3511		540 RPM Driveline - Cat 6	In Base Price
3541		1000 RPM Driveline - 1 3/8" coupler - Cat 6	In Configuration
3545		1000 RPM Driveline - 1 3/4" coupler - Cat 6	In Configuration
<b>TONGUE</b>			
5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	672.00
<b>HITCH</b>			
5110		Clevis Hitch	-259.00
5120		Ball Type Hitch	In Base Price
5140		Swivel Hitch	430.00
<b>TIRES</b>			
<b>Laminated Tires</b>			
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof	-673.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof	59.00
<b>Severe Duty Tires</b>			
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires	948.00
<b>Foam Filled Tires</b>			
3035		6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires	352.00
3335		8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires	1,406.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge

AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS

**R15 Flex wing Rotary Cutter**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
		<b>...Continued...</b>	
9043		Text Free Operator's Manual and Decal Kit	No Charge
		<b>BLADES</b>	
9100		Hi-Impact Hammer Blades <i>Includes blades, bolts and nuts to replace the current. Kit with 6 pairs of blades, bolts and nuts.</i>	630.00
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
		<b>DOUBLE FRONT SAFETY CHAIN SHIELDS</b>	
9400		Front Safety Shield - Second row chain	149.00
		<b>DOUBLE REAR SAFETY CHAIN SHIELDS</b>	
9410		Rear Safety Shield - Second row chain	149.00
		<b>WALKING TANDEM</b>	
9300		Walking Tandem Kit <i>Kit just for center section. For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,917.00
		<b>INDEPENDENT CONTROL VALVE</b>	
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	851.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

---

**R15 Flex wing Rotary Cutter**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### R20 Flex Wing Rotary cutter Equipment for Base Machine

Pull Type  
20 Ft. (6.1 m) Cutting Width  
4 In. Brush Cutting Capacity  
Four Gear cases  
Continuous Horsepower Rating:  
  Splitter 250 HP (186 kW)  
  Wing : 125 HP (93 kW)  
Peak Horsepower Rating:  
  Splitter 300 HP (224 kW)  
  Wing 194 HP (145 kW)  
1-3/4 In. Gear case Input Shafts  
Xxx in Gear case output shaft  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline Cat 6  
Three Slip Clutches,  
Tubular Telescoping Driveshaft Members  
Easy Clean Dome Shaped  
Replaceable bolt on Wear skid shoes  
Frames:  
  Deck Thickness: 0.17 in (4.5 mm) 7ga  
  Body Depth 10 In. (276 mm)  
  1/4 In. (6 mm) Side Skirt Thickness  
  3-Section Flexible  
  90 Degrees Up for transportation

Working angles: 22 Degrees Down, 45 Degrees Up  
Pivot Pins with Single Bushings  
Maintenance free bushings on hinges  
Blade Tip Speed:  
  540 rpm: 16,087 fpm, (81.7 m/s)  
  1000 rpm: 16,346 fpm, (83 m/s)  
Double Leveling Rods for tip adjustment  
Easy Adjust Wing Leveling Turnbuckles  
Front and Rear Safety Shields single row chains  
Safety Tow Chain  
Hitch Integrated Jack Stand (on rigid casting hitch)  
Implement Jack  
SMV Emblem and Support Transport light kit - comply with regulations  
Fully Assembled Heavy Duty Rating Intermittent,  
5-Bolt Wheel Hubs with sealed bearings - six Wheels

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2350P		R20 Flex Wing Rotary cutter <i>Serial Number P00R20X000001 and above</i>	36,983.00
-------	--	---	-----------

#### DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0186		Cuba <i>Include Decals and OM text free in Spanish. To be changed and installed by Dealer.</i>	No Added Cost

#### GEARBOX

3602		540 RPM - 125 hp Gearbox - Commercial duty	No Added Cost
3641		1000 RPM - 125 hp Gearbox - Commercial duty	In Base Price

#### DRIVELINES

3511		540 RPM Driveline - Cat 6	In Configuration
3541		1000 RPM Driveline - 1 3/8" coupler - Cat 6	In Base Price

## AGRICULTURAL PRODUCTS FLEX-WING ROTARY CUTTERS

### R20 Flex Wing Rotary cutter Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DRIVELINES ...Continued...</b>			
3545		1000 RPM Driveline - 1 3/4" coupler - Cat 6	In Configuration
<b>TONGUE</b>			
5280		Rigid Casting Tongue	In Base Price
5290		Suspended Tongue	672.00
<b>HITCH</b>			
5110		Clevis Hitch	-259.00
5120		Ball Type Hitch	In Base Price
<b>TIRES</b>			
<b>Laminated Tires</b>			
3015		6 Laminated Tires - (Double center, single on wings) - Puncture proof	-673.00
3315		8 Laminated Tires - (Double tires on center and wings) - Puncture proof	59.00
<b>Severe Duty Tires</b>			
3025		6 Pneumatic Tires - (Double center, single on wings) - Severe duty ag tires	In Base Price
3325		8 Pneumatic Tires - (Double tires on center and wings) - Severe duty ag tires	948.00
<b>Foam Filled Tires</b>			
3035		6 Foam-Filled Tires - (Double center, single on wings) - Severe duty ag tires	352.00
3335		8 Foam-Filled Tires - (Double tires on center and wings) - Severe duty ag tires	1,406.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9013		French Operator's Manual and Decal Kit	No Charge
9037		Spanish Operator's Manual and Decal Kit	No Charge
9043		Text Free Operator's Manual and Decal Kit	No Charge
<b>BLADES</b>			
9100		Hi-Impact Hammer Blades <i>Includes blades, bolts and nuts to replace the current. Kit with 6 pairs of blades, bolts and nuts.</i>	630.00
9120		Blade Bolt and Bushing Kit <i>Includes 6 bolts, 6 bushings and 6 nuts.</i>	221.00
<b>DOUBLE FRONT SAFETY CHAIN SHIELDS</b>			
9400		Front Safety Shield - Second row chain	149.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

**R20 Flex Wing Rotary cutter**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DOUBLE REAR SAFETY CHAIN SHIELDS</b>	
9410		Rear Safety Shield - Second row chain	149.00
		<b>WALKING TANDEM</b>	
9300		Walking Tandem Kit <i>Kit just for center section. For full coverage, order 1 additional kit and 2 additional tires/dual tires on wings. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,917.00
		<b>INDEPENDENT CONTROL VALVE</b>	
9130		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	851.00

**AGRICULTURAL PRODUCTS  
FLEX-WING ROTARY CUTTERS**

---

**R20 Flex Wing Rotary cutter**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX5 Lift-Type Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 1/8 In. (3.0 mm)  
Lower Deck - 1/8 In. (3.0 mm)  
Total - 1/4" (6.0 mm)  
One Gearcase, Power Rating:  
75 HP (56 kW) Continuous  
90 HP (67 kW) Peak  
2 In. Brush Cutting Capacity  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216 mm) Body Depth  
1/4 In. (6.0 mm) Skirt Thickness  
Cutting Width: 60 In. (1.52 m)  
Transport Width: 65 In. (1.62 m)  
Cutting Height: 1 to 9.5 In. (25 - 241 mm)  
Blade Tip Speed: 14121 ft/min (71.7 m/s)  
Hitch:  
Integral Hitch (Category I, Convertible  
to II, 3-Point Hitch with or without

Quick Coupler)  
Weld on Full Length Wear Shoes - Replaceable  
Driveline:  
Standard Driveline (Category 3)  
- 540 RPM PTO  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
One Wheel Support (Swiveling,  
Height Adjustable)  
One Puncture Proof Laminated Tire  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Minimum Recommended Tractor PTO HP:  
25 HP; 4300 or equivalent

*Note: Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2134P		MX5 Lift-Type Rotary Cutter - 540 RPM PTO <i>Order Code 9020 for Quick Coupler Compatibility. Order Code 9030 for Conversion to Category II. If ordering for use with the iMatch Auto-Hitch, you will need to shorten the rotary cutter driveline according to the iMatch Auto-Hitch instructions. Serial Number P00MX5C016000 and above.</i>	3,011.00
-------	--	--	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**HITCH ADAPTERS**

9020		iMatch / Quik-Coupler Bushing Kit	92.00
9030		Category II Conversion Kit	147.00

**ATTACHMENTS FOR FIELD CONVERSION**

BW15128		<b>HITCH ADAPTERS</b> Category II Conversion Kit	161.70
---------	--	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX5 Lift-Type Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
	W46506	Cat. I Hitch Pin <i>Two required.</i>	46.45
	W46345	Skid Shoe (weld on) <i>Two required.</i>	35.76
		<b>Miscellaneous</b>	
	BW15056	iMatch/Quik-Coupler Brushing Kit	101.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
	BW14503	French Operator's Manual and Decal Kit	No Charge
	BW15676	Spanish Operator's Manual and Decal Kit	No Charge
		<b>Safety Shields</b>	
	BW14480	Front Safety Shield	235.40
	BW14483	Rear Safety Shield	259.60

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**MX6 Lift-Type Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

<p>Deck Thickness: Upper Deck - 9/64 In. (3.5 mm) Lower Deck - 9/64 In. (3.5 mm) Total - 9/32 In. (7.0 mm) One Gearcase, Power Rating: 75 HP (56 kW) Continuous 90 HP (67 kW) Peak 2 In. Brush Cutting Capacity Slip Clutch Protection Unibody Frame: 8.5 In. (216 mm) Body Depth 1/4 In. (6.0 mm) Skirt Thickness Cutting Width: 72 In. (1.83 m) Transport Width: 75 In. (1.91 m) Cutting Height: 1 to 9.5 In. (25 - 241 mm) Blade Tip Speed: 17416 ft/min (88.5 m/s) Hitch: Integral Hitch (Category I Convertible to II, 3-Point Hitch with or without Quick Coupler)</p>	<p>Weld on Full Length Wear Shoes - Replaceable Driveline: Standard Driveline (Category 3) - 540 RPM PTO Round Pan Bladeholder (Stump Jumper) Suction Blades (1/2 In. x 4 In.) One Wheel Support (Swiveling, Height Adjustable) One Puncture Proof Laminated Tire Front Safety Shield - Chain Rear Safety Shield - Chain Minimum Recommended Tractor PTO HP: 30 HP; 4500 or equivalent</p>
--	--

*Note: Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2144P		MX6 Lift-Type Rotary Cutter - 540 RPM PTO <i>Order Code 9020 for Quick Coupler Compatibility.</i> <i>Order Code 9030 for Conversion to Category II.</i> <i>If ordering for use with the iMatch Auto-Hitch, you will need to shorten the rotary cutter driveline according to the iMatch Auto-Hitch instructions.</i> <i>Serial Number P00MX6C034000 and above.</i>	3,497.00
-------	--	--	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**HITCH ADAPTERS**

9020		iMatch / Quik-Coupler Bushing Kit	92.00
9030		Category II Conversion Kit	147.00

**ATTACHMENTS FOR FIELD CONVERSION**

	BW15128	<b>HITCH ADAPTERS</b> Category II Conversion Kit	161.70
--	---------	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX6 Lift-Type Rotary Cutter - 540 RPM PTO**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
	W46506	Cat. I Hitch Pin <i>Two required.</i>	46.45
	W46345	Skid Shoe (weld on) <i>Two required.</i>	35.76
		<b>Miscellaneous</b>	
	BW15056	iMatch/Quik-Coupler Brushing Kit	101.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
	BW14503	French Operator's Manual and Decal Kit	No Charge
	BW15676	Spanish Operator's Manual and Decal Kit	No Charge
		<b>Safety Shields</b>	
	BW14481	Front Safety Shield	235.40
	BW14484	Rear Safety Shield	338.80

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX7 Lift-Type Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 9/64 In. (3.5 mm)  
Lower Deck - 9/64 In. (3.5 mm)  
Total - 9/32 In. (7.0 mm)  
One Gearcase, Power Rating:  
75 HP (56 kW) Continuous  
100 HP (74.5 kW) Peak  
2 In. Brush Cutting Capacity  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216 mm) Body Depth  
1/4 In. (6.0 mm) Skirt Thickness  
Cutting Width: 84 In. (2.13 m)  
Transport Width: 88 In. (2.24 m)  
Cutting Height: 1 to 9.5 In. (25 - 241 mm)  
Blade Tip Speed: 16182 ft/min (82.2 m/s)  
Hitch:  
Integral Hitch (Category II and IIIN 3-Point  
Hitch with or without Quick Coupler)

Weld on Full Length Wear Shoes - Replaceable  
Driveline:  
Standard Driveline (Category 4)  
- 540 RPM PTO  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
One Wheel Support (Swiveling,  
Height Adjustable)  
One Puncture Proof Laminated Tire  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Minimum Recommended Tractor PTO HP:  
40 HP; 4 cylinder 5000 Series or equivalent

*Note: Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2154P		MX7 Lift-Type Rotary Cutter - 540 RPM PTO <i>Order Code 9020 for Quick Coupler Compatibility. Serial Number P00MX7C017500 and above.</i>	4,615.00
-------	--	---	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**DUAL TAIL WHEEL SUPPORT**

9010		Dual Tailwheel Support, Hub and Wheel <i>Includes the following components: 1 AW30473 -dual tail wheel support and hub 1 AW30715 -4X8 Bolt Wheel Hub- Puncture Proof Laminated Tire.</i>	384.00
------	--	---	--------

**HITCH ADAPTERS**

9020		iMatch / Quik-Coupler Bushing Kit	92.00
------	--	-----------------------------------	-------

**ATTACHMENTS FOR FIELD CONVERSION**

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX7 Lift-Type Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
BW00454		<b>DUAL TAIL WHEEL SUPPORT</b> Dual Tailwheel Support, Hub and Wheel <i>Includes the following components:</i> 1 AW30473 -dual tail wheel support and hub 1 AW30715 -4X8 Bolt Wheel Hub- Puncture Proof Laminated Tire.	422.40
W46503		<b>Miscellaneous</b> Cat. II Hitch Pin <i>Two required.</i>	57.11
W46345		Skid Shoe (weld on) <i>Two required.</i>	35.76
BW15056		<b>Miscellaneous</b> iMatch/Quik-Coupler Brushing Kit	101.20
BW14503		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b> French Operator's Manual and Decal Kit	No Charge
BW15676		Spanish Operator's Manual and Decal Kit	No Charge
BW13700		<b>Safety Shields</b> Front Safety Shield	453.20
BW13701		Rear Safety Shield	367.40
AW30715		<b>Wheels and Tires</b> 4 X 8 Bolt Wheel Hub - Puncture Proof Laminated Tire <i>For MX7.</i>	253.00
AW30473		Dual Tail Wheel Support and Hub	152.90

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 1/8" (3.0 mm)  
Lower Deck - 1/8" (3.0 mm)  
Total - 1/4" (6.0 mm)  
Three Gearcases, Power Ratings:  
Center - 120 Continuous HP (88.2 kW);  
Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216 mm) Body Depth  
3/16 In. (4.5 mm) Skirt Thickness  
Cutting Width: 96 In. (2.44 m)  
Transport Width: 102 In. (2.58 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 15739 ft/min (80 m/s)  
Weld on Full Length Wear Shoes  
Minimum Recommended Tractor PTO HP: 40 HP

Standard Driveline with Lock Slide Collar  
(Equal Angle, Cat.4) - 540 RPM PTO  
Level Lift  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling and Row  
Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Safety Tow Chain  
Jack with Mounting Brackets  
Lift Cylinder and Hose  
Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

216AP		MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8E018000 and above.</i>	8,546.00
-------	--	---	----------

**TIRES**

1210		<b>Laminated Tires</b> Two 533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Puncture Proof Laminated Tires	In Base Price
1230		<b>Severe Duty Tires</b> Two 304.8 mm (12 in.) wheels with 533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tires	143.00

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**THIRD OR FOURTH PULL-TYPE WHEEL**

9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	237.00
------	--	--	--------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>TIRES</b>			
		<b>Laminated Tires</b>	
9030		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	128.00
		<b>Severe Duty Tires</b>	
9045		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	207.00
<b>LIGHTING</b>			
9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
<b>SMV EMBLEM AND SUPPORT</b>			
9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
		<b>LIGHTING</b>	
BW14472		Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
AW29956		Clevis Kit - Clamp on Jaws with Special Drawbar Pin <i>To reduce tractor drawbar and implement clevis wear.</i>	794.25
AW31553		Cylinder Stops	151.80
W45401		Skid Shoe (Weld On)	34.52
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14500		French Operator's Manual and Decal Kit	No Charge
BW15677		Spanish Operator's Manual and Decal Kit	No Charge



AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>SMV EMBLEM AND SUPPORT</b>	
BW00381		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
		<b>Safety Shields</b>	
BW14467		Front Safety Shield	361.90
BW15254		Rear Safety Shield	430.10
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>	
BW14332		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	260.70
		<b>Wheels and Tires</b>	
AW33090		Tire and tube kit for 21" x 7" x 12" Severe Duty Ag Tire	192.39

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**MX8 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX8 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 1/8" (3.0 mm)  
Lower Deck - 1/8" (3.0 mm)  
Total - 1/4" (6.0 mm)  
Three Gearcases, Power Ratings:  
Center - 120 Continuous HP (88.2 kW);  
Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216 mm) Body Depth  
3/16 In. (4.5 mm) Skirt Thickness  
Cutting Width: 96 In. (2.44 m)  
Transport Width: 102 In. (2.58 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 15739 ft/min (80 m/s)  
Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP:  
4 cyl. 5000 Series or equivalent  
Standard Driveline with Lock Slide Collar  
(Cat. 4) - 540 RPM 1-3/8 PTO  
Hitch (Cat. II, III and IIIN 3-Point Hitch  
with or without Quick Coupler)  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling,  
Height Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

216BP		MX8 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8C018000 and above.</i>	6,751.00
-------	--	---	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**ATTACHMENTS FOR FIELD CONVERSION**

BW14472		<b>LIGHTING</b> Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
---------	--	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX8 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
	AW31553	Cylinder Stops	151.80
	W45401	Skid Shoe (Weld On)	34.52
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
	BW14500	French Operator's Manual and Decal Kit	No Charge
	BW15677	Spanish Operator's Manual and Decal Kit	No Charge
<b>SMV EMBLEM AND SUPPORT</b>			
	BW00381	SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
<b>Safety Shields</b>			
	BW14467	Front Safety Shield	361.90
	BW15254	Rear Safety Shield	430.10

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX8 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 1/8" (3.0 mm)  
Lower Deck - 1/8" (3.0 mm)  
Total - 1/4" (6.0 mm)  
Three Gearcases, Power Ratings:  
Center - 120 Continuous HP (88.2 kW);  
Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216 mm) Body Depth  
3/16 In. (4.5 mm) Skirt Thickness  
Cutting Width: 96 In. (2.44 m)  
Transport Width: 102 In. (2.58 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 15739 ft/min (80 m/s)  
Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP: 40 HP  
Standard Driveline with Lock Slide Collar  
(Cat. 4) - 540 RPM PTO  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling and Row  
Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Lift Cylinder and Hose  
Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

216CP		MX8 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8H018000 and above.</i>	6,880.00
-------	--	--	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**ATTACHMENTS FOR FIELD CONVERSION**

	BW14472	<b>LIGHTING</b> Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
--	---------	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX8 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
W46672		Cat. I Hitch Pin <i>Two required. Also requires (2) M72431 and (2) A15146.</i>	98.01
AW31553		Cylinder Stops	151.80
W45401		Skid Shoe (Weld On)	34.52
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14500		French Operator's Manual and Decal Kit	No Charge
BW15677		Spanish Operator's Manual and Decal Kit	No Charge
<b>SMV EMBLEM AND SUPPORT</b>			
BW00381		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
<b>Safety Shields</b>			
BW14467		Front Safety Shield	361.90
BW15254		Rear Safety Shield	430.10

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX8 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 1/8" (3.0 mm)  
Lower Deck - 1/8" (3.0 mm)  
Total - 1/4" (6.0mm)  
Three Gearcases, Power Ratings:  
Center - 120 Continuous HP (88.2 kW);  
Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216mm) Body Depth  
3/16 In. (4.5mm) Skirt Thickness  
Cutting Width: 96 In. (2.44 m)  
Transport Width: 102 In. (2.58 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 15739 ft/min (80 m/s)  
Weld on Full Length Wear Shoes  
Minimum Recommended Tractor PTO HP: 40 HP

Offset: 0-13" RIGHT or LEFT  
Standard Driveline with Lock Slide Collar  
(Cat. 4) - 540 RPM PTO  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling and Row  
Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Offset Cylinder and Hoses  
Lift Cylinder and Hose  
Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

216DP		MX8 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX8G018000 and above.</i>	7,992.00
-------	--	--	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**ATTACHMENTS FOR FIELD CONVERSION**

BW14472		<b>LIGHTING</b> Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
---------	--	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX8 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
W46672		Cat. I Hitch Pin <i>Two required. Also requires (2) M72431 and (2) A15146.</i>	98.01
W45401		Skid Shoe (Weld On)	34.52
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14500		French Operator's Manual and Decal Kit	No Charge
BW15677		Spanish Operator's Manual and Decal Kit	No Charge
<b>SMV EMBLEM AND SUPPORT</b>			
BW00381		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
<b>Safety Shields</b>			
BW14467		Front Safety Shield	361.90
BW15254		Rear Safety Shield	430.10



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
  Upper Deck - 1/8" (3.0 mm)  
  Lower Deck - 1/8" (3.0 mm)  
  Total - 1/4" (6.0 mm)  
Three Gearcases, Power Ratings:  
  Center - 120 Continuous HP (88.2 kW);  
  Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
  8.5 In. (216 mm) Body Depth  
  3/16 In. (4.5 mm) Skirt Thickness  
Cutting Width: 125.5 In. (3.19 m)  
Transport Width: 129 In. (3.28 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 16275 ft/min (82.7 m/s)  
Weld on Full Length Wear Shoes  
Minimum Recommended Tractor PTO HP: 40 HP

Standard Driveline with Lock Slide Collar  
  (Equal Angle, Cat.4) - 540 RPM PTO  
Level Lift  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling and Row  
  Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Safety Tow Chain  
Jack with Mounting Brackets  
Lift Cylinder and Hose  
Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

217AP		MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POMX10E0170000 and above.</i>	9,201.00
-------	--	---	----------

**TIRES**

1210	<b>Laminated Tires</b>	Two 533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Puncture Proof Laminated Tires	In Base Price
1230	<b>Severe Duty Tires</b>	Two 304.8 mm (12 in.) wheels with 533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tires	143.00

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**THIRD OR FOURTH PULL-TYPE WHEEL**

9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	237.00
------	--	--	--------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>TIRES</b>			
		<b>Laminated Tires</b>	
9030		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	128.00
		<b>Severe Duty Tires</b>	
9045		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	207.00
<b>LIGHTING</b>			
9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
<b>SMV EMBLEM AND SUPPORT</b>			
9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
		<b>LIGHTING</b>	
BW14472		Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
W45327		1/2 x 4" Blade (high suction) CCW <i>Two required.</i>	48.48
W45326		1/2 x 4" Blade (high suction) CW <i>Two required.</i>	34.97
AW29956		Clevis Kit - Clamp on Jaws with Special Drawbar Pin <i>To reduce tractor drawbar and implement clevis wear.</i>	794.25
AW31553		Cylinder Stops	151.80
W45401		Skid Shoe (Weld On)	34.52
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	BW14053	Support Assembly	20.90
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
	BW14500	French Operator's Manual and Decal Kit	No Charge
	BW15677	Spanish Operator's Manual and Decal Kit	No Charge
		<b>SMV EMBLEM AND SUPPORT</b>	
	BW00381	SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
		<b>Safety Shields</b>	
	BW14464	Front Safety Shield - Chain	402.60
	BW14465	Rear Safety Shield - Chain	360.80
		<b>Severe Duty Tires</b>	
	AW34778	533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>	
	BW14332	MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	260.70
		<b>Wheels and Tires</b>	
	AW33090	Tire and tube kit for 21" x 7" x 12" Severe Duty Ag Tire	192.39

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**MX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 1/8" (3.0 mm)  
Lower Deck - 1/8" (3.0 mm)  
Total - 1/4" (6.0 mm)  
Three Gearcases, Power Ratings:  
Center - 120 Continuous HP (88.2 kW);  
Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
8.5 In. (216 mm) Body Depth  
3/16 In. (4.5 mm) Skirt Thickness  
Cutting Width: 125.5 In. (3.19 m)  
Transport Width: 129 In. (3.28 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 16275 ft/min (82.7 m/s)  
Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP:  
6000 Series or equivalent  
Standard Driveline with Lock Slide Collar (Cat. 4)  
- 540 RPM 1-3/8 PTO  
Hitch (Cat. II, III and IIIN 3-Point Hitch  
with or without Quick Coupler)  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling,  
Height Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

217BP		MX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POMX10C017000 and above.</i>	7,906.00
-------	--	--	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**ATTACHMENTS FOR FIELD CONVERSION**

BW14472	<b>LIGHTING</b>	Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
---------	-----------------	--	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
W45327		1/2 x 4" Blade (high suction) CCW <i>Two required.</i>	48.48
W45326		1/2 x 4" Blade (high suction) CW <i>Two required.</i>	34.97
W45401		Skid Shoe (Weld On)	34.52
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80
BW14053		Support Assembly	20.90
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14500		French Operator's Manual and Decal Kit	No Charge
BW15677		Spanish Operator's Manual and Decal Kit	No Charge
<b>SMV EMBLEM AND SUPPORT</b>			
BW00381		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
<b>Safety Shields</b>			
BW14464		Front Safety Shield - Chain	402.60
BW14465		Rear Safety Shield - Chain	360.80

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX10 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck

Deck Thickness:

Upper Deck - 1/8" (3.0 mm)

Lower Deck - 1/8" (3.0 mm)

Total - 1/4" (6.0mm)

Three Gearcases, Power Ratings:

Center - 120 Continuous HP (88.2 kW);

Outer - 75 Continuous HP (55.1 kW);

2 In. Brush Cutting Capacity

Shock Absorbing Cross Shafts

Slip Clutch Protection

Unibody Frame:

8.5 In. (216 mm) Body Depth

3/16 In. (4.5 mm) Skirt Thickness

Cutting Width: 125.5 In. (3.19 m)

Transport Width: 129 In. (3.28 m)

Cutting Height: 1 to 12 In. (25 - 305 mm)

Blade Tip Speed: 16275 ft/min (82.7 m/s)

Weld on Full Length Wear Shoes

Minimum Recommended Tractor PTO HP: 40 HP

Standard 217CP with Lock Slide Collar (Cat. 4) - 540 RPM PTO

Round Pan Bladeholder (Stump Jumper)

Suction Blades (1/2 In. x 4 In.)

Two Wheel Supports (Swiveling and Row Width Adjustable)

Two Puncture Proof Laminated Tires

Front Safety Shield - Chain

Rear Safety Shield - Chain

Lift Cylinder and Hose

Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

217CP		MX10 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number P00MX10H017000 and above.</i>	7,892.00
-------	--	--	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**HOMOLOGATION KITS**

9070		Semi-mount extension brackets <i>Order when attaching a semi-mount machine to a tractor with a three-point hitch only</i>	119.00
------	--	--	--------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX10 Semi-Mount Center Drive Rotary Cutter - 540 RPM PTO**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>HOMOLOGATION KITS</b>	
BW14552		Semi-mount extension brackets <i>Order when attaching a semi-mount machine to a tractor with a three-point hitch only</i>	130.90
		<b>LIGHTING</b>	
BW14472		Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
		<b>Miscellaneous</b>	
W45327		1/2 x 4" Blade (high suction) CCW <i>Two required.</i>	48.48
W45326		1/2 x 4" Blade (high suction) CW <i>Two required.</i>	34.97
AW31553		Cylinder Stops	151.80
W45401		Skid Shoe (Weld On)	34.52
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80
BW14053		Support Assembly	20.90
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14500		French Operator's Manual and Decal Kit	No Charge
BW15677		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SMV EMBLEM AND SUPPORT</b>	
BW00381		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
		<b>Safety Shields</b>	
BW14464		Front Safety Shield - Chain	402.60
BW14465		Rear Safety Shield - Chain	360.80



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX10 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
  Upper Deck - 1/8" (3.0 mm)  
  Lower Deck - 1/8" (3.0 mm)  
  Total - 1/4" (6.0 mm)  
Three Gearcases, Power Ratings:  
  Center - 120 Continuous HP (88.2 kW);  
  Outer - 75 Continuous HP (55.1 kW);  
2 In. Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
  8.5 In. (216 mm) Body Depth  
  3/16 In. (4.5 mm) Skirt Thickness  
Cutting Width: 125.5 In. (3.19 m)  
Transport Width: 129 In. (3.28 m)  
Cutting Height: 1 to 12 In. (25 - 305 mm)  
Blade Tip Speed: 16275 ft/min (82.7 m/s)  
Weld on Full Length Wear Shoes  
Minimum Recommended Tractor PTO HP: 40 HP

Offset: 0-13" RIGHT or LEFT  
Standard Driveline with Lock Slide Collar (Cat. 4)  
- 540 RPM PTO  
Round Pan Bladeholder (Stump Jumper)  
Suction Blades (1/2 In. x 4 In.)  
Two Wheel Supports (Swiveling and Row  
  Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Offset Cylinder and Hoses  
Lift Cylinder and Hose  
Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the Industrial Mower Safety Standard SAE J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

217DP		MX10 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO <i>Serial Number POMX10G017000 and above.</i>	9,181.00
-------	--	---	----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**ATTACHMENTS FOR FIELD CONVERSION**

	BW14472	<b>LIGHTING</b> Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
--	---------	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**MX10 Semi-Mount, Hydraulic Offset, Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
W45327		1/2 x 4" Blade (high suction) CCW <i>Two required.</i>	48.48
W45326		1/2 x 4" Blade (high suction) CW <i>Two required.</i>	34.97
AW31553		Cylinder Stops	151.80
W45401		Skid Shoe (Weld On)	34.52
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80
BW14053		Support Assembly	20.90
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14500		French Operator's Manual and Decal Kit	No Charge
BW15677		Spanish Operator's Manual and Decal Kit	No Charge
<b>SMV EMBLEM AND SUPPORT</b>			
BW00381		SMV Emblem and Support <i>Includes the following components:</i> <i>1 BW10809 - SMV Emblem</i> <i>1 BW14053 - Support Assembly</i>	64.90
<b>Safety Shields</b>			
BW14464		Front Safety Shield - Chain	402.60
BW14465		Rear Safety Shield - Chain	360.80

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX15 Flex-Wing Rotary Cutter - 540 RPM  
Equipment for Base Machine**

Pull Type  
Medium Duty Rating  
Double Deck Design, Easy Clean Dome  
Shaped Top Deck  
540 RPM Tractor PTO Speed  
Deck Thickness:  
Upper Deck Thickness: 0.118 In. (3.0 mm)  
Lower Deck Thickness: 0.118 In. (3.0 mm)  
Four Gear cases  
Gear Box Rating:  
Splitter 300 HP (223 kW)  
Wing 100 HP (75 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (183.8 kW)  
Wing 75 HP (55.1 kW)  
1 - 3/8" Center and Wing Gear case Input Shaft  
2 In. Brush Cutting Capacity  
10.5 In. (267 mm) Body Depth  
1/4 In. (6 mm) Side Shirt Thickness  
15 Ft. (4.6 m) Cutting Width  
Pan Blade holder (Stump Jumper)  
Single Suction Blades 1/2" (13 mm) x 4" (102 mm)  
Blade Tip Speed:  
17,323 fpm, 88 m/s  
3-Section Flexible 90 Degrees Up, 22 Degrees Down  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops

Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Four Wheels - 21" X 7" X 12" - 16 PR Severe Duty AG Tires  
4-Bolt Wheel Hubs  
Constant Velocity and Lock-Slide Collar  
Tractor to Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Safety Tow Chain  
SMV Emblem and Support  
Transport light kit comply with regulations  
Fully Assembled  
Intermittent, Greaseable Hinges  
Tubular Telescoping Driveshaft Members  
30 mm Pivot Pins with Single Bushings  
Simultaneous Wing Lift

Front and Rear Safety Shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2181P		MX15 Flex-Wing Rotary Cutter - 540 RPM	16,093.00
-------	--	--	-----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**SEVERE DUTY TIRES**

9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	930.00
------	--	---	--------

**INDEPENDENT CONTROL VALVE**

9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
------	--	---	--------

**WING CYLINDER HOSE**

9050		Extra Wing Cylinder Hose	98.00
------	--	--------------------------	-------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**MX15 Flex-Wing Rotary Cutter - 540 RPM**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Drivelines</b>	
AP40627		Constant Velocity Drive Line with Lock-Slide Collar, Cat. 5, 540 RPM	1,008.70
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>Miscellaneous</b>	
TY25778		Implement Jack	110.49
BW15588		Mounting Kit for Implement Jack	225.50
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW15870		French Operator's Manual and Decal Kit	No Charge
BW15871		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	1,023.00
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel	227.70
		<b>WING CYLINDER HOSE</b>	
BW15083		Extra Wing Cylinder Hose	107.80
		<b>Wheels and Tires</b>	
BW14521		Dual Wing Wheel Spindles and Hubs	588.50

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX6 Lift-Type Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

1.83-m (72-in.) cutting width  
10.16-cm (4-in.) brush cutting capacity  
Heavy-duty construction  
Smooth, easy clean, top deck  
Deck thickness: Upper deck - 3.0-mm (0.118-in.),  
lower deck - 3.5-mm (0.138-in.), total - 6.5-mm  
(0.256-in.)  
One gear case, power rating: 112-kW (150-hp)  
continuous, 153-kW (205-hp) peak  
Category 2 or 3N  
Slip clutch protection  
Shielded driveline with lock slide collar - 540  
revolutions per minute (RPM)

Suction blades 1.27-cm x 10.16-cm (0.5-in. x 4-in.)  
One wheel support (swiveling, height adjustable)  
One puncture proof laminated tire  
Safety shields - front and rear chain  
Less safety chain  
Round pan blade holder (stump jumper)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

219HP		HX6 Lift-Type Rotary Cutter - 540 RPM PTO <i>(with Stump Jumper and Single Suction Blades)</i>	5,887.00
-------	--	---	----------

**DESTINATION**

	<b>North America</b>		
0202	United States of America		In Base Price
0184	Canada		No Added Cost
	<b>Central America</b>		
0195	Mexico		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost
0192	Haiti		No Added Cost
0194	Jamaica		No Added Cost
0201	Trinidad and Tobago		No Added Cost
0203	Puerto Rico		No Added Cost
0183	Belize		No Added Cost
0185	Costa Rica		No Added Cost
0189	El Salvador		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX6 Lift-Type Rotary Cutter - 540 RPM PTO**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DESTINATION ...Continued...</b>	
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
		<b>South America</b>	
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0220		Uruguay	No Added Cost
0221		Venezuela	No Added Cost

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**ATTACHMENTS FOR FIELD CONVERSION**

	<b>Drivelines</b>		
AP40626		Constant Velocity Drive Line with Lock-Slide Collar, 540 RPM PTO	689.70
	<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>		
BP18519		French Operator's Manual and Decal Kit	No Charge
BP18518		Spanish Operator's Manual and Decal Kit	No Charge
	<b>Safety Shields</b>		
BP18447		Front Safety Shield - Chain	359.70
BW14484		Rear Safety Shield	338.80

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX7 Lift-Type Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

2.130-m (84-in.) cutting width  
10.16-cm (4-in.) brush cutting capacity  
Heavy-duty construction  
Smooth, easy clean, top deck  
Deck thickness: Upper deck - 3.0-mm (0.118-in.),  
lower deck - 3.5-mm (0.138-in.), total - 6.5-mm  
(0.256-in.)  
One gear case, power rating: 112-kW (150-hp)  
continuous, 153-kW (205-hp) peak  
Category 2 or 3N  
Slip clutch protection  
Shielded driveline with lock slide collar - 540  
revolutions per minute (RPM)

Suction blades 1.27-cm x 10.16-cm (0.5-in. x 4-in.)  
One wheel support (swiveling, height adjustable)  
One puncture proof laminated tire  
Safety shields - front and rear chain  
Less safety chain  
Round pan blade holder (stump jumper)

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

220HP		HX7 Lift-Type Rotary Cutter - 540 RPM PTO <i>(with Stump Jumper and Single Suction Blades)</i>	7,543.00
-------	--	---	----------

**DESTINATION**

	<b>North America</b>		
0202	United States of America		In Base Price
0184	Canada		No Added Cost
	<b>Central America</b>		
0195	Mexico		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost
0192	Haiti		No Added Cost
0194	Jamaica		No Added Cost
0201	Trinidad and Tobago		No Added Cost
0203	Puerto Rico		No Added Cost
0183	Belize		No Added Cost
0185	Costa Rica		No Added Cost
0189	El Salvador		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX7 Lift-Type Rotary Cutter - 540 RPM PTO**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DESTINATION ...Continued...</b>	
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
		<b>South America</b>	
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0220		Uruguay	No Added Cost
0221		Venezuela	No Added Cost

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**ATTACHMENTS FOR FIELD CONVERSION**

	<b>Drivelines</b>		
AP40625		Constant Velocity Driveline with Lock Slide Collar, 540 RPM PTO	745.80
	<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>		
BP18519		French Operator's Manual and Decal Kit	No Charge
BP18518		Spanish Operator's Manual and Decal Kit	No Charge
	<b>Safety Shields</b>		
BP18448		Front Safety Shield - Chain	359.70
BW13701		Rear Safety Shield	367.40



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 3.5 mm (0.138 in.)  
Lower Deck - 3.5 mm (0.138 in.)  
Total - 7.0 mm (0.28 in.)  
Three Gearcases, Power Ratings:  
Center - 150 Continuous hp (112 kW);  
Outer - 100 Continuous hp (73.5 kW);  
Round Pan Bladeholder (Stump Jumper)  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
267 mm (10.5 in.) Body Depth  
6 mm (.25 in.) Skirt Thickness  
Cutting Width: 3.20 m (126 in.)  
Transport Width: 3.35 m (132 in.)  
Cutting Height: 25 - 305 mm (1 to 12 in.)  
Blade Tip Speed: 85.8 m/s (16889 fpm)  
Replaceable Full Length Wear Shoes  
Minimum Recommended Tractor Power Take-Off (PTO)

hp:  
6000 Series or Equivalent  
Standard Driveline with  
Lock-Slide Collar (Category 4) - 540 rpm 1.38 PTO  
Integral Hitch (Category 2, 3 and  
3N 3-Point Hitch with or without Quick Coupler)  
Suction Blades 12.7 mm by 101.6 mm (.5 in. by 4  
in.)  
Two Wheel Supports (Swiveling, Height and Row Width  
Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Rear safety shield - Chain

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the industrial mower safety standard Society of Automotive Engineers (SAE) J232.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

221AP		HX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO <i>Serial Number POHX10C010000 and above.</i>	10,407.00
-------	--	--	-----------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**LIGHTING**

9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
------	--	--	--------

**SMV EMBLEM AND SUPPORT**

9080		SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	59.00
------	--	---	-------

**ATTACHMENTS FOR FIELD CONVERSION**

BW14472		<b>LIGHTING</b> Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
---------	--	---	--------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX10 Lift-Type Center Drive Rotary Cutter - 540 RPM PTO**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
	BW10809	Slow-Moving Vehicle (SMV) Emblem	41.80
	BW14053	Support Assembly	20.90
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
	BW14501	French Operator's Manual and Decal Kit	No Charge
	BW15679	Spanish Operator's Manual and Decal Kit	No Charge
<b>SMV EMBLEM AND SUPPORT</b>			
	BW00381	SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
<b>Safety Shields</b>			
	BW14464	Front Safety Shield - Chain	402.60

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**  
Equipment for Base Machine

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 3.5 mm (0.138 in.)  
Lower Deck - 3.5 mm. (0.138 in.)  
Total - 7.0 mm (0.28 in.)  
Three Gearcases, Power Ratings:  
Center - 150 Continuous hp (112 kW);  
Outer - 100 Continuous hp (73.5 kW);  
44.45 mm (1.75 in.) Gearcase Input Shafts  
76.2 mm (3 in.) Brush Cutting Capacity  
Round Pan Bladeholder (Stump Jumper)  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
267 mm (10.5 in. ) Body Depth  
6 mm (.25 in.) Skirt Thickness  
Cutting Width: 3.20 m (126 in.)  
Transport Width: 3.35 m (132 in.)  
Cutting Height: 1 to 12 in. (25 - 305 mm)  
Blade Tip Speed: 16889 fpm (85.8 m/s)  
Replaceable Full Length Wear Shoes  
Minimum Recommended Tractor PTO hp: 50 hp

Constant Velocity Driveline with  
Lock-Slide Collar - 540 rpm (Category 4) - 1.38  
PTO  
Level Lift  
Suction Blades 12.7 mm by 101.6 mm (.5 in. by 4  
in.)  
Two Wheel Supports (Swiveling, Height and Row Width  
Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Chain  
Safety Tow Chain  
Jack with Mounting Brackets  
Lift Cylinder and Hoses  
Lift Cylinder and Depth Stops

Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter complies with the industrial mower safety standard Society of Automotive Engineers (SAE) J232.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

221BP		HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO Serial Number POHX10C010000 and above.	11,086.00
-------	--	---	-----------

**TIRES**

1210	<b>Laminated Tires</b>	Two 533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Puncture Proof Laminated Tires	In Base Price
------	------------------------	--	---------------

1230	<b>Severe Duty Tires</b>	Two 304.8 mm (12 in.) wheels with 533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tires	143.00
------	--------------------------	---	--------

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**THIRD OR FOURTH PULL-TYPE WHEEL**

9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub	237.00
------	--	---	--------

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>THIRD OR FOURTH PULL-TYPE WHEEL ...Continued...</b> <i>Additional wheel support and hub. Requires wheel and tire.</i>	
		<b>TIRES</b>	
		<b>Laminated Tires</b>	
9030		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	128.00
		<b>Severe Duty Tires</b>	
9045		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	207.00
		<b>LIGHTING</b>	
9060		Lighting Kit (Tractor must have 7 Pin Electrical Outlet)	620.00
		<b>SMV EMBLEM AND SUPPORT</b>	
9080		SMV Emblem and Support <i>Includes the following components:</i> <i>1 BW10809 - SMV Emblem</i> <i>1 BW14053 - Support Assembly</i>	59.00
		<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
		<b>Drivelines</b>	
BP18396		Constant Velocity Driveline with Lock- Slide Collar - 540 RPM Power Take-Off (PTO)	1,236.40
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otumwa Works.</i>	44.00
		<b>LIGHTING</b>	
BW14472		Lighting Kit (Tractor must have 7-Pin Electrical Outlet)	682.00
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
AW29956		Clevis Kit - Clamp on Jaws with Special Drawbar Pin <i>To reduce tractor drawbar and implement clevis wear.</i>	794.25
AW31553		Cylinder Stops	151.80
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	BW14053	Support Assembly	20.90
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
	BW14501	French Operator's Manual and Decal Kit	No Charge
	BW15679	Spanish Operator's Manual and Decal Kit	No Charge
		<b>SMV EMBLEM AND SUPPORT</b>	
	BW00381	SMV Emblem and Support <i>Includes the following components: 1 BW10809 - SMV Emblem 1 BW14053 - Support Assembly</i>	64.90
		<b>Safety Shields</b>	
	BW14464	Front Safety Shield - Chain	402.60
		<b>Severe Duty Tires</b>	
	AW34778	533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>	
	BW14332	MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	260.70
		<b>Wheels and Tires</b>	
	AW33090	Tire and tube kit for 21" x 7" x 12" Severe Duty Ag Tire	192.39

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX10 Pull-Type Center Drive Rotary Cutter - 540 RPM PTO**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder  
Equipment for Base Machine**

Three Gearcases, Power Ratings:  
Center - 119.311 Continuous kW (160 hp);  
Outer - 74.569 Continuous kW (100 hp);  
50.8 mm (2 in.) Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
266.7 mm (10.5 in.) Body Depth  
6.35 mm (0.25 in.) Skirt Thickness  
Cutting Width: 4.191 m (165 in.)  
Transport Width: 4.3434 m (171 in.)  
Cutting Height: 25.4 mm to 304.8 mm (1 in. to 12 in.)  
Blade Tip Speed: 14896 fpm (75.7 m/s)  
Replaceable Full Length Wear Shoes  
Transport Warning Lights  
Minimum Recommended Tractor Power Take-Off (PTO) hp: 7610 or equivalent

Standard Driveline with Lock-Slide Collar (Category 5) - 1000 rpm 1.375 PTO  
Lock-Slide Collar (Cat. 5) -1000 rpm 1.375 Power Take-Off (PTO)  
Integral Hitch (Category 2, 3 and 3N 3-Point Hitch with or without Quik-Coupler Bar Type Bladeholder and Dual Suction Blades Two Wheel Supports (Swiveling, Height and Row Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Solid

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter is designed for agricultural applications only. This machine shall not be used in areas where bystanders may be present and could be injured or where property could be damaged by thrown objects.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

2228P		HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder <i>Serial Number POHX14D008500 and above.</i>	12,639.00
-------	--	--	-----------

**DRIVELINES**

1060		Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/8 Power Take-Off (PTO)	In Base Price
1070		Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/4 Power Take-Off (PTO)	202.00

**TIRES**

<b>Laminated Tires</b>			
1210		Two 533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Puncture Proof Laminated Tires	In Base Price
<b>Severe Duty Tires</b>			
1230		Two 304.8 mm (12 in.) Wheels with 533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tires	143.00

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>TIRES</b>			
		<b>Laminated Tires</b>	
9030		533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	128.00
		<b>Severe Duty Tires</b>	
9060		533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	207.00
<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>			
9020		Third or Fourth Lift-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	444.00
<b>SMV EMBLEM AND SUPPORT</b>			
9080		Slow Moving Vehicle (SMV) Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	59.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80
BW14053		Support Assembly	20.90
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14501		French Operator's Manual and Decal Kit	No Charge
BW15679		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SMV EMBLEM AND SUPPORT</b>	
BW00381		SMV Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	64.90
		<b>Safety Shields</b>	
BW14394		Front Safety Shield - Chain	470.80



AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	BW14339	Rear Safety Shield - Solid	192.50
		<b>Severe Duty Tires</b>	
	AW34778	533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>	
	BW14333	Third or Fourth Lift-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	488.40
		<b>Wheels and Tires</b>	
	AW33090	Tire and tube kit for 21" x 7" x 12" Severe Duty Ag Tire	192.39

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX14 Lift-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

## AGRICULTURAL PRODUCTS JOHN DEERE ROTARY CUTTERS

### HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder Equipment for Base Machine

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 3.5052 mm (0.138 in.)  
Lower deck - 3.5052 mm (0.138 in.)  
Total - 7.112 mm (0.28 in.)  
Three Gearcases, Power Ratings:  
Center - 119.311 Continuous kW (160 hp);  
Outer - 74.569 Continuous kW (100 hp);  
44.45 mm (1.75 in.) Gearcase Input Shafts  
50.8 mm (2 in.) Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
266.7 mm (10.5 in.) Body Depth  
6.35 mm (0.25 in.) Skirt Thickness  
Cutting Width: 4.191 m (165 in.)  
Transport Width: 4.3434 m (171 in.)  
Cutting Height: 25.4 mm to 304.8 mm (1 in. to 12 in.)  
Blade Tip Speed: 14896 fpm (75.7 m/s)  
Replaceable Full Length Wear Shoes  
Transport Warning Lights

Minimum Recommended Tractor Power Take-Off  
(PTO) hp: 44.741 kW (60 hp)  
Constant Velocity Driveline with  
Lock-Slide Collar - 1000 rpm (Category 4) 1.375  
PTO  
Level Lift  
Bar Type Bladeholder  
Dual Suction Blades  
Two Wheel Supports (Row Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Solid  
Safety Tow Chain  
Jack with Mounting Brackets  
Lift Cylinder and Hose(s)  
Lift Cylinder Depth Stops

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter is designed for agricultural applications only. This machine shall not be used in areas where bystanders may be present and could be injured or where property could be damaged by thrown objects.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

2229P		HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder <i>Serial Number POHX14F008500 and above.</i>	12,579.00
-------	--	--	-----------

#### DRIVELINES

1030		Constant Velocity Driveline with Lock-Slide Collar - 1000 rpm 1-3/8 Power Take-Off (PTO)	In Base Price
1040		Constant Velocity Driveline with Lock-Slide Collar - 1000 rpm 1-3/4 Power Take-Off (PTO)	229.00

#### TIRES

		<b>Laminated Tires</b>	
1210		Two 533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Puncture Proof Laminated Tires	In Base Price
		<b>Severe Duty Tires</b>	
1230		Two 304.8 mm (12 in.) Wheels with 533.4 mm by 177.8 mm by 304.8 mm(21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tires	143.00

#### OPERATOR'S MANUAL, DECALS, AND LANGUAGE

9099		French Operator's Manual and Decal Kit	No Charge
------	--	--	-----------

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
<b>...Continued...</b>			
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>TIRES</b>			
<b>Laminated Tires</b>			
9030		533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	128.00
<b>Severe Duty Tires</b>			
9060		533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	207.00
<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>			
9010		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	237.00
<b>SMV EMBLEM AND SUPPORT</b>			
9080		Slow Moving Vehicle (SMV) Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	59.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18395		Constant Velocity Driveline with Lock-Slide Collar - 1000 RPM 1-3/4 Power Take-Off (PTO)	1,428.90
BP18414		Constant Velocity Driveline with Lock-Slide Collar - 1000 RPM 1-3/8 Power Take-Off (PTO)	1,189.10
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
<b>Laminated Tires</b>			
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
<b>Miscellaneous</b>			
AW29956		Clevis Kit - Clamp on Jaws with Special Drawbar Pin <i>To reduce tractor drawbar and implement clevis wear.</i>	794.25
AW31553		Cylinder Stops	151.80

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14501		French Operator's Manual and Decal Kit	No Charge
BW15679		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SMV EMBLEM AND SUPPORT</b>	
BW00381		SMV Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	64.90
		<b>Safety Shields</b>	
BW14394		Front Safety Shield - Chain	470.80
BW14339		Rear Safety Shield - Solid	192.50
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>	
BW14332		MX8, MX10, HX10, HX14 Third or Fourth Pull-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	260.70
		<b>Wheels and Tires</b>	
AW33090		Tire and tube kit for 21" x 7" x 12" Severe Duty Ag Tire	192.39

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX14 Pull-Type Rotary Cutter - 1000 RPM PTO Bar Type Blade Holder**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper  
Equipment for Base Machine**

Smooth, Easy Clean, Top Deck  
Deck Thickness:  
Upper Deck - 3.5052 mm (0.138 in.)  
Lower Deck - 3.5052 mm (0.138 in.)  
Total - 7.112 mm (0.28 in.)  
Three Gearcases, Power Ratings:  
Center - 119.311 Continuous kW (160 hp);  
Outer - 74.569 Continuous kW (100 hp);  
44.45 mm (1.75 in.) Gearcase Input Shafts  
50.8 mm (2 in.) Brush Cutting Capacity  
Shock Absorbing Cross Shafts  
Slip Clutch Protection  
Unibody Frame:  
266.7 mm (10.5 in.) Body Depth  
6.35 mm (0.25 in.) Skirt Thickness  
Cutting Width: 4.191 m (165 in.)  
Transport Width: 4.3434 m (171 in.)  
Cutting Height: 25.4 mm to 304.8 mm (1 in. to 12 in.)  
Blade Tip Speed: 14896 fpm (75.7 m/s)  
Replaceable Full Length Wear Shoes

Transport Warning Lights  
Minimum Recommended Tractor Power Take-Off  
(PTO) hp: 7610 or equivalent  
Standard Driveline with  
Lock-Slide Collar (Category 5) - 1000 rpm 1,375 PTO  
Integral Hitch (Category 2, 3 and 3N 3-Point Hitch with or without Quik-Coupler  
Round Pan Blade Holder (Stump Jumper) and Single Suction Blades  
Two Wheel Supports (Swiveling, Height and Row Width Adjustable)  
Two Puncture Proof Laminated Tires  
Front Safety Shield - Chain  
Rear Safety Shield - Solid

*Front and rear safety shields reduce the risk of thrown objects which could be hazardous. The base rotary cutter is designed for agricultural applications only. This machine shall not be used in areas where bystanders may be present and could be injured or where property could be damaged by thrown objects.*

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Martinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario.*

222AP		HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper <i>Serial Number P0HX14D008500 and above.</i>	12,274.00
-------	--	--	-----------

**DRIVELINES**

1060		Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/8 Power Take-Off (PTO)	In Base Price
1070		Standard Driveline with Lock-Slide Collar - 1000 rpm 1-3/4 Power Take-Off (PTO)	202.00

**TIRES**

1210		<b>Laminated Tires</b> Two 533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Puncture Proof Laminated Tires	In Base Price
1230		<b>Severe Duty Tires</b> Two 304.8 mm (12 in.) Wheels with 533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tires	143.00

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

## HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
<b>...Continued...</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>TIRES</b>			
<b>Laminated Tires</b>			
9030		533.4 mm by 133.35 mm by 228.6 mm (21 in. by 5.25 in. by 9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	128.00
<b>Severe Duty Tires</b>			
9060		533.4 mm by 177.8 mm by 304.8 mm (21 in. by 7 in. by 12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	207.00
<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>			
9020		Third or Fourth Lift-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	444.00
<b>SMV EMBLEM AND SUPPORT</b>			
9080		Slow Moving Vehicle (SMV) Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	59.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Laminated Tires</b>			
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
<b>Miscellaneous</b>			
BW10809		Slow-Moving Vehicle (SMV) Emblem	41.80
BW14053		Support Assembly	20.90
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14501		French Operator's Manual and Decal Kit	No Charge
BW15679		Spanish Operator's Manual and Decal Kit	No Charge



AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>SMV EMBLEM AND SUPPORT</b>	
BW00381		SMV Emblem and Support <i>Includes the following components: One BW10809 - SMV Emblem. One BW14053 - Support Assembly.</i>	64.90
		<b>Safety Shields</b>	
BW14394		Front Safety Shield - Chain	470.80
BW14339		Rear Safety Shield - Solid	192.50
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>THIRD OR FOURTH PULL-TYPE WHEEL</b>	
BW14333		Third or Fourth Lift-Type Wheel Support and Hub <i>Additional wheel support and hub. Requires wheel and tire.</i>	488.40
		<b>Wheels and Tires</b>	
AW33090		Tire and tube kit for 21" x 7" x 12" Severe Duty Ag Tire	192.39

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX14 Lift-Type Rotary Cutter - 1000 RPM Round Pan Blade Holder - Stump Jumper**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**

Equipment for Base Machine

Pull Type  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.118 In. (3.0 mm)  
Lower Deck Thickness: 0.138 In. (3.5 mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 210 HP (156 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 150 HP (111 kW)  
1-3/4 In. Gear case Input Shafts  
3 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267 mm) Body Depth  
1/4 In. (6 mm) Side Skirt Thickness  
15 Ft. (4.6 m) Cutting Width  
Blade Tip Speed:  
15,590 fpm, 79.2 m/s  
3-Section Flexible 90 Degrees Up for  
transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)  
21" x 5.25" x 9" Puncture Proof Laminated Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit - comply with regulations  
Fully Assembled  
Heavy Duty Rating  
Intermittent, Greaseable Hinges  
Tubular Telescoping Driveshaft Members  
Standard Self Level Hitch Clevis  
30 mm Pivot Pins with Single Bushings  
Six Wheel Spring Suspension  
4-Bolt Wheel Hubs  
Simultaneous Wing Lift  
Front and rear safety shields reduce the risk of  
thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

227EP		HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6 Wheels <i>Serial Number POHX15E018500 and above.</i>	20,984.00
-------	--	---	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DESTINATION ...Continued...</b>	
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**TIRES**

		<b>Laminated Tires</b>	
1200		21.0" x 5.25" x 9.00" Puncture-Proof Laminated Tires	In Base Price
		<b>Severe Duty Tires</b>	
1210		21" x 7" x 12" 16 PR Severe Duty Ag Tires	421.00
1230		21" x 7" x 12" 16 PR Foam Filled Severe Duty Ag Tires	756.00

**FRONT SAFETY SHIELD**

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	144.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	144.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires	930.00
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
<b>DOUBLE WHEEL ON WINGS</b>			
9022		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" PunctureProof Laminated Tires	779.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	98.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
BWA1244		<b>DOUBLE WHEEL ON WINGS</b> Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" PunctureProof Laminated Tires	856.90
BP18399		<b>Drivelines</b> Constant Velocity with Lock-Slide Collar Driveline, Category 5, 540 RPM - 34.925 mm (1 3/8 in.)	1,471.80

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
W49091		Deck Ring (Center Section) <i>Three required.</i>	58.51
W49092		Deck Ring (Wing Sections) <i>Three required.</i>	51.52
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BP18696		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires	1,023.00
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW15083		Extra Wing Cylinder Hose	107.80
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		<b>Wheels and Tires</b>	
BW14521		Dual Wing Wheel Spindles and Hubs <i>1 Bolt.</i>	588.50

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**

Equipment for Base Machine

Pull Type  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.118 In. (3.0 mm)  
Lower Deck Thickness: 0.138 In. (3.5 mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 210 HP (156 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 150 HP (111 kW)  
1-3/4 In. Gear case Input Shafts  
3 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267 mm) Body Depth  
1/4 In. (6 mm) Side Skirt Thickness  
15 Ft. (4.6 m) Cutting Width  
Blade Tip Speed:  
15,841 fpm, 80.4 m/s  
3-Section Flexible 90 Degrees Up for  
transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)  
21" x 5.25" x 9" Puncture Proof Laminated Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit - comply with regulations  
Fully Assembled  
Heavy Duty Rating  
Intermittent, Greaseable Hinges  
Tubular Telescoping Driveshaft Members  
Standard Self Level Hitch Clevis  
30 mm Pivot Pins with Single Bushings  
Six Wheel Spring Suspension  
4-Bolt Wheel Hubs  
Simultaneous Wing Lift  
Front and rear safety shields reduce the risk of  
thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

227FP		HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 Wheels <i>Serial Number POHX15F018500 and above.</i>	20,979.00
-------	--	--	-----------

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DESTINATION ...Continued...</b>	
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**TIRES**

		<b>Laminated Tires</b>	
1200		21.0" x 5.25" x 9.00" Puncture-Proof Laminated Tires	In Base Price
		<b>Severe Duty Tires</b>	
1210		21" x 7" x 12" 16 PR Severe Duty Ag Tires	421.00
1230		21" x 7" x 12" 16 PR Foam Filled Severe Duty Ag Tires	756.00

**FRONT SAFETY SHIELD**

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	144.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	144.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires	930.00
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
<b>DOUBLE WHEEL ON WINGS</b>			
9022		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" PunctureProof Laminated Tires <i>Can also be used to provide dual wheels for center section.</i>	779.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	98.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>DOUBLE WHEEL ON WINGS</b>	
BWA1244		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" PunctureProof Laminated Tires <i>Can also be used to provide dual wheels for center section.</i>	856.90
		<b>Drivelines</b>	
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
W49091		Deck Ring (Center Section) <i>Three required.</i>	58.51
W49092		Deck Ring (Wing Sections) <i>Three required.</i>	51.52
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BP18696		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires	1,023.00
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Safety Shields</b>	
	BW15670	Front Safety Shield - Second Row Chain	509.30
	BW15671	Rear Safety Shield - Second Row Chain	397.10
		<b>Severe Duty Tires</b>	
	AW34778	533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>WALKING TANDEM</b>	
	BP18538	Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
	BW15083	Extra Wing Cylinder Hose	107.80
		<b>Weight Box</b>	
	AW33895	Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		<b>Wheels and Tires</b>	
	BW14521	Dual Wing Wheel Spindles and Hubs <i>1 Bolt.</i>	588.50

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Wheels**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Wheels**

Equipment for Base Machine

<p>Pull Type Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0 mm) Lower Deck Thickness: 0.138 In. (3.5 mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267 mm) Body Depth 1/4 In. (6 mm) Side Skirt Thickness 15 Ft. (4.6 m) Cutting Width Blade Tip Speed: 15,841 fpm, 80.4 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels 21" x 7" x 12" 16PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit - comply with regulations Fully Assembled Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self Level Hitch Clevis 30 mm Pivot Pins with Single Bushings Six Wheel Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

227GP	HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 Wheels <i>Serial Number POHX15F018500 and above.</i>	22,038.00
-------	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost
0192	Haiti	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost
<b>FRONT SAFETY SHIELD</b>			
1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	144.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	144.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DRIVELINES ...Continued...</b>			
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires	930.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	98.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
<b>INDEPENDENT CONTROL VALVE</b>			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
W49091		Deck Ring (Center Section) <i>Three required.</i>	58.51
W49092		Deck Ring (Wing Sections) <i>Three required.</i>	51.52
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires	1,023.00
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW15083		Extra Wing Cylinder Hose	107.80
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Wheels and Tires</b>	
	BW14521	Dual Wing Wheel Spindles and Hubs <i>1 Bolt.</i>	588.50

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Wheels**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled Wheels  
Equipment for Base Machine**

Pull Type  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.118 In. (3.0 mm)  
Lower Deck Thickness: 0.138 In. (3.5 mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 210 HP (156 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 150 HP (111 kW)  
1-3/4 In. Gear case Input Shafts  
3 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267 mm) Body Depth  
1/4 In. (6 mm) Side Skirt Thickness  
15 Ft. (4.6 m) Cutting Width  
Blade Tip Speed:  
15,841 fpm, 80.4 m/s  
3-Section Flexible 90 Degrees Up for transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available  
row spacing, especially for ridge-till

applications)  
Six Foam Filled Wheels 21" x 7" x 12" 16PR Severe  
Duty Ag Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit - comply with regulations  
Fully Assembled  
Heavy Duty Rating  
Intermittent, Greaseable Hinges  
Tubular Telescoping Driveshaft Members  
Standard Self Level Hitch Clevis  
30 mm Pivot Pins with Single Bushings  
Six Wheel Spring Suspension  
4-Bolt Wheel Hubs  
Simultaneous Wing Lift

Front and rear safety shields reduce the risk of  
thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

227HP		HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 Foam Filled Wheels <i>Serial Number POHX15FAGG072612 and above.</i>	22,388.00
-------	--	---	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0196	Nicaragua	No Added Cost

**FRONT SAFETY SHIELD**

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled Wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	144.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	144.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	98.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
BW15063		<b>INDEPENDENT CONTROL VALVE</b> Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled Wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BP18696		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW15083		Extra Wing Cylinder Hose	107.80

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX15 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled Wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.138 In. (3.5mm) Lower Deck Thickness: 0.177 In. (4.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 216 HP (161 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 160 HP (119 kW) 1-3/4 In. Gear case Input Shafts 4 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm Side Skirt Thickness 15 Ft. (4.6m) Cutting Width Blade Tip Speed: 15,590 fpm, 79.2 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels - 21" x 5.25" x 9" - Puncture Proof Laminated Tires Constant Velocity with Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit comply to regulation Fully Assembled Commercial Duty Rating Deck Rings Continuous, Full Length, Greaseable Hinges Splined Telescoping Driveshaft Members Ball Type Self Level Hitch Clevis 30 mm Pivot Pins with Double Bushings Air Cushioned Suspension with Shock Absorbers 5-Bolt Wheel Hubs Independent Wing Lift</p>
--	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

225FP	CX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades <i>Serial Number POCX15E008500 and above.</i>	23,322.00
-------	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost
0192	Haiti	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**TIRES**

<b>Laminated Tires</b>			
1200		21.0" x 5.25" x 9.00" Puncture-Proof Laminated Tires	In Base Price
<b>Severe Duty Tires</b>			
1220		26" x 9" x 14.5" 24 Ply "Fat Boy" Severe Duty Ag Tires	651.00
1240		26" x 9" x 14.5" 24 Ply Foam Filled "Fat Boy" Severe Duty Ag Tires	991.00

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
------	--	-----------------------------	---------------

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	144.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	144.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
<b>LAMINATED TIRES</b>			
9024		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" PunctureProof Laminated Tires	772.00
<b>SEVERE DUTY TIRES</b>			
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy"Severe Duty Ag Tires	1,008.00
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy"Severe Duty Ag Tires	1,120.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Drivelines</b>	
BP18399		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 540 RPM - 34.925 mm (1 3/8 in.)	1,471.80
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>LAMINATED TIRES</b>	
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
BP18697		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe Duty Ag Tires	See Parts
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		<b>Wheels and Tires</b>	
AW30747		21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.138 In. (3.5mm) Lower Deck Thickness: 0.177 In. (4.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 216 HP (161 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 160 HP (119 kW) 1-3/4 In. Gear case Input Shafts 4 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 15 Ft. (4.6m) Cutting Width Blade Tip Speed: 15,841 fpm, 80.5 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels - 21" x 5.25" x 9" - Puncture Proof Laminated Tires Constant Velocity with Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit comply to regulations Fully Assembled Commercial Duty Rating Deck Rings Continuous, Full Length, Greaseable Hinges Splined Telescoping Driveshaft Members Ball Type Self Level Hitch Clevis 30 mm Pivot Pins with Double Bushings Air Cushioned Suspension with Shock Absorbers 5-Bolt Wheel Hubs Independent Wing Lift</p>
---	--

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

225GP	CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades	Serial Number P0CX15F008500 and above.	23,302.00
-------	--	--	-----------

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost
0192	Haiti		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**TIRES**

<b>Laminated Tires</b>			
1200		21.0" x 5.25" x 9.00" Puncture-Proof Laminated Tires	In Base Price
<b>Severe Duty Tires</b>			
1220		26" x 9" x 14.5" 24 Ply "Fat Boy" Severe Duty Ag Tires	651.00
1240		26" x 9" x 14.5" 24 Ply Foam Filled "Fat Boy" Severe Duty Ag Tires	991.00

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
------	--	-----------------------------	---------------

## AGRICULTURAL PRODUCTS

### JOHN DEERE ROTARY CUTTERS

#### CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	144.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	144.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
<b>LAMINATED TIRES</b>			
9024		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" PunctureProof Laminated Tires	772.00
<b>SEVERE DUTY TIRES</b>			
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy"Severe Duty Ag Tires	1,008.00
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy"Severe Duty Ag Tires	1,120.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Drivelines</b>	
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10

**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
		<b>Hitches</b>	
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otumwa Works.</i>	44.00
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>LAMINATED TIRES</b>	
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
BP18697		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe Duty Ag Tires	See Parts
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74



AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Wheels and Tires</b>	
	AW30747	21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
	AW34779	26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX15 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Wheels  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.138 In. (3.5mm) Lower Deck Thickness: 0.177 In. (4.5mm) Three Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 216 HP (161 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 160 HP (119 kW) 1-3/4 In. Gear case Input Shafts 4 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm Side Skirt Thickness 15 Ft. (4.6m) Cutting Width Blade Tip Speed: 15,590 fpm, 79.2 m/s 2-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angle 45 Degrees Up, working angle Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Five Wheels - 26" x 9" x 14.5" 24 Ply "Fat Boy" Severe Duty Ag Tires Constant Velocity with Lock-Slide Collar Tractor-to-Cutter Driveline Two Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit comply to regulation Fully Assembled Commercial Duty Rating Deck Rings Continuous, Full Length, Greaseable Hinges Splined Telescoping Driveshaft Members Ball Type Self Level Hitch Clevis 30 mm Pivot Pins with Double Bushings Air Cushioned Suspension with Shock Absorbers 5-Bolt Wheel Hubs</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

225CP	CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 5 Wheels <i>Serial Number POCX15G008500 and above.</i>	19,116.00
-------	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DESTINATION ...Continued...</b>			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**WALKING TANDEM**

9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
------	--	---	----------

**ATTACHMENTS FOR FIELD CONVERSION**

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Drivelines</b>	
BP18399		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 540 RPM - 34.925 mm (1 3/8 in.)	1,471.80
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - Single  
Suction Blades - 6 Wheels  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.138 In. (3.5mm) Lower Deck Thickness: 0.177 In. (4.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 216 HP (161 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 160 HP (119 kW) 1-3/4 In. Gear case Input Shafts 4 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm Side Skirt Thickness 15 Ft. (4.6m) Cutting Width Blade Tip Speed: 15,590 fpm, 79.2 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels - 26" x 9" x 14.5" 24 Ply "Fat Boy" Severe Duty Ag Tires Constant Velocity with Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit comply to regulation Fully Assembled Commercial Duty Rating Deck Rings Continuous, Full Length, Greaseable Hinges Splined Telescoping Driveshaft Members Ball Type Self Level Hitch Clevis 30 mm Pivot Pins with Double Bushings Spring Suspension with Shock Absorbers Shock Absorbers 5-Bolt Wheel Hubs Independent Wing Lift</p>
--	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

225EP	CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - Single Suction Blades - 6 Wheels	Serial Number POCX15F008500 and above.	22,772.00
-------	---	--	-----------

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - Single  
Suction Blades - 6 Wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DESTINATION ...Continued...</b>	
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
		<b>WALKING TANDEM</b>	
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
		<b>SEVERE DUTY TIRES</b>	
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,008.00



**AGRICULTURAL PRODUCTS**  
**JOHN DEERE ROTARY CUTTERS**

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - Single  
Suction Blades - 6 Wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>SEVERE DUTY TIRES ...Continued...</b>			
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	466.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18399		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 540 RPM - 34.925 mm (1 3/8 in.)	1,471.80
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
<b>INDEPENDENT CONTROL VALVE</b>			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control)	904.20
<b>LAMINATED TIRES</b>			
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
<b>SEVERE DUTY TIRES</b>			
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
<b>SPREADING CONTROL KIT</b>			
BP18443		Spreading Control Kit	512.60
<b>Safety Shields</b>			
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - Single Suction Blades - 6 Wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		<b>Wheels and Tires</b>	
AW30747		21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Foam filled Tires  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.138 In. (3.5mm) Lower Deck Thickness: 0.177 In. (4.5mm) Three Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 216 HP (161 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 160 HP (119 kW) 1-3/4 In. Gear case Input Shafts 4 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm Side Skirt Thickness 15 Ft. (4.6m) Cutting Width Blade Tip Speed: 15,590 fpm, 79.2 m/s 2-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angle 45 Degrees Up, working angle Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Five Foam Filled Wheels - 26" x 9" x 14.5" 24 Ply "Fat Boy" Severe Duty Ag Tires Constant Velocity with Lock-Slide Collar Tractor-to-Cutter Driveline Two Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit comply to regulation Fully Assembled Commercial Duty Rating Deck Rings Continuous, Full Length, Greaseable Hinges Splined Telescoping Driveshaft Members Ball Type Self Level Hitch Clevis 30 mm Pivot Pins with Double Bushings Air Cushioned Suspension with Shock Absorbers 5-Bolt Wheel Hubs</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

225NP	CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 5 Foam filled Tires	Serial Number P0CX15GEGC046767 and above.	19,413.00
-------	--	---	-----------

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost
0192	Haiti		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Foam filled Tires**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge

**WALKING TANDEM**

9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
------	--	---	----------

**ATTACHMENTS FOR FIELD CONVERSION**

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Foam filled Tires**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX15 - 10 Ft. Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction  
Blades - 5 Foam filled Tires**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - 6  
Wheels Foam Filled  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.138 In. (3.5mm) Lower Deck Thickness: 0.177 In. (4.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 216 HP (161 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 160 HP (119 kW) 1-3/4 In. Gear case Input Shafts 4 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm Side Skirt Thickness 15 Ft. (4.6m) Cutting Width Blade Tip Speed: 15,590 fpm, 79.2 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing (Refer to Ag Sales Manual for available</p>	<p>row spacing, especially for ridge-till applications) Six Foam Filled Wheels - 26" x 9" x 14.5" 24 Ply "Fat Boy" Severe Duty Ag Tires Constant Velocity with Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit comply to regulation Fully Assembled Commercial Duty Rating Deck Rings Continuous, Full Length, Greaseable Hinges Splined Telescoping Driveshaft Members Ball Type Self Level Hitch Clevis 30 mm Pivot Pins with Double Bushings Spring Suspension with Shock Absorbers Shock Absorbers 5-Bolt Wheel Hubs Independent Wing Lift</p>
--	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

225MP	CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - 6 Wheels Foam Filled <i>Serial Number POCX15EAGF048608 and above.</i>		23,127.00
-------	--	--	-----------

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - 6  
Wheels Foam Filled**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>DESTINATION ...Continued...</b>	
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
		<b>WALKING TANDEM</b>	
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
		<b>SEVERE DUTY TIRES</b>	
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe	1,120.00



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - 6  
Wheels Foam Filled**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>SEVERE DUTY TIRES ...Continued...</b> Duty Ag Tires	
		<b>INDEPENDENT CONTROL VALVE</b>	
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
		<b>SPREADING CONTROL KIT</b>	
9010		Spreading Control Kit	466.00
		<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BP18697		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy"Severe Duty Ag Tires	See Parts
		<b>SPREADING CONTROL KIT</b>	
BP18443		Spreading Control Kit	512.60
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX15 - Flex-Wing Rotary Cutter - Spring Suspension -540 RPM- Stump Jumpers - 6  
Wheels Foam Filled**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 540 RPM - Stump Jumpers - Single Suction Blades - 6 wheels**

Equipment for Base Machine

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,069 fpm, 81.6 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Pre-set wing drivelines Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Fully Assembled Transport light kit -comply to regulations Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

224AP	HX20 Flex-Wing Rotary Cutter - 540 RPM - Stump Jumpers - Single Suction Blades - 6 wheels <i>Serial Number POHX20E006500 and above.</i>	27,339.00
-------	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 540 RPM - Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

**REAR SAFETY SHIELD**

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

**OPERATOR'S MANUAL, DECALS, AND LANGUAGE**

9099		French Operator's Manual and Decal Kit	No Charge
------	--	--	-----------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 540 RPM - Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
<b>...Continued...</b>			
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	930.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	96.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	626.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18398		Standard Driveline with Clutch and Lick-Slide Collar - 1000 RPM 1-3/4 Power Take-Off (PTO)	1,372.80
BP18397		Standard Driveline with Clutch and Lock-Slide Collar - 1000 RPM 1-3/8 Power Take-Off (PTO)	1,141.80
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
<b>INDEPENDENT CONTROL VALVE</b>			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
<b>Laminated Tires</b>			
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 540 RPM - Stump Jumpers - Single Suction Blades - 6 wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
W49089		Deck Ring <i>Nine required.</i>	68.72
W50394		HX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	260.09
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	1,023.00
		<b>SPREADING CONTROL KIT</b>	
BP18444		Spreading Control Kit	688.60
		<b>Safety Shields</b>	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW14559		Extra Wing Cylinder Hose	105.60
		<b>Weight Box</b>	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,069 fpm, 81.6 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Foam Filled Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Pre-set wing drivelines Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Fully Assembled Transport light kit -comply to regulations Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

<i>EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario</i>			
224GP		HX20 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6 Foam Filled wheels <i>Serial Number POHX20E006500 and above.</i>	27,694.00

**DESTINATION**

0202		United States	In Base Price
0184		Canada	No Added Cost
0195		Mexico	No Added Cost
0220		Uruguay	No Added Cost

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
------	--	-----------------------------	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	141.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	96.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	626.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
BW15063		INDEPENDENT CONTROL VALVE Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
BW14560		OPERATOR'S MANUAL, DECALS, AND LANGUAGE French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
BP18696		SEVERE DUTY TIRES Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts



AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>SPREADING CONTROL KIT</b>	
	BP18444	Spreading Control Kit	688.60
		<b>WALKING TANDEM</b>	
	BP18538	Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
	BW14559	Extra Wing Cylinder Hose	105.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX20 Flex-Wing Rotary Cutter - 540 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 wheels**

Equipment for Base Machine

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,327 fpm, 82.9 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit - to comply with regulations Fully Assembled Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

224BP	HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 wheels <i>Serial Number POHX20F006500 and above.</i>	27,339.00
-------	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

**REAR SAFETY SHIELD**

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

**DRIVELINES**

1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
------	--	---	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DRIVELINES ...Continued...</b>			
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	930.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	96.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	626.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
<b>INDEPENDENT CONTROL VALVE</b>			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
W49089		Deck Ring <i>Nine required.</i>	68.72
W50394		HX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	260.09
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	1,023.00
		<b>SPREADING CONTROL KIT</b>	
BP18444		Spreading Control Kit	688.60
		<b>Safety Shields</b>	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW14559		Extra Wing Cylinder Hose	105.60
		<b>Weight Box</b>	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Wheels and Tires</b>	
	BW14521	Dual Wing Wheel Spindles and Hubs <i>1 Bolt.</i>	588.50

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,327 fpm, 82.9 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Foam Filled Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit - to comply with regulations Fully Assembled Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

224HP	HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 Foam Filled wheels	Serial Number POHX20F006500 and above.	27,694.00
-------	---	--	-----------

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost

**FRONT SAFETY SHIELD**

1600	Front Safety Shield - Chain		In Base Price
------	-----------------------------	--	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	141.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	96.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	626.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
BW15063		<b>INDEPENDENT CONTROL VALVE</b> Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
BW14560		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b> French Operator's Manual and Decal Kit	No Charge

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	BW15680	Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
	BP18696	Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts
		<b>SPREADING CONTROL KIT</b>	
	BP18444	Spreading Control Kit	688.60
		<b>WALKING TANDEM</b>	
	BP18538	Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
	BW14559	Extra Wing Cylinder Hose	105.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,327 fpm, 82.9 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit - to comply with regulations Fully Assembled Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

<i>EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario</i>			
224CP		HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 wheels <i>Serial Number POHX20G006500 and above.</i>	27,783.00

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost
0182	Barbados		No Added Cost
0188	Dominican Republic		No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DESTINATION ...Continued...</b>			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

**REAR SAFETY SHIELD**

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

**DRIVELINES**

1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
------	--	---	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DRIVELINES ...Continued...</b>			
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9023		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	930.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	96.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	626.00
<b>SHREDDING KIT</b>			
9011		Shredding Attachment Kit	1,583.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otunwa Works.</i>	44.00

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>Laminated Tires</b>	
AW30717		533.4 mm (21 in.) by 133.35 mm (5.25 in.) by 228.6 mm (9 in.) Laminated Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	140.80
		<b>Miscellaneous</b>	
AW32489		Bag of Hardware - For Shredding Attachment Kit	95.70
W49089		Deck Ring <i>Nine required.</i>	68.72
W50394		HX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	260.09
BWA1489		Shredding Attachment Kit	1,630.84
BW15812		Stalk Shredder Attachment <i>For CX20 / HX20</i>	335.50
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1245		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR SevereDuty Ag Tires <i>Can also be used to provide dual wheels for center section.</i>	1,023.00
		<b>SPREADING CONTROL KIT</b>	
BP18444		Spreading Control Kit	688.60
		<b>Safety Shields</b>	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		<b>Severe Duty Tires</b>	
AW34778		533.4 mm (21 in.) by 177.8 mm (7 in.) by 304.8 mm (12 in.) 16 PR Severe Duty AG Tire and Wheel <i>Additional wheel and tire. Requires wheel support and hub.</i>	227.70



AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW14559		Extra Wing Cylinder Hose	105.60
		<b>Weight Box</b>	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels  
Equipment for Base Machine**

<p>Pull Type Double Deck Design Easy Clean Dome Shaped Top Deck Deck Thickness: Upper Deck Thickness: 0.118 In. (3.0mm) Lower Deck Thickness: 0.138 In. (3.5mm) Four Gear cases Peak Horsepower Rating: Splitter 300 HP (223 kW) Wing 210 HP (156 kW) Continuous Horsepower Rating: Splitter 250 HP (186 kW) Wing 150 HP (111 kW) 1-3/4 In. Gear case Input Shafts 3 In. Brush Cutting Capacity Unibody Frame: 10.5 In. (267mm) Body Depth 1/4 In. (6mm) Side Skirt Thickness 20 Ft. (6.1m) Cutting Width Blade Tip Speed: 16,327 fpm, 82.9 m/s 3-Section Flexible 90 Degrees Up for transportation 22 Degrees Down, working angles 45 Degrees Up, working angles Level Lift (Fore/Aft and Side-to-Side) Lift and Fold Hydraulics Lift Cylinder Depth Stops Double Leveling Rods Easy Adjust Wing Leveling Turnbuckles Adjustable Wheel Spacing</p>	<p>(Refer to Ag Sales Manual for available row spacing, especially for ridge-till applications) Six Foam Filled Wheels - 21" x 7" x 12" 16 PR Severe Duty Ag Tires Constant Velocity and Lock-Slide Collar Tractor-to-Cutter Driveline Three Slip Clutches, Factory Preset, Front and Rear Safety Shields - Chains Bolt-On Wear Shoes Safety Tow Chain Hitch Integrated Jack Stand, Implement Jack SMV Emblem and Support Transport light kit - to comply with regulations Fully Assembled Heavy Duty Rating Intermittent, Greaseable Hinges Tubular Telescoping Driveshaft Members Standard Self-Level Hitch Clevis 30mm Pivot Pins with Single Bushings Standard Spring Suspension 4-Bolt Wheel Hubs Simultaneous Wing Lift Front and rear safety shields reduce the risk of thrown objects which could be hazardous.</p>
---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

<i>EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario</i>			
224KP		HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 Foam Filled wheels <i>Serial Number POHX20G006500 and above.</i>	28,141.00

**DESTINATION**

0202	United States		In Base Price
0184	Canada		No Added Cost
0195	Mexico		No Added Cost
0220	Uruguay		No Added Cost

**FRONT SAFETY SHIELD**

1600	Front Safety Shield - Chain		In Base Price
------	-----------------------------	--	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	141.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9080		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,800.00
<b>SEVERE DUTY TIRES</b>			
9026		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	1,043.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>WING CYLINDER HOSE</b>			
9050		Extra Wing Cylinder Hose	96.00
<b>SPREADING CONTROL KIT</b>			
9010		Spreading Control Kit	626.00
<b>SHREDDING KIT</b>			
9011		Shredding Attachment Kit	1,583.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
BW15063		<b>INDEPENDENT CONTROL VALVE</b> Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BP18696		Dual Wing Wheel Spindles, Hubs and 21" x 7" x 12" 16 PR Foam filled SevereDuty Ag Tires	See Parts
		<b>SPREADING CONTROL KIT</b>	
BP18444		Spreading Control Kit	688.60
		<b>WALKING TANDEM</b>	
BP18538		Walking Tandem Kit <i>Note: Kit just for centre section. For full coverage order 1 additional kit and 2 additional tires</i>	1,980.00
		<b>WING CYLINDER HOSE</b>	
BW14559		Extra Wing Cylinder Hose	105.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**HX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 wheels**

Equipment for Base Machine

Pull Type  
Double Deck Design  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.138 In. (3.5mm)  
Lower Deck Thickness: 0.18 In. (4.5mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 216 HP (159 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 160 HP (119 kW)  
1-3/4 In. Gear case Input Shafts  
4 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267mm) Body Depth  
1/4 In. (6mm) Side Skirt Thickness  
20 Ft. (6.1 m) Cutting Width  
Blade Tip Speed:  
16,327 fpm, 82.9 m/s  
3-Section Flexible 90 Degrees Up for transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)  
Six Wheels - 26" x 9" x 14.5" 24 Ply  
"Fat Boy" Severe Duty Ag Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit comply with regulation  
Fully Assembled  
Commercial Duty Rating  
Deck Rings  
Continuous, Full Length, Greaseable Hinges  
Splined Telescoping Driveshaft Members  
Ball Type Self Level Hitch Clevis  
30mm Pivot Pins with Double Bushings  
Air Cushioned Suspension with  
Shock Absorbers  
5-Bolt Wheel Hubs  
Independent Wing Lift  
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2268P		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 wheels <i>Serial Number POCX20F005000 and above.</i>	34,484.00
-------	--	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

**REAR SAFETY SHIELD**

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

**DRIVELINES**



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>DRIVELINES ...Continued...</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
<b>SEVERE DUTY TIRES</b>			
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,008.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
BP18398		Standard Driveline with Clutch and Lock-Slide Collar - 1000 RPM 1-3/4 Power Take-Off (PTO)	1,372.80
BP18397		Standard Driveline with Clutch and Lock-Slide Collar - 1000 RPM 1-3/8 Power Take-Off (PTO)	1,141.80
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otumwa Works.</i>	44.00
<b>INDEPENDENT CONTROL VALVE</b>			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
W50393		CX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	250.28
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		<b>Safety Shields</b>	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91
		<b>Wheels and Tires</b>	
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60
BW14522		Dual Wing Wheel Spindles and Hubs	550.00
AW33092		Tire and tube kit for 26" x 9" x 14.5" 'Fat Boy' Severe Duty Ag Tire	310.84

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels  
Equipment for Base Machine**

Pull Type  
Double Deck Design  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.138 In. (3.5mm)  
Lower Deck Thickness: 0.18 In. (4.5mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 216 HP (159 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 160 HP (119 kW)  
1-3/4 In. Gear case Input Shafts  
4 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267mm) Body Depth  
1/4 In. (6mm) Side Skirt Thickness  
20 Ft. (6.1 m) Cutting Width  
Blade Tip Speed:  
16,327 fpm, 82.9 m/s  
3-Section Flexible 90 Degrees Up for transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)  
Six Foam Filled Wheels - 26" x 9" x 14.5" 24 Ply  
"Fat Boy" Severe Duty Ag Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit comply with regulation  
Fully Assembled  
Commercial Duty Rating  
Deck Rings  
Continuous, Full Length, Greaseable Hinges  
Splined Telescoping Driveshaft Members  
Ball Type Self Level Hitch Clevis  
30mm Pivot Pins with Double Bushings  
Air Cushioned Suspension with  
Shock Absorbers  
5-Bolt Wheel Hubs  
Independent Wing Lift  
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

226AP		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6 Foam Filled wheels <i>Serial Number POCX20F005000 and above.</i>	34,832.00
-------	--	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost

**FRONT SAFETY SHIELD**

1600	Front Safety Shield - Chain	In Base Price
------	-----------------------------	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	141.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
<b>SEVERE DUTY TIRES</b>			
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe Duty Ag Tires	1,008.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
	<b>Drivelines</b>		
BP18399		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 540 RPM - 34.925 mm (1 3/8 in.)	1,471.80
	<b>Hitches</b>		
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Otumwa Works.</i>	44.00
	<b>INDEPENDENT CONTROL VALVE</b>		
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>LAMINATED TIRES</b>	
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		<b>Wheels and Tires</b>	
AW30747		21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Stump Jumpers - Single Suction Blades - 6  
Foam Filled wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels**

Equipment for Base Machine

Pull Type  
Double Deck Design  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.138 In. (3.5mm)  
Lower Deck Thickness: 0.18 In. (4.5mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 216 HP (159 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 160 HP (119 kW)  
1-3/4 In. Gear case Input Shafts  
4 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267mm) Body Depth  
1/4 In. (6mm) Side Skirt Thickness  
20 Ft. (6.1 m) Cutting Width  
Blade Tip Speed:  
16,327 fpm, 82.9 m/s  
3-Section Flexible 90 Degrees Up for transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)  
Six Wheels - 26" x 9" x 14.5" 24 Ply  
"Fat Boy" Severe Duty Ag Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit comply with regulation  
Fully Assembled  
Commercial Duty Rating  
Deck Rings  
Continuous, Full Length, Greaseable Hinges  
Splined Telescoping Driveshaft Members  
Ball Type Self Level Hitch Clevis  
30mm Pivot Pins with Double Bushings  
Air Cushioned Suspension with  
Shock Absorbers  
5-Bolt Wheel Hubs  
Independent Wing Lift  
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

2269P		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 wheels <i>Serial Number POCX20F005000 and above.</i>	35,328.00
-------	--	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost
0182	Barbados	No Added Cost
0188	Dominican Republic	No Added Cost

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DESTINATION ...Continued...</b>			
0192		Haiti	No Added Cost
0194		Jamaica	No Added Cost
0201		Trinidad & Tobago	No Added Cost
0203		Puerto Rico	No Added Cost
0183		Belize	No Added Cost
0185		Costa Rica	No Added Cost
0189		El Salvador	No Added Cost
0191		Guatemala	No Added Cost
0193		Honduras	No Added Cost
0196		Nicaragua	No Added Cost
0197		Panama	No Added Cost
0211		Bolivia	No Added Cost
0213		Chile	No Added Cost
0214		Colombia	No Added Cost
0215		Ecuador	No Added Cost
0216		Guyana	No Added Cost
0217		Paraguay	No Added Cost
0218		Peru	No Added Cost
0219		Suriname	No Added Cost
0221		Venezuela	No Added Cost

**FRONT SAFETY SHIELD**

1600		Front Safety Shield - Chain	In Base Price
1620		Front Safety Shield - Second Row Chain	141.00

**REAR SAFETY SHIELD**

1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00

**DRIVELINES**



**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Continued**

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>DRIVELINES ...Continued...</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
<b>SEVERE DUTY TIRES</b>			
9025		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,008.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>SHREDDING KIT</b>			
9011		Shredding Attachment Kit	1,583.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00
<b>INDEPENDENT CONTROL VALVE</b>			
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
<b>Miscellaneous</b>			
AW32489		Bag of Hardware - For Shredding Attachment Kit	95.70

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 wheels  
Continued**

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
W50393		CX20 Center Section Wheel Spindle for 38 In. Rows <i>Two required.</i>	250.28
BWA1489		Shredding Attachment Kit	1,630.84
BW15812		Stalk Shredder Attachment <i>For CX20 / HX20</i>	335.50
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		<b>Safety Shields</b>	
BW15672		Front Safety Shield - Second Row Chain	655.60
BW15673		Rear Safety Shield - Second Row Chain	460.90
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW30669		Weight Box <i>To replace left wing for conversion from 20 Ft. to 13.5 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	9,628.91
		<b>Wheels and Tires</b>	
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60
BW14522		Dual Wing Wheel Spindles and Hubs	550.00
AW33092		Tire and tube kit for 26" x 9" x 14.5" "Fat Boy" Severe Duty Ag Tire	310.84

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels  
Equipment for Base Machine**

Pull Type  
Double Deck Design  
Easy Clean Dome Shaped Top Deck  
Deck Thickness:  
Upper Deck Thickness: 0.138 In. (3.5mm)  
Lower Deck Thickness: 0.18 In. (4.5mm)  
Four Gear cases  
Peak Horsepower Rating:  
Splitter 300 HP (223 kW)  
Wing 216 HP (159 kW)  
Continuous Horsepower Rating:  
Splitter 250 HP (186 kW)  
Wing 160 HP (119 kW)  
1-3/4 In. Gear case Input Shafts  
4 In. Brush Cutting Capacity  
Unibody Frame:  
10.5 In. (267mm) Body Depth  
1/4 In. (6mm) Side Skirt Thickness  
20 Ft. (6.1 m) Cutting Width  
Blade Tip Speed:  
16,327 fpm, 82.9 m/s  
3-Section Flexible 90 Degrees Up for transportation  
22 Degrees Down, working angles  
45 Degrees Up, working angles  
Level Lift (Fore/Aft and Side-to-Side)  
Lift and Fold Hydraulics  
Lift Cylinder Depth Stops  
Double Leveling Rods  
Easy Adjust Wing Leveling Turnbuckles  
Adjustable Wheel Spacing  
(Refer to Ag Sales Manual for available

row spacing, especially for ridge-till applications)  
Six Foam Filled Wheels - 26" x 9" x 14.5" 24 Ply  
"Fat Boy" Severe Duty Ag Tires  
Constant Velocity and Lock-Slide Collar  
Tractor-to-Cutter Driveline  
Three Slip Clutches, Factory Preset,  
Front and Rear Safety Shields - Chains  
Bolt-On Wear Shoes  
Safety Tow Chain  
Hitch Integrated Jack Stand, Implement Jack  
SMV Emblem and Support  
Transport light kit comply with regulation  
Fully Assembled  
Commercial Duty Rating  
Deck Rings  
Continuous, Full Length, Greaseable Hinges  
Splined Telescoping Driveshaft Members  
Ball Type Self Level Hitch Clevis  
30mm Pivot Pins with Double Bushings  
Air Cushioned Suspension with  
Shock Absorbers  
5-Bolt Wheel Hubs  
Independent Wing Lift  
Front and rear safety shields reduce the risk of thrown objects which could be hazardous.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

*EX-WORKS Laredo, Texas; Marinez, Georgia; Waterloo, Iowa; Frisco, Texas; Grimsby, Ontario*

226BP		CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades - 6 Foam Filled wheels <i>Serial Number POCX20F005000 and above.</i>	35,678.00
-------	--	--	-----------

**DESTINATION**

0202	United States	In Base Price
0184	Canada	No Added Cost
0195	Mexico	No Added Cost
0220	Uruguay	No Added Cost

**FRONT SAFETY SHIELD**

1600	Front Safety Shield - Chain	In Base Price
------	-----------------------------	---------------

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>FRONT SAFETY SHIELD ...Continued...</b>			
1620		Front Safety Shield - Second Row Chain	141.00
<b>REAR SAFETY SHIELD</b>			
1700		Rear Safety Shield - Chain	In Base Price
1720		Rear Safety Shield - Second Row Chain	141.00
<b>DRIVELINES</b>			
1010		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/8 In.	In Base Price
1030		Constant Velocity with Lock-Slide Collar Driveline, Cat. 5, 1000 RPM, 1-3/4 In.	54.00
<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>			
9099		French Operator's Manual and Decal Kit	No Charge
9100		Spanish Operator's Manual and Decal Kit	No Charge
<b>WALKING TANDEM</b>			
9070		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	1,852.00
<b>SEVERE DUTY TIRES</b>			
9027		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR Foam Filled "Fat Boy" Severe Duty Ag Tires	1,008.00
<b>INDEPENDENT CONTROL VALVE</b>			
9030		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	822.00
<b>SHREDDING KIT</b>			
9011		Shredding Attachment Kit	1,583.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Drivelines</b>			
BP18400		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 34.925 mm (1 3/8 in.)	1,453.10
BP18401		Constant Velocity with Lock-Slide Collar Driveline, Category 5, 1000 RPM - 44.45 mm (1 3/4 in.)	1,514.70
<b>Hitches</b>			
BE24260		Safety chain for towed equipment, 4535.924 kg (10,000 lb) <i>Order from JD Ottumwa Works.</i>	44.00

**AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS**

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>INDEPENDENT CONTROL VALVE</b>	
BW15063		Independent Control Valve - 3 Function with Hoses and ROPS Mounting Bracket(For Separate Wing and Lift Control) <i>Can be used with either open or closed center hydraulics.</i>	904.20
		<b>LAMINATED TIRES</b>	
BWA1246		Dual Wing Wheel Spindles, Hubs and 21.0" x 5.25" x 9.0" Puncture Proof Laminated Tires	849.20
		<b>OPERATOR'S MANUAL, DECALS, AND LANGUAGE</b>	
BW14560		French Operator's Manual and Decal Kit	No Charge
BW15680		Spanish Operator's Manual and Decal Kit	No Charge
		<b>SEVERE DUTY TIRES</b>	
BWA1247		Dual Wing Wheel Spindles, Hubs and 26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tires	1,108.80
		<b>Safety Shields</b>	
BW15670		Front Safety Shield - Second Row Chain	509.30
BW15671		Rear Safety Shield - Second Row Chain	397.10
		<b>WALKING TANDEM</b>	
BP18539		Walking Tandem Kit <i>Kit just for center section. For full coverage order 1 additional kit and 2 additional tires. Machine is not available with the walking tandem installed, kit to be installed by the dealer.</i>	2,037.20
		<b>Weight Box</b>	
AW33895		Weight Box <i>To replace left wing for conversion from 15 Ft. to 10 Ft. flex wing. See parts catalog for other parts needed for conversion.</i>	3,842.74
		<b>Wheels and Tires</b>	
AW30747		21.0" x 5.25" x 9.0" Laminated Tire and Wheel	157.87
AW34779		26" x 9" x 14.5" 24 PR "Fat Boy" Severe Duty Ag Tire and Wheel	281.60

AGRICULTURAL PRODUCTS  
JOHN DEERE ROTARY CUTTERS

---

**CX20 Flex-Wing Rotary Cutter - 1000 RPM- Bar Type Bladeholders - Dual Suction Blades  
- 6 Foam Filled wheels**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---