

CATERPILLAR MACHINE PRICE LIST

M318F

M318 HYDRAULIC WHEEL EXCAVATOR
 GRENOBLE, FRANCE

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

- Engine:
- Cat C7.1, EPA/ARB tier 4 Final and EU
- Stage IV certified engine with
- Aftertreatment
- Altitude capability: 3000m/9842 ft
- Automatic engine speed Control
 incl. one touch low idle
 and engine idle shutdown functionality
- Automatic starting aid
- Power mode selector

UNDERCARRIAGE

- Four wheel drive
- Heavy-duty axles with advanced disc
 brake system and travel motor with
 adjustable braking force
- Hydrostatic transmission, two speed
- Full hydraulic steering with emergency
 capability
- Oscillating front axle, lockable, with
 remote greasing point
- Automatic lock mode for oscillating
 front axle & service brake
- Steps including tool boxes, left & right
- Creeper speed

HYDRAULICS

- Cat XT-6 ES hoses
- Heavy lift mode
- Separate swing pump
- Load sensing hydraulic system
- Adjustable hydraulic sensitivity

ELECTRICAL

- Alternator, 115 ampere
- Roading lights (two front, two rear)
- Main shut-off switch
- Signal/warning horn
- Two Caterpillar maintenance
 free batteries
- Refueling pump

OPERATOR ENVIRONMENT

- Reinforced cab structure compliant with
 2006/42/EC and tested according
 ISO 12117-2:2008
- Air conditioner heater & defroster
- Adjustable armrests
- 24 Volt lighter
- Beverage cup/can holder
- Bolt-on FOGS capability
- Bottle holder
- Bottom mounted, intermittent, parallel
 wiper and washer
- Coat hook
- Floor mat, washable, with storage
 compartment
- Full graphic and full color display
- Interior lighting with door switch
- Joysticks, pilot operated
- Laminated front windshield
- Left side console, tiltable, with
 lock-out for all controls
- Literature compartment behind seat
- Literature holder in right hand cab
 panel
- Mobile phone holder
- FM radio incl speakers
- Parking brake
- Sealed cab with positive filtered
 ventilation
- Power supply, 12V-10A
- Sliding door windows
- Steering column, adjustable angle &
 height
- Storage compartment suitable for a lunch
 box
- Sunshade for windshield and skylight
- Cruise control system
- Pin code type engine start prevention
- RHS and rear view camera (incl.lights)
 displayed on additional cab monitor

OTHER STANDARD EQUIPMENT

- BLCV including overload warning device
- SLCV
- VA booms include FLCV
- Automatic swing brake
- Capability to add auxiliary hydraulic
 circuits
- Caterpillar datalink and electronic
 technician capability
- Door locks and cab locks with
 Caterpillar one-key security system
- SOS quick sampling valves for engine
 oil, hydraulic oil and coolant

CATERPILLAR MACHINE PRICE LIST

M318F

M318 HYDRAULIC WHEEL EXCAVATOR GRENOBLE, FRANCE	Ship Weight lbs	LIST PRICE AT DEALER
--	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management program.
 Please only use Lane 2 when placing orders that are part of the Base
 Order Management Program.**

**2018 YOY list price reductions will be offset by reductions
 in discounts or merchandising support.**

512-3079	M318F WHL HEX AM-N DCA3 0 LANE 1 - AVAILABLE FROM BALTIMORE PDC	\$300,800
----------	---	------------------

Versatility for contractors and county work:
 Blade front, stabilizers rear, VA boom, 8'6" stick, high &
 medium pressure and pin grabber lines, tool control,
 joystick steering , 315 linkage compatible.

The following attachments MUST be selected from Lane 1
 Mandatory section : 0P9001 , 0G9240 .
 Undercarriage attachments are welded on and are therefore
 permanent part of the lower frame. It is not possible to
 add/remove or to change any outrigger or blade undercarriage

- INCLUDES:
- 501-3120 M318F WHEEL EXCAVATOR
 - 503-4942 BOOM, VA, A-LUBE
 - 503-2177 STICK, 2.6M , A-LUBE (8'6")
 - 423-0706 UC BLADE FRONT/ OUT.REAR
 - 373-6030 SEAT COMFORT W/51 MM SEAT BELT (2")
 - 489-2995 CAB, 70/30
 - 374-5098 WIPER, 70/30
 - 474-7221 TIRES, MITAS 10.00-20 DUAL
 - 123-4968 PIN, BUCKET, ADJ
 - 383-3964 PEDAL, HPF/HAMMER
 - 422-9762 BEACON, ROTATING, REMOVABLE
 - 423-0582 COUNTERWEIGHT, 3900 KG (8600 LBS)
 - 423-0667 BLCV, VA & OFFSET
 - 425-0170 SPEED 35 KPH (21.7 MPH)
 - 431-9304 CONTROL, JOYSTICK STEERING
 - 432-6342 COOLING SYSTEM, STANDARD
 - 432-8600 HYDRAULIC OIL, MINERAL
 - 454-2156 STEPS, UC
 - 459-6004 PRODUCT LINK, CELLULAR PL641
 - 473-2982 DECALS, NORTH AMERICA (ANSI)
 - 491-1065 MIRROR, VA/MH
 - 491-8396 LIGHTS, LED
 - 492-8468 CONTROLLER, ELECTRONIC XL
 - 494-0903 SETTING, QC CTRL, PIN GRABBER
 - 497-1005 JOYSTICK, 1-SLIDER
 - 505-5366 ALARM, BACK-UP
 - 506-7504 CONTROL, 1PC & VA
 - 509-9862 JOYSTICK PATTERN, CHANGEABLE

NOTE: Please refer to the Lane 1 section to complete your order.

CATERPILLAR MACHINE PRICE LIST

M318F

M318 HYDRAULIC WHEEL EXCAVATOR GRENOBLE, FRANCE	Ship Weight lbs	LIST PRICE AT DEALER
--	--------------------	-------------------------

501-3120	M318F WHEEL EXCAVATOR 0 LANE 2 - AVAILABLE FROM GRENOBLE FACTORY LANE 3 - AVAILABLE FROM GRENOBLE FACTORY AVAILABLE FOR: AM-N, EU, ISRAEL, ANZ-A	\$213,800
-----------------	--	------------------

0G-0390	M318F MISCELLANEOUS MATERIAL 0 AVAILABLE FROM GRENOBLE FACTORY	NC
----------------	--	-----------

Only reference numbers that have the text
 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a Misc order.

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------------------	-------------------------

NOTE

IF NO REFERENCE NUMBER IS LISTED, LANE 1 CONFIGURATION IS NOT AVAILABLE .

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION for DCA

0P-9001	LANE 1 ORDER	0		NC
	ONLY FOR USE WITH: Distribution Center Arrangements (DCA) from PDC			
0G-9240	COMPLETE STORAGE PROTECTION	0		\$377 NET
	Includes CILIX and foam protection on all cylinders			
	Machines from the factory have been sprayed with Fluid Film TM.			
	This product is added for corrosion protection while shipping			
	and for extended storage periods. This product will need to be power			
	washed with soapy water prior to shipment to the customer.			
	Cilix AND foam protection on all cylinders are also included			
	in this storage protection procedure.			
	Includes operator protections in cab			
	Required for: Shipping by sea from Grenoble France			
	Recommended for: all type of long distance shipment			

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0		NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.			
OP-9003	LANE 3 ORDER	0		NC

BOOMS, STICKS, AND LINKAGES

BOOM ARRANGEMENTS

Includes:

Cab controlled Automatic Lubrication System for front linkage and swing bearing.
 High pressure 2-way tool control circuit boom lines.
 Medium pressure auxiliary hydraulic circuit boom lines.
 CW & Pin Grabber Quick coupler control booms lines.

L	503-4077	BOOM, 1PC, A-LUBE	0	\$36,260
		Arrangements for standard Stick		
		Includes:		
		Cab controlled Automatic Lubrication System for front linkage and swing bearing.		
		High pressure 2-way tool control circuit boom lines.		
		Medium pressure auxiliary hydraulic circuit boom lines.		
		CW & Pin Grabber Quick coupler control booms lines.		
		One piece boom 5.05M / 16' 7"		
		ONLY FOR USE WITH: LANE 3 ONLY		
		CANNOT BE USED WITH: Drop nose stick		

L	503-4942	BOOM, VA, A-LUBE	0	\$39,470
		Arrangements for standard Stick		
		Includes:		
		Cab controlled Automatic Lubrication System for front linkage and swing bearing.		
		High pressure 2-way tool control circuit boom lines.		
		Medium pressure auxiliary hydraulic circuit boom lines.		
		CW & Pin Grabber Quick coupler control booms lines.		
		Two piece boom 5.2M / 17' 1"		
		CANNOT BE USED WITH: Drop nose stick		

STICK ARRANGEMENTS

L	503-2176	STICK, 7'10'', A-LUBE	0	\$14,450
		Includes:		
		Bucket linkage and cylinder.		
		High pressure auxiliary hydraulic circuit stick lines.		
		Medium pressure auxiliary hydraulic circuit stick lines.		
		with CVC type quick disconnect couplings		
		Quick coupler control stick lines.		
		Automatic Lubrication System stick lines.		
		ONLY FOR USE WITH: Boom Arrangement for standard sticks		

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

STICK ARRANGEMENTS (Cont.)

L	503-2177	STICK, 8'6", A-LUBE 0		\$14,750
		Includes: Bucket linkage and cylinder. High pressure auxiliary hydraulic circuit stick lines. Medium pressure auxiliary hydraulic circuit stick lines. with CVC type quick disconnect couplings Quick coupler control stick lines. Automatic Lubrication System stick lines. ONLY FOR USE WITH: Boom Arrangement for standard sticks CANNOT BE USED WITH: Two piece boom (offset)		

DROP NOSE STICKS WITHOUT BUCKET LINKAGE

Includes:
 High Pressure stick lines, operated by bucket circuit for tool open/close function.
 Medium pressure auxiliary hydraulic circuit stick lines for tool rotation.
 Automatic Lubrication System stick lines.
 CVC type quick disconnect couplings
 One grapple pin.

SMARTBOOM & RIDE CONTROL

The Ride Control feature improves operator comfort by reducing machine bouncing when travelling.
 Smartboom eases operations and improves operator comfort. It is useful and recommended for Hammering, Rock-cleaning and smooth leveling.

Includes:
 Boom lowering control device, reducing boom drift, and overload warning device, which signals a hydraulic overload with an acoustical warning in the cab.

Arrangements including Ride Control

L	423-0673	RIDE CONTROL, 1PC 0		\$4,290
		Arrangement including Ride Control & BLCV Note: Smartboom not included ONLY FOR USE WITH: One piece boom (1PC) LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick		
L	423-0670	RIDE CONTROL, VA 0		\$5,420
		Arrangement including Ride Control & BLCV Note: Smartboom not included ONLY FOR USE WITH: Two piece boom (VA) CANNOT BE USED WITH: Drop nose stick		

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

SMARTBOOM & RIDE CONTROL (Cont.)

L	423-0685	RC, 1PC INCL. SMARTBOOM 0		\$7,120
		Arrangement including Ride Control & BLCV Includes: Smartboom ONLY FOR USE WITH: One piece boom (1PC) LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick		
L	423-0682	RC, VA INCL. SMARTBOOM 0		\$8,230
		Arrangement including Ride Control & BLCV Includes: Smartboom ONLY FOR USE WITH: Two piece boom (VA) CANNOT BE USED WITH: Drop nose stick		

Arrangements without Ride Control

L	431-4766	BLCV, 1PC 0		NC
		Arrangements without Ride Control Note: Smartboom not included ONLY FOR USE WITH: One piece boom (1PC) LANE 3 ONLY		
L	423-0667	BLCV, VA & OFFSET 0		\$1,110
		Note: Smartboom not included ONLY FOR USE WITH: Two piece boom (VA & Offset)		

POWERTRAIN

TRAVEL SPEED

L	425-0166	SPEED 12.4 MPH 0		NC
		Travel speed 20kph / 12.4mph CANNOT BE USED WITH: Cooling Package Fine Mesh		
L	425-0170	SPEED 21.7 MPH 0		NC
		Travel speed 35kph / 21,7mph CANNOT BE USED WITH: Cooling Package Fine Mesh Solid Rubber Tires		
L	440-3561	SPEED 12.4 MPH, FINE MESH 0		NC
		Travel speed 20kph / 12.4mph ONLY FOR USE WITH: Cooling Package Fine Mesh		
L	440-3562	SPEED 21.7 MPH, FINE MESH 0		NC
		Travel speed 35kph / 21,7mph ONLY FOR USE WITH: Cooling Package Fine Mesh CANNOT BE USED WITH: Solid Rubber Tires		

UNDERCARRIAGE

UNDERCARRIAGE ARRANGEMENTS

NOTE: Undercarriage attachments are welded on and are therefore a permanent part of the machine. It is not possible to add or change dozer blade or outrigger attachments.

Axle width 2.5M / 8' 2"

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

UNDERCARRIAGE (CONT.)

UNDERCARRIAGE ARRANGEMENTS (Cont.)

L	423-0706	UC BLADE FRONT/ OUT.REAR 0 Includes: Welded undercarriage Outriggers rear Parallel blade front remote greasing (width: 2.55M / 8' 4") Standard Axle width 2.5M / 8' 2"		\$21,260
L	503-4255	UC BLADE FRONT / OUT. REAR, TR 0 Includes: Welded undercarriage Trailer Preparation(Bracket for trailer hook at outrigger,elec- trical & hydraulic ports at undrecarriage) Outriggers rear Parallel blade front remote greasing (width: 2.55M / 8' 4") Standard Axle width 2.5M / 8' 2"		\$28,170
L	423-0707	UC OUT.FRONT / BLADE REAR 0 Includes: Welded undercarriage Outriggers front Parallel blade rear remote greasing (width: 2.55M / 8' 4") Standard Axle width 2.5M / 8' 2"		\$21,960
L	423-0708	UC OUT. FRONT & REAR. 0 Includes: Welded undercarriage Outriggers front Outriggers rear Standard Axle width 2.5M / 8' 2"		\$26,030

Wide Axle Arrangements

Axle width 2.69M / 8' 10"

STEPS & FENDERS

L	454-2156	STEPS, UC 0 Uppercarriage access steps with integrated toolbox.		\$256
L	455-7169	STEPS, UC, INCL. FENDERS 0 Uppercarriage access steps with integrated toolbox. Includes: One set of four fenders reducing dirt and water spray from tires onto machine.		\$2,705

TIRES

DUAL TIRES

L	474-7221	TIRES, MITAS 10.00-20 DUAL 0 MITAS NB38, BIAS (DIAGONAL/CROSS PLY), PR16. Spacer rings are included.		\$1,820
L	478-6660	TIRES,MITAS EM23 10.00-20 DUAL 0 MITAS EM23, BIAS (DIAGONAL/CROSS PLY), PR16. Higher resistance to puncture and tread wear due to higher filling of tread area. Special tread pattern for stony and hard terrain. Spacer rings are included.		\$2,900

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

UNDERCARRIAGE (CONT.)

TIRES (Cont.)

L	474-7226	TIRES,SOLID RUB.10.00-20 DUAL 0 SOLID RUBBER Tires for industrial applications. Requires: 20kph / 12.4mph travel speed Spacer rings are included.		\$16,160
L	474-7236	TIRES,BRIDGEST.11.00-20 DUAL 0 BRIDGESTONE FG, PR16 (DIAGONAL/CROSS PLY) The FG's separate lugs are tapered for greater traction and self cleaning, resulting in an easier drive through heavy dirt and mud. Spacer rings are included. CANNOT BE USED WITH: Axles, wide		\$6,180

SINGLE TIRES

L	253-1634	TIRES,MICH.18R19.5 XF SINGLE 1,349 MICHELIN XF, 445/70R 19.5 Radial single tire with aggressive directional tread designed to deliver exceptional traction and performance.		\$6,580
---	----------	---	--	---------

HYDRAULICS

MEDIUM PRESSURE AUXILIARY HYDRAULIC CONTROLS

L	431-8614	CONTROL, MPF 0 Provides medium pressure circuit for tool rotation/tilt. ONLY FOR USE WITH: One piece boom (1PC) Two piece boom (VA)		\$1,280
L	431-9304	CONTROL, JOYSTICK STEERING 0 Provides medium pressure circuit for tool rotation/tilt. Enables steering of the machine while travelling in first gear by using the sliding switch on the right hand joystick. Includes: Auxiliary medium pressure control circuit ONLY FOR USE WITH: One piece boom (1PC) Two piece boom (VA)		\$3,395

OPERATOR ENVIRONMENT

CAB WINDSHIELD

L	486-0957	CAB, 1-PC 0 Fixed, one piece laminated glass windshield (10MM / 0.4", EN356 P5A) Laminated glass top window (10MM / 0.4", EN356 P5A). Tempered glass side & rear windows.		NC
L	489-2995	CAB, 70/30 0 Openable, 70/30 split, laminated glass windshield (Tempered glass lower window 4MM / 0.16" Laminated glass upper window 7MM / 0.28") Laminated glass top window and tempered glass side and rear windows.		NC

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

WINDSHIELD WIPER

L	374-5097	WIPER, 1-PC	0	NC
		ONLY FOR USE WITH: 1-PC windshield		
L	374-5098	WIPER, 70/30	0	NC
		ONLY FOR USE WITH: 70/30 windshield		

SEATS & SEAT-BELTS

Comfort Seat

L	373-6030	SEAT COMFORT W/2" SEAT BELT	0	\$830
		Includes: 2"/51mm retractable seat belt The Comfort Seat features vertical air suspension (low-frequency), horizontal suspension, automatic weight adjustment, mechanical lumbar support, passive climate system, seat cushion length and angle adjustment and a seat heater		
L	393-1386	SEAT COMFORT W/3" SEAT BELT	0	\$830
		Includes: 3"/76mm retractable seat belt The Comfort Seat features vertical air suspension (low-frequency), horizontal suspension, automatic weight adjustment, mechanical lumbar support, passive climate system, seat cushion length and angle adjustment and a seat heater		

Deluxe Seat

L	377-4501	SEAT DELUXE W/2" SEAT BELT	0	\$2,495
		Includes: 2"/51mm retractable seat belt The Deluxe Seat features vertical air suspension (low-frequency), horizontal suspension, automatic height & weight adjustment, active climate system (two step heating & body sweat removal), premium microfibre seat fabric, pneumatic lumbar support, seat cushion length and angle adjustment and adjustable dampening.		
L	393-1387	SEAT DELUXE W/3" SEAT BELT	0	\$2,495
		Includes: 3"/76mm retractable seat belt The Deluxe Seat features vertical air suspension (low-frequency), horizontal suspension, automatic height & weight adjustment, active climate system (two step heating & body sweat removal), premium microfibre seat fabric, pneumatic lumbar support, seat cushion length and angle adjustment and adjustable dampening.		

AUXILIARY HYDRAULIC PEDAL

L	261-3608	NO PEDAL	2	NC
		Floorboard cover required if HPF/Hammer pedal is not selected.		
L	383-3964	PEDAL, HPF/HAMMER	0	\$1,015
		HPF/Hammer Pedal allows secondary operation of auxiliary high pressure control circuit in addition to the standard slider control on the right joystick. CANNOT BE USED WITH: Drop nose stick		

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

HYDRAULIC JOYSTICK PATTERN

L	509-9862	JOYSTICK PATTERN, CHANGEABLE 0 Provides ability to change from the standard excavator joystick control pattern (SAE) for hydraulic functions to the backhoe joystick control pattern (ISO).		\$930
---	----------	--	--	-------

HYDRAULIC JOYSTICK

L	497-1005	JOYSTICK, 1-SLIDER 0 Provides standard joysticks with 1 slider and 4 buttons.		NC
L	488-1890	JOYSTICK, 2-SLIDER 0 Provides enhanced joysticks with 2 sliders and 5 buttons.		\$1,245

CONTROL MAIN VALVE

SELECT ONE

L	506-7504	CONTROL, 1PC & VA 0 Implement Control Valve including 2-way tool control. ONLY FOR USE WITH: Boom Arrangements for standard sticks		NC
---	----------	--	--	----

CONTROLLERS

L	337-5820	CONTROLLER, ELECTRONIC 0 Provides a control unit to activate and control electrical functions of hydraulic components. CANNOT BE USED WITH: Offset Boom, Ride Control, Joystick Steering 2nd High Pressure Control, Smartboom		NC
L	492-8468	CONTROLLER, ELECTRONIC XL 0 Provides a control unit to activate and control electrical functions of hydraulic components. ONLY FOR USE WITH: Offset Boom, Ride Control, Joystick Steering 2nd High Pressure Control, Smartboom		NC

TECHNOLOGY PRODUCTS

PRODUCT LINK COMMUNICATIONS

Product Link enables the remote transmission of information about the the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country. Please contact your Cat marketing representative with questions.

L	459-6004	PRODUCT LINK, CELLULAR PL641 0 Product Link Pro series PL641 uses UMTS and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

PRODUCT LINK COMMUNICATIONS (Cont.)

L	459-6005	PRODUCT LINK, SATELLITE PL631 0		\$432
		Product Link Pro series PL631 uses satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		

SAFETY AND SECURITY

LIGHTING / CAB GUARD

Provides led type cab working lights

L	491-8396	LIGHTS, LED 0		NC
		Provides LED type cab working lights Includes cab rain visor. Without Cab Guard		

Arrangements Including Cab Guard

L	491-8397	FOGS, LED 0		\$4,740
		Provides LED type cab working lights. Includes cab guards front and roof.		

MIRRORS

L	489-4672	MIRROR, ELECTRIC, VA/MH 0		\$990
		Provides rearview mirrors on cab and on RH side of machine. Heated Mirrors adjustable from Cab ONLY FOR USE WITH: VA/Offset		
L	489-4673	MIRROR, ELECTRIC, 1PC. 0		\$990
		Provides rearview mirrors on cab and on RH side of machine. Heated Mirrors adjustable from Cab ONLY FOR USE WITH: LANE 3 ONLY One piece booms		
L	491-1065	MIRROR, VA/MH 0		NC
		Provides rearview mirrors on cab and on RH side of machine. ONLY FOR USE WITH: Two piece booms (VA & Offset)		
L	491-1066	MIRROR, 1PC. 0		NC
		Provides rearview mirrors on cab and on RH side of machine. ONLY FOR USE WITH: LANE 3 ONLY One piece booms		

COOLING

COOLING PACKAGE

L	432-6342	COOLING SYSTEM, STANDARD 0		NC
L	432-6346	COOLING SYSTEM, FINE MESH 0		\$905
		Provides improved protection to the radiator, the ATAAC, the A/C condenser to prevent clogging, when working with the machine in dusty environments. Includes an additional engine air pre-cleaner.		

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FRAMES

COUNTERWEIGHTS

L	423-0581	COUNTERWEIGHT, 7496 LBS	0	\$675
		Standard Counterweight 3400KG / 7450LBS		
L	423-0582	COUNTERWEIGHT, 8600 LBS	0	\$775
		Heavy Counterweight 3900KG / 8600LBS		
		Recommended for use with: Two piece boom and blade only undercarriage arrangements		

FLUIDS

LUBRICATIONS

L	432-8600	HYDRAULIC OIL, MINERAL	0	NC
		Filling with Cat HYDO Advanced 10 oil		

INSTRUCTIONS

INTERNATIONAL INSTRUCTIONS

SELECT ONE:

L	473-2982	DECALS, NORTH AMERICA (ANSI)	0	NC
---	----------	--	---	----

PACKING

EXPORT PACKING

SELECT ONE:

	0G-9240	COMPLETE STORAGE PROTECTION	0	\$377 NET
		Includes CILIX and foam protection on all cylinders		
		Machines from the factory have been sprayed with Fluid Film TM.		
		This product is added for corrosion protection while shipping		
		and for extended storage periods. This product will need to be power		
		washed with soapy water prior to shipment to the customer.		
		Cilix and foam protection on all cylinders are also included		
		in this storage protection procedure.		
		Includes operator protections in cab		
		Required for: Shipping by sea from Grenoble France		
		Recommended for: all type of long distance shipment		

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

UNDERCARRIAGE

UNDERCARRIAGE ATTACHMENTS

L	538-2520	BRACKET, WIDE AXLE FENDERS 0		NC
		Provides adapters to align steps with outside of tires of Wide Axle Undercarriage Arrangements. REQUIRED BY : Fenders if axle wide ONLY FOR USE WITH: 455-7169 & 423-0710 or 423-0709		

HYDRAULICS

SECOND HIGH PRESSURE HYDRAULIC CIRCUIT CONTROL GROUP

Provides additional two way high or medium pressure function for worktools requiring additional hydraulic circuits for tilting or rotating, such as tilt-rotators.
Must order control and stick lines to complete auxiliary circuit.
REQUIRES 2- Slider Joystick

If CAT TILTROTATOR SUPPORT is selected ,2ND HPF Control will be optimized for usage with a Cat Tiltrotator.In this case only one way flow with minimized return line back pressure will be provided

L	507-1390	CONTROL, 2ND HPF, 1PC 0		\$6,000
		Second high pressure control valve. ONLY FOR USE WITH: One piece boom & 2 slider joystick LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick		
L	507-1391	CONTROL, 2ND HPF, VA 0		\$5,690
		Second high pressure control valve. ONLY FOR USE WITH: Two piece boom (VA)& 2 slider joystick CANNOT BE USED WITH: Drop nose stick		

Second High Pressure Hydraulic Circuit Stick Lines

Must order stick lines to complete auxiliary circuit.

L	254-2610	LINES, 2ND HPF, 7'10" STICK 24		\$765
		Second high pressure lines for stick 2.4M / 7' 10". REQUIRED BY: CONTROL 2ND HPF		
L	254-2611	LINES, 2ND HPF, 8'6" STICK 29		\$835
		Second high pressure lines for stick 2.6M / 8' 6". REQUIRED BY: CONTROL 2ND HPF		

Couplings Circuit

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

HYDRAULICS (CONT.)

SECOND HIGH PRESSURE HYDRAULIC CIRCUIT CONTROL GROUP (Cont.)

P	176-6765	COUPLING, QUICK DISC MPF DC 2 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" Provides a set of two adapters (CVC type coupling to internal thread M22 x 1.5) for stick lines medium pressure, side (bucket tilt)		\$335 NI
---	----------	---	--	----------

Quick Coupler Control Settings

L	494-0903	SETTING, QC CTRL, PIN GRABBER 0 Provides control strategy and pressure settings appropriate for Cat Pin Grabber quick coupler. CANNOT BE USED WITH: Drop nose stick, CW-type quick coupler, CAT tilt rotator support		NC
L	501-6515	CAT TILTROTATOR SUPPORT 0 Activation of cat tilt rotator support Includes modification of 2nd HPF Control to provide only one way flow with minimized return line back pressure. ONLY FOR USE WITH: CONTROL, 2ND HPF and 2-SLIDER JOYSTICK CANNOT BE USED WITH: SETTING, QC CTRL, PIN GRABBER		\$2, 670

ELECTRICAL

ALARM

L	505-5366	ALARM, BACK-UP 0 REQUIRED BY: USA & Canada dealers Acoustical warning signal when moving the machine .		\$735
---	----------	--	--	-------

SAFETY AND SECURITY

BEACON

L	422-9762	BEACON, ROTATING, REMOVABLE 0 Orange beacon light with cable and magnet foot.		\$295
---	----------	--	--	-------

MACHINE SECURITY SYSTEM

L	422-9723	SECURITY SYSTEM, MACHINE 0 Advanced, programmable system to manage access to machine. Requires special Machine Security System keys. Machine shipped with system inactive but with two of these keys already programmed into system. Requires Caterpillar Service Tool Electronic Technician (ET) to activate and to program system for additional keys. Additional keys available through Parts Distribution.		\$1, 410
---	----------	---	--	----------

CATERPILLAR MACHINE PRICE LIST

M318F

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BUCKETS

BUCKET RETENTION PINS

Note: PIN, BUCKET, TDP bucket retention pins are not compatible with pin-on CAT Tilt-Rotator System (TRS) models. If the machine will be equipped with a pin-on TRS model please select PIN, BUCKET, ADJ.

P	123-4968	PIN, BUCKET, ADJ	68	\$362
			68	\$362 NI

"ALSO AVAILABLE ON A MISCELLANEOUS ORDER"
 CANNOT BE USED WITH: Drop nose stick

EXCAVATION BUCKETS (CW Coupler Buckets)

These buckets cannot be ordered with MISC Material Order. Dealers in AM-N can place miscellaneous bucket orders by consulting Cat Work Tools at 1-800- 255-2372 for bucket options, availability and appropriate ordering instructions.

FIELD INSTALLED ATTACHMENTS

KITS FOR FIELD INSTALLATION

Please contact Product Group if further details are required.

L	473-7060	KIT, CAB GUARD, FOGS	0	\$4,885 NI
		Provides cab guards front and top for field installation. " AVAILABLE ON A MISCELLANEOUS ORDER"		
L	487-0165	KIT, COOLING, WASTE HANDLING	0	\$9,060 NI
		Provides reversible fan and radiator screen vibration functionality to prevent radiator clogging in dusty environments. Includes engine air precleaner. " AVAILABLE ON A MISCELLANEOUS ORDER"		

PACKING

EXPORT PACKING

0G-3565	PACKING -SEA/TRUCK MISC.MATER..	0	\$217 NET
	ONLY FOR USE WITH: only with Not installed Misc.Mater (Ni)		
0G-3561	PACKING - SEA/TRUCK BH BUCKET	0	\$283 NET
	ONLY FOR USE WITH: Only with Not installed bucket (Ni)		