



November 2, 2018

## PRODUCT AND PRICING BULLETIN

NEW HOLLAND BRAND PRODUCTS, U.S. NO. 18-57A

### NEW HOLLAND DEALERS WITH MRT AGREEMENT

SUBJECT: **WORKMASTER™ 55, 65 & 75 SERIES: UPDATE EFFECTIVE 11/2/2018**

The WORKMASTER 55, 65 and 75 Series tractors that were announced in a Product and Pricing Bulletin in July of this year provided a new opportunity for New Holland growth in the utility tractor market. Thank you for your support, thus far, for this new series. In order to continue the growth, we are pleased to provide additional enhancements to the product offering:



- 19.5L24 R4 rear and 12.5/80-18 R4 front industrial tires
- Front and rear shipping wheels
- Horizontal exhaust for the WORKMASTER 75 ROPS

These new options expand the utilitarian nature of this WORKMASTER series. The R4 industrial tires provide a less aggressive tread design for customers who want to be more gentle with their turf or who want a longer-lasting tread design on hard surfaces. The shipping wheel option enables you to tailor the tires to your customer's needs in the event that they would like a turf tire or any other special tire or tread pattern. The horizontal exhaust makes the ROPS to the tallest point of an open station tractor, enabling you to easily enter garages and buildings with the standard eight foot tall entry ways. The horizontal exhaust also helps to direct the exhaust down and away from the operator for those who are more comfortable with a horizontal exhaust.

New Holland continuously strives to provide products to suit the needs of your customers. To stay competitive in the marketplace, review the customer segments in your primary market of responsibility, ensuring that you have a complete and thorough mix of these products.

This bulletin and the price pages may be accessed via the Dealer Portal if you have the MRT agreement with New Holland. Log on to the Dealer Portal. With the "Wholegoods" button displayed, click on "Pricing," click on "Tractors," and then click on "WORKMASTER Series." The latest published items will appear at the top of the list.

Christine Chleboun  
Director, Commercial Marketing  
New Holland, North America

Dan Valen  
Director, Product Marketing  
New Holland, North America

Attachment



## WORKMASTER™ Series Tractor Index

<b><u>EQUIPMENT DESCRIPTION</u></b>	<b><u>LATEST REVISION</u></b>	<b><u>PAGE NUMBER</u></b>
<u>Index</u>	11/02/18	1
<u>Models</u>		
WORKMASTER 55, 65, 75 Cab	11/02/18	2
WORKMASTER 75 ROPS	11/02/18	8
WORKMASTER 55, 65, 75 Special Order	11/02/18	14



**WORKMASTER 55, 65, 75 CAB  
US PRICE LIST**

## Standard Equipment

The Workmaster Utility tractors from New Holland are the perfect combination of basic value, comfort, and features with the visibility to ensure you are productive in all your chores.

Value Utility Target Customers:

Lifestyler / Weekender

Who are they?

Small land-owners, who are owner-operators engaged in farming as a lifestyle

Why do they buy?

- Comfortable operator area
- Simple, easy to operate
- Low price tag

Mixed Beef / Cow/Calf

Who are they?

Owner-operator farmers engaged in mixed farming (haying or grain farming with a Beef or Cow/Calf herd) for income

Why do they buy?

- Comfortable operator area
- Low cost of ownership
- Good visibility

Small Livestock

Who are they?

Owner-operator farmers engaged in raising livestock herds for additional income

Why do they buy?

- Comfortable operator area
- Low cost of ownership
- Reliability

Key Features:

4 post cab (316 degrees visibility)



Instructor seat



Factory Installed Loader



Cab, 4WD, power shuttle configuration





**WORKMASTER 55, 65, 75 CAB  
US PRICE LIST**

**Standard Equipment**

Workmaster 55  
54 Gross Engine hp  
40 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

Workmaster 65  
64 Gross Engine hp  
50 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

ALL MODELS:  
Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

TRANSMISSION:  
LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

STEERING/BRAKES:  
Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:  
Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

REAR AXLE  
Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

HYDRAULIC SYSTEM:  
Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(2) Open Center Remote Valves with  
Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:  
Mechanically Engaged

PTO:  
Fully Independent  
Flip-up PTO Shaft Guard  
4WD power shuttle:  
-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:  
Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends



**WORKMASTER 55, 65, 75 CAB  
US PRICE LIST**

**Standard Equipment**

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

**INSTRUMENTATION:**

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

**CAB LIGHTING:**

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

**OPERATOR PROTECTIVE STRUCTURE:**

**CAB MODELS**

ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, front wiper  
and washer, rear wiper and washer,  
two doors with locks, two external  
mirrors, hinged rear window (opens  
completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

**TIRES:**

11.2x24 R1 Front  
16.9X30 R1 Rear

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:**

**550LU NON SELF-LEVELING**

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach

**555LU MECHANICAL SELF-LEVELING**

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach



**WORKMASTER 55, 65, 75 CAB  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab		9037777P74	\$48,433.00
WORKMASTER 65 T4A	Cab		9039724P62	\$50,929.00
WORKMASTER 75 T4A	Cab	6,239 LB	9041671P50	\$53,425.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**OPERATOR PLATFORM**

SD\_T9200 OPERATOR STRUCTURE #1

	333606	CAB FIX SCREEN OPEN <b>Cab with openable high visibility panel</b>		9000283P92	\$364.00
--	--------	---	--	------------	----------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

	8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
	8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000507P00	\$650.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000234P00	\$300.00



**WORKMASTER 55, 65, 75 CAB  
US PRICE LIST**

**HYDRAULICS**

REAR REMOTES

SD\_T8270 REAR REMOTES

	335640	3 REMOTE VALVE 3 rear remote valves  Float, Detent and kickout on 2nd and 3rd remotes		9000608P40	\$780.00
--	--------	--	--	------------	----------

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344743	LOADER-NSL-2F-EU-WGG 550LU Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344738	LOADER-MSL.2F.SSLWGG 555LU Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000831P48	\$1,066.00
	344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000831P48	\$1,066.00



**WORKMASTER 55, 65, 75 CAB  
 US PRICE LIST**

**3-POINT HITCH**

REAR 3 POINT HITCH

SD\_T8200 HITCH

		332785	MDC Hitch aux lift ram <b>1 Auxiliary lift ram = 4,000 lbs total lift capacity</b>		9000344P76	\$442.00
--	--	--------	---	--	------------	----------

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000462P54	\$593.00
--	--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------





**WORKMASTER 75 ROPS  
US PRICE LIST**

**Standard Equipment**

The Workmaster Utility tractors from New Holland are the perfect combination of basic value, comfort, and features with the visibility to ensure you are productive in all your chores.

Key Features:

Flat deck platform



Ergonomic right hand console



Value Utility Target Customers:

Lifestyler / Weekender

Who are they?

Small land-owners, who are owner-operators engaged in farming as a lifestyle

Why do they buy?

- Comfortable operator area
- Simple, easy to operate
- Low price tag

Mixed Beef / Cow/Calf

Who are they?

Owner-operator farmers engaged in mixed farming (haying or grain farming with a Beef or Cow/Calf herd) for income

Why do they buy?

- Comfortable operator area
- Low cost of ownership
- Good visibility

Factory Installed Loader



Small Livestock

Who are they?

Owner-operator farmers engaged in raising livestock herds for additional income

Why do they buy?

- Comfortable operator area
- Low cost of ownership
- Reliability

ROPS, 4WD, power shuttle configuration





**WORKMASTER 75 ROPS  
US PRICE LIST**

**Standard Equipment**

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

REAR AXLE  
Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(2) Open Center Remote Valves with  
Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent  
Flip-up PTO Shaft Guard  
4WD power shuttle:  
-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)



**WORKMASTER 75 ROPS  
US PRICE LIST**

**Standard Equipment**

**INSTRUMENTATION:**

Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake  
Gauges for fuel level, engine temperature and tachometer  
Digital Readout for PTO speed, ground speed, battery & hours

**ROPS LIGHTING:**

Front: (2) Halogen Headlights  
Rear: (1) Right hand fender mounted worklights  
Turn Signals/Flashers/Rear Lights

**OPERATOR PROTECTIVE STRUCTURE:**

**ROPS MODELS**

2-Post Foldable ROPS with ISO-mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl mechanical suspension, operator's presence sensor, retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

**TIRES:**

11.2x24 R1 Front  
16.9X30 R1 Rear

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:**

**550LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45 deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach

**555LU MECHANICAL SELF-LEVELING**

Maximum Lift Height @ pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45 deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach



**WORKMASTER 75 ROPS  
US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9035628P06	\$45,677.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

	8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
	8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000507P00	\$650.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000234P00	\$300.00

**HYDRAULICS**

REAR REMOTES

SD\_T8270 REAR REMOTES

	335640	3 REMOTE VALVE <b>3 rear remote valves</b>  <b>Float, Detent and kickout on 2nd and 3rd remotes</b>		9000608P40	\$780.00
--	--------	--	--	------------	----------



**WORKMASTER 75 ROPS  
 US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344743	LOADER-NSL-2F-EU-WGG <b>550LU</b> Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344738	LOADER-MSL.2F.SSLWGG <b>555LU</b> Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000831P48	\$1,066.00
	344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000831P48	\$1,066.00

**ENGINE**

MUFFLERS

SD\_T1510 ENGINE EXHAUST

	330150	Horizontal exhaust w/ guard <b>WORKMASTER 75 ROPS ONLY</b>		9000117P00	\$150.00
--	--------	---	--	------------	----------



**WORKMASTER 75 ROPS  
 US PRICE LIST**

**3-POINT HITCH**

REAR 3 POINT HITCH

SD\_T8200 HITCH

		332785	MDC Hitch aux lift ram <b>1 Auxiliary lift ram = 4,000 lbs total lift capacity</b>		9000344P76	\$442.00
--	--	--------	---	--	------------	----------

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

		330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000462P54	\$593.00
--	--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

		330986	Spanish Operators Manual			No Charge
--	--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

		330982	French Operators Manual			No Charge
--	--	--------	-------------------------	--	--	-----------



**WORKMASTER 55, 65, 75 SPECIAL ORDER  
 US PRICE LIST**

**Standard Equipment**

Special Custom Order Options

Requires YSR, YRT or YGR order codes.

Please place an order in the system with the configuration as close as possible to your desired configuration and then contact Dealer Sales Support with the following information to get the order configuration changed:

1. Vehicle Number(s)
2. Order Code(s) desired for each vehicle number

The orders will then be sent to have the order configurations changed to include your desired order code(s).

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**OPERATOR PLATFORM**

SD_T8520 INSTRUCTIONAL SEAT				
	390865	Less Instructional Seat <b>Removes instructor seat option from Cab Models</b>  <b>Instructor seat CANNOT be installed as a Dealer Installed Accessory</b>	(900405P60)	(\$520.00)



**WORKMASTER 55, 65, 75 SPECIAL ORDER  
 US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

		391489	Less Loader Bracket <b>No Loader</b>  Removes mid mount valve, loader & bucket		(905807P88)	(\$7,446.00)
--	--	--------	---	--	-------------	--------------

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

		330183	FRONT WEIGHT 8X30KG Front weight carrier (42 lbs) + 8 front weights (66 lbs) = 572 lbs  <b>NOT COMPATIBLE with front loader</b>		9000794P82	\$1,019.00
--	--	--------	--	--	------------	------------